



Multicat by Bay-lynx MC15

THE ONLY MACHINE THAT WILL SPREAD BOTH TOPSOIL & AGGREGATE

In minutes, one operator can unload and spread material in diffi cult, 'hard to reach' areas. Used by quarry operators, haulers, landscapers, contractors, and many others.

Advantages

- Patented Load Suspension Beam
- Lowest Centre of Gravity in the Market
- Can spread material up to 100' from rear of truck
- Ability to Control unloading (front to rear) or opposite
- Constantly throws aggregate, mulch, soil, sand, etc.
- Slinging costs lower than manual labor

Features

- Full control of Patented Load Suspension Beam
- Variable Speed Conveyor Controls
- Ability to break clumps / no bridging
- Plastic liner inside box to help load release

Options

- Wireless Radio Remote, Spreader & Chassis
- Electric Flop Tarp c/w Aluminum Arms
- Super Shield™, Friction and/or Power Drive
- Aluminium Fenders
- Planetary Drive Swing Frame
- Additional Customizations/Options Available

Main Conveyor

Removable for ease of belt replacement

- 21" wide x 20' long
- Horizontal rollers with UHMW troughing strips
- Variable speed 0-240 fpm approximately
- Endless, rubber back belt
- Direct drive hydraulic motor

Throw Conveyor

Super shield attachment with friction or power drive

- 14" wide x 19' long
- 35 degree troughing idlers
- Endless belt with raised chevron pattern
- Dual racking swing frame
- Option to full rotation planetary drive
- Stainless steel pressure lines
- Temperature controlled oil cooler

Capacity: 14 cubic yards

Hydraulic System and Controls

- Standard upper operating platform
- Mechanical valves standard with options to full radio remote
- Super heavy duty PTO
- Vickers Vane tandem pump

Box Construction

- Full plastic hopper liner
- 4 way interior load suspension beam
- Formed plate sides with box-style columns
- Temperature controlled oil cooler

Minimum Platform Dimensions

- MC15 - 222"

