



**Multicat** by Bay-lynx **MC17**

**THE ONLY MACHINE THAT WILL SPREAD BOTH TOPSOIL & AGGREGATE**

In minutes, one operator can unload and spread material in diffi cult, 'hard to reach' areas. Used by quarry operators, haulers, landscapers, contractors, and many others.

**Advantages**

- Patented Load Suspension Beam
- Lowest Centre of Gravity in the Market
- Can spread material up to 100' from rear of truck
- Ability to Control unloading (front to rear) or opposite
- Constantly throws aggregate, mulch, soil, sand, etc.
- Slinging costs lower than manual labor

**Features**

- Full control of Patented Load Suspension Beam
- Variable Speed Conveyor Controls
- Ability to break clumps / no bridging
- Plastic liner inside box to help load release

**Options**

- Wireless Radio Remote, Spreader & Chassis
- Electric Flop Tarp c/w Aluminum Arms
- Super Shield™, Friction and/or Power Drive
- Aluminium Fenders
- Planetary Drive Swing Frame
- Additional Customizations/Options Available

**Main Conveyor**

Removable for ease of belt replacement

- 21" wide x 20' long
- Horizontal rollers with UHMW troughing strips
- Variable speed 0-240 fpm approximately
- Endless, rubber back belt
- Direct drive hydraulic motor

**Throw Conveyor**

Super shield attachment with friction or power drive

- 14" wide x 19' long
- 35 degree troughing idlers
- Endless belt with raised chevron pattern
- Dual racking swing frame
- Option to full rotation planetary drive

**Capacity:** 15 cubic yard

**Hydraulic System and Controls**

- Standard upper operating platform
- Mechanical valves standard with options to full radio remote
- Super heavy duty PTO
- Vickers Vane tandem pump
- Stainless steel pressure lines
- Temperature controlled oil cooler

**Box Construction**

- Full plastic hopper liner
- 4 way interior load suspension beam
- Formed plate sides with box-style columns

**Minimum Platform Dimensions**

- MC17 - 248"

