

TROLLER Consisting of 7 value-oriented models: the four tiller and three side console TROLLER models continue to cover the performance and value equation. Our TROLLER models bring quality features in a smaller package. The console models feature a fiberglass console. All TROLLER models offer great performing hulls with molded-in spray rails for a dry ride and truly great handling. TROLLERS feature a list of standard features and available options that make them capable performance fishing machines. Powered with an outboard ranging from 25 to 60 HP, depending on model, they will offer unmatched performance and value for years to come.



FEATURES		140T	145T	145SC	165T	165SC	167T	167SC
Accessories	Transom Handles	●						
	Deck Hardware		●	●	●	●	●	●
	Battery Tray/Box	●	●	●	●	●	●	●
	Bilge Pump	●	●	●	●	●	●	●
Electrical	12V Bow Trolling Receptacle	●	●	●	●	●	●	●
	Switches w/Fuses	●	●	●	●	●	●	●
Instruments	Volt			●		●		●
	Tachometer			✓		✓		✓
	Speedometer			●		●		●
Storage	Rod Holders		●	●	●	●	●	●
	Rod Locker		6.5"	6.5"	7.5"	7.5"	8.5"	8.5"
	Bow	●	●	●	●	●	●	●
Livewells	60 Qt. Aerated Livewell (32"L x 10"W x 12"D)	●						
	50 Qt. Aerated Livewell (30"L x 13"W x 8"D)		●	●	●	●	●	●
General Features	Seating							
	Pedestal Bases	2	3	4	4	5	4	5
	Removable Locking Seats	2	2	2	2	2	2	2
	Navigational Lighting	●	●	●	●	●	●	●
	Cockpit Floor Vinyl	●	●	●	●	●	●	●
	Fiberglass Console					●		●
	Level Flotation	●	●	●	●	●	●	●

● Standard ✓ Optional

OPTIONS	140T	145T	145SC	165T	165SC	167T	167SC
Chrome Logo Upgrade	✓	✓	✓	✓	✓	✓	✓
Stainless Steel Cleats		✓	✓	✓	✓	✓	✓
Flip Up Cleats		✓	✓	✓	✓	✓	✓
Rear Casting Platform		✓	●	✓	●	✓	●
Removable Windshield			✓		✓		✓
Horn		✓	✓	✓	✓	✓	✓
Carpeted Cockpit Floor	✓	✓	✓	✓	✓	✓	✓
Oar Locks	✓						
Mooring Cover	✓		✓	✓	✓	✓	✓
Removable Seat w/Hrd	✓	✓	✓	✓	✓	✓	✓
Bimini Sun Top	✓	✓	✓	✓	✓	✓	✓
Livewell Recirculation Timer		✓	✓	✓	✓	✓	✓
Stereo AM/FM/Bluetooth		✓	✓	✓	✓	✓	✓
Steering Wheel Upgrade			✓		✓		✓
Bilge Pump w/Auto Float Switch	✓	✓	✓	✓	✓	✓	✓



MODEL SPECS	140T	145T	145SC	165T	165SC	167T	167SC
Length	14' 2"	14' 6"	14' 6"	16' 0"	16' 0"	16' 7"	16' 7"
Beam	64"	70"	70"	70"	70"	76"	76"
Bow Depth	30"	30½"	30½"	30½"	30½"	35"	35"
Transom Height	20"	20"	20"	20"	20"	20"	20"
BIA Max. H.P.	25 HP	30 HP	30 HP	40 HP	40 HP	60 HP	60 HP
BIA Capacity/Persons	920#/4	897#/4	890#/4	989#/4	979#/4	1293#/6	1287#/6
Approx. Weight	340#	540#	575#	625#	660#	715#	745#
Alum. Side Thickness	.063	.080	.080	.080	.080	.080	.080
Alum. Bottom Thickness	.063	.080	.080	.080	.080	.080	.080

US Coast Guard / NMMA Specifications

MirroCraft by Northport Marine, LLC

P.O. Box 380 / Gillett, Wisconsin 54124 • Ph: 920-855-2168 • F: 920-855-6537 • Email: info@mirrocraft.com • www.mirrocraft.com