

GCT 3-14 +

CONSTRUCTION TELEHANDLERS



Key Features

- ✓ Multi-Function Joystick on Floating Armrest
- ✓ Automatic Parking Brake
- ✓ Polycarbonate Roof Window, FOPS Level 1
- ✓ Universal Skid Steer Attachment Quick Attach

Key Specifications

- ✓ Maximum Capacity of 2,650 lbs.
- ✓ Standard Machine GVW 6,400 lbs.
- ✓ 3 Steering Modes: 2-Wheel, 4-Wheel, Crab
- ✓ Super Compact: W 4' 11" | H 6' 4" | L 11'5"
- ✓ 35hp Yanmar Tier IV Final Engine
- ✓ Maximum Lift of 14' 1"

SPECIFICATIONS

		METRIC
Capacities	Max. capacity	1202 kg
	Max. lifting height	4.30 m
	Maximum outreach	2.62 m
	Reach at max. height	1 m
	Breakout force with bucket	1880 daN
Weight and dimensions	Shipping mass (min. / max.)	2700 kg / 2900 kg
	Ground clearance	0.29 m
	Wheelbase	2.13 m
	Overall length to carriage (with hitch)	3.47 m
	Overall length to carriage (without hitch)	3.47 m
	Front overhang	0.77 m
	Overall width	1.49 m
	Overall cab width	0.66 m
	Overall height	1.92 m
	Tilt-down angle	116 °
	Tilt-up angle	23 °
	External turning radius (over tyres)	2.62 m
Performances	Standard tires	CAMSO - MPT 552 - 10.0/75-15.3 124A8
	Lifting	8.80 s
	Lowering	7 s
	Extension	6.40 s
	Retraction	4.30 s
	Crowd	3.40 s
	Dump	2.60 s
Engine	Engine brand	Yanmar
	Engine norm	Stage V / Tier 4 Final
	Engine model	3TNV88C-DMU
	Number of cylinders - Capacity of cylinders	3 - 1642 cm³
	I.C. Engine power rating / Power	35.10 Hp / 26.20 kW
	Max. torque / Engine rotation	105 Nm @1950 rpm
	Drawbar pull (Laden)	2000 daN
	Reversible fan	Option
	Engine cooling system	3 radiators (water + hydraulic oil + fuel)
Transmission	HVO validated (according to EN 15940 standard)	Yes
	Transmission type	Hydrostatic
	Number of gears (forward / reverse)	2 / 2
	Max. travel speed (may vary according to applicable regulations)	25 km/h
	Differential lock	Limited slip differential on front and rear axles
	Parking brake	Automatic negative parking brake
Hydraulics	Service brake	Hydraulic servo brake
	Hydraulic pump type	Gear pump
	Hydraulic flow - Pressure	48 l/min - 235 bar
	Flow sharing distributor	Standard
Tank capacities	Hydraulic tank capacity	39 l
	Fuel tank	35 l
Noise and vibration	Noise at driving position (LpA) tested following NF EN 12053 norm	76 dB
	Noise to environment (LwA)	104 dB
	Vibration on hands/arms	< 2.50 m/s²
Miscellaneous	Cab certification	ROPS - FOPS cab (level 1)
	Controls	Joystick



STANDARD FEATURES

- Four Wheel Drive
- Crab mode
- Battery cut-off
- USB Plug
- Harmony screen - 5 in.
- Automatic parking brake
- 12Volt Power Port
- Document holder
- Connected machine
- Cabin Rops and fops level I

OPTIONAL FEATURES

- Attachment hydraulic line
- Air prefilter
- Stop & Start
- Air suspension fabric seat - GRAMMER
- Auto reversing fan
- LED work lights - On the top of the boom (fixed part) (x2)
- Continuous flow hydraulics
- Attachment hydraulic locking
- Air Conditioning

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT