

RS 4-14

CONSTRUCTION TELEHANDLERS



Key Features

- ✓ Four-wheel Drive/Four-Wheel Steer
- ✓ Universal Skid Steer Attach System Standard
- ✓ Manitou Quick Attach Optional

Key Specifications

- ✓ 4,400 lbs. (1996 kg) maximum lift capacity
- ✓ 14' 3" (4.35 m) maximum lift height
- ✓ 4,400 lbs. (1996 kg) lift capacity to 14' 3" (4.35 m)
- ✓ 56.3 hp (42 kW) Kubota diesel engine

SPECIFICATIONS

		METRIC
Capacities	Max. capacity	1995.81 kg
	Max. lifting height	4.34 m
	Maximum outreach	2.74 m
	Breakout force with bucket	1886 daN
Weight and dimensions	Overall length to carriage	3.64 m
	Length to face of forks	3.58 m
	Overall width	1.49 m
	Overall height	1.91 m
	Wheelbase	2.13 m
	Ground clearance	0.24 m
	Overall cab width	0.80 m
	Tilt-up angle	12 °
	Tilt-down angle	116 °
	External turning radius (over tyres)	3.07 m
	Unladen weight (with forks)	4190 kg
	Overall weight	4189.83 kg
Engine	Tires type	Pneumatic
	Engine brand	Kubota
	Engine norm	Stage V
	Engine model	2607-CR-E5
	Number of cylinders / Capacity of cylinders	4 - 2615 cm³
	I.C. Engine power rating - Power	56.30 Hp / 42 kW
	Max. torque / Engine rotation	174 Nm @ 2700 rpm
	Drawbar pull	2850 daN
	Drawbar pull (Laden)	2850 daN
	Transmission type	Hydrostatic
Transmission	Number of gears (forward / reverse)	2 / 2
	Max. travel speed	25 km/h
	Max. travel speed (may vary according to applicable regulations)	24.90 km/h
	Parking brake	Automatic Negative Hand-brake
	Service brake	Disk brake on the cadran shaft
	Axle Manufacturer	Dana
Hydraulics	Hydraulic pump type	Gear pump
	Hydraulic flow / Pressure	77.41 l/min-235 bar
Tank capacities	Engine oil	10.20 l
	Hydraulic oil	68.14 l
	Fuel tank	60 l
Miscellaneous	Steering wheels (front / rear)	2 / 2
	Drive wheels (front / rear)	2 / 2
	Safety / Cab certification	Standard EN 15000 / ROPS/FOPS
	Controls	Single Joystick FNR



Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT