

## Construction

<b>Imperial</b>	<b>SL-80</b>	<b>SL-80SS</b>
Frame	Powder coated steel	Stainless steel
Tank	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	12-volt direct-drive pump	12-volt direct-drive pump

<b>Metric</b>	<b>SL-80</b>	<b>SL-80SS</b>
Frame	Powder coated steel	Stainless steel
Tank	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	12-volt direct-drive pump	12-volt direct-drive pump

## Dimensions

<b>Imperial</b>	<b>SL-80</b>	<b>SL-80SS</b>
Approx. Weight (Empty)	60 lb	60 lb
Overall Length	48"	48"
Overall Height	33"	33"
Overall Width	28"	28"

<b>Metric</b>	<b>SL-80</b>	<b>SL-80SS</b>
Approx. Weight (Empty)	27.2 kg	27.2 kg
Overall Length	121.9 cm	121.9 cm
Overall Height	83.8 cm	83.8 cm
Overall Width	71.1 cm	71.1 cm

## Electrical

<b>Imperial</b>	<b>SL-80</b>	<b>SL-80SS</b>
Wiring Harness	Integral harness with molded plugs for battery recharge	Integral harness with molded plugs for battery recharge

<b>Metric</b>	<b>SL-80</b>	<b>SL-80SS</b>
Wiring Harness	Integral harness with molded plugs for battery recharge	Integral harness with molded plugs for battery recharge

## Operational

<b>Imperial</b>	<b>SL-80</b>	<b>SL-80SS</b>
Capacity	12 gal	12 gal
Spraying Width	Up to 48"	Up to 48"
Spraying Volume	1 gpm	1 gpm

<b>Metric</b>	<b>SL-80</b>	<b>SL-80SS</b>
Capacity	45.4 L	45.4 L

Spraying Width	Up to 121.9 cm	Up to 121.9 cm
Spraying Volume	3.8 lpm	3.8 lpm