

Frontier 10 Series Rotary Rake and Tedder

For fast yet gentle hay raking, look to a **Frontier Rotary Rake**. Ideal for use in all types of crops, but especially crops requiring gentle handling, the Frontier Rotary Rake is your tool of choice.

Nine cam-action steel arms operate like pitchforks to gently sweep the crop into fluffy windrows for faster drying while maintaining the crop's nutritional value. The arms rotate via the tractor's PTO, not ground contact, thereby minimizing soil contamination and leaf loss. You get clean, efficient raking, and your livestock gets higher quality, cleaner forage.

With a working width of 11 feet 8 inches, the Frontier Rotary Rake provides excellent productivity at an affordable price. It's perfect in smaller fields, and fields with tight corners and steep terrain. Plus, the transport width of 5 feet makes it easier to move the rake through narrow gates (and takes less space in storage).

Gentle and thorough crop conditioning starts with a Frontier Tedder. This easy-to-use tool helps minimize your crop's drying time so you can bale your hay faster. Flexible steel tines skim the surface, lift the crop, and gently distribute it evenly over the field for faster drying and minimal leaf loss.

With a working width of 10 feet 4 inches, the Frontier TD1010E Tedder improves dry-down of crop at an affordable price. It's perfect in smaller fields, and fields with flat terrain.

Frontier Rotary Rakes and Tedders are backed with a one-year warranty and the best dealer network in the industry – John Deere. Visit your local John Deere dealer and find the products, support, and know-how you need for your haymaking operation.

www.BuyFrontier.com

RR1012E ROTARY RAKE



TD1010E TEDDER



RR1012E & TD1010E

Frontier 10 Series Economy Hay Tools

RAKE SPECIFICATIONS

Model Number	RR1012E
Model	RR1012E
Duty	Economy
Hitch	Pull-type
Working width	11 ft. 8 in. (3.5 m)
Transport width	5 ft. (1.5 m)
Tine arms	9
Tines per arm	6 (3 sets of double coil tines)
Tires	(2) 15 x 6.00-6
Required PTO hp	20 hp (15 kw)
PTO	540 rpm
Weight	682 lb. (309 kg)
PTO with torque limiter	Standard
Transport safety chain	Standard
Warranty	1 year

The Frontier RR1012E Rotary Rake meets ASABE safety requirements.

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. Frontier Equipment reserves the right to change specifications, design, and price of products described in this literature without notice. Copyright 2007, Frontier Equipment.



The Frontier RR1012E Rotary Rake easily folds to a narrow 5 feet for safe transport.



Ground wheels provide maximum stability when working rough, uneven terrain.



Each arm holds three sets of double coil tines, making replacement fast and easy. Tines are angled to minimize crop damage and heat-treated for durability.



Matching the rotary rake to differing field conditions is simple. Just turn the crank to achieve the desired height and tilt.

TEDDER SPECIFICATIONS

Model Number	TD1010E
Hitch	Drawbar
Rotors	2
Tine arms per rotor	6
Working width	10 ft. 4 in. (3.15 m)
Transport width	7 ft. 6 in. (2.29 m)
PTO horsepower requirement	15 hp (11 kw)
PTO with torque limiter	Standard
Weight	396 lb. (180 kg)
Tires	(2) 15x6.00-6
Rotor angle adjustment	Crank
Height adjustment	Crank
Transport safety chain	Standard
Warranty	1 year

The Frontier TD1010E Tedder meets ASABE safety requirements.



Rotor arms are positioned for maximum tine overlap and complete coverage of the field.



Flexible, steel tines are heat-treated for durability and are highly resistant to fatigue.



Quick and easy adjustment of the rotor angle and height allows for accurate and clean pick-up of all types of forage.



Flotation tires provide added stability when working rough terrain.