

FRONTIER
EQUIPMENT™

Rugged. Reliable. Ready.

Frontier Carted Wheel Rakes



WR30 Series: 8 Wheel • 10 Wheel • 12 Wheel

RIGHT RAKES FOR THE JOB

Handle just about any hay condition with the Frontier WR30 Series Carted Wheel Rakes. The WR30 Series is aggressive enough to pick-up tough crop, but gentle enough to maintain the hay's nutritional value. You get full, nutrient-rich hay that's ready for baling. Available in 8-, 10-, and 12-wheel models, there's a hay rake perfect for your haymaking chores.

The WR3008 is equipped with 8 wheels and provides a 15- to 19-foot raking width to handle your small haymaking chores. And with an 8-foot 6-inch transport width, the WR3008 is easy to maneuver through narrow gates.

The WR3010 features a 10-wheel design and gives you an 18- to 22-foot raking width for increased productivity. This implement is great for owners whose land requires a bigger rake.

Or to cover even more acres, check out the WR3012 with a 20- to 24-foot raking width. Featuring 12 productive wheels, the WR3012 helps you make the most of your haymaking time.

The economical WR30 Series offers tremendous versatility to adapt to each job. Work over rough or uneven terrain. Collect hay from multiple types of crop. Get thick, consistent windrows for more compact bales. Tackle moist crops quickly and efficiently for faster drydown – these tools do it all. Hook the WR30 Series up to your tractor with a minimum of 30 horsepower and take advantage of superior raking.

The Frontier Carted Wheel Rakes are sold and supported by John Deere, the most trusted name in farm, ranch and lawn equipment. To help you choose the right Frontier Carted Wheel Rake, talk to your local John Deere dealer, your exclusive source of Frontier Equipment.



The WR30 Series Carted Wheel Rakes feature 15- to 24-foot raking widths for gentle, efficient windrowing. Each model folds 9-foot 6-inches wide or less for easy transporting and convenient storage.



The WR30 Series comes in 8-, 10-, or 12-wheel options. With 55-inch wheel diameters and 40 rugged, steel tines per wheel, you get fluffier, more-even windrows for better quality bales.

variety of hay conditions.

Details – WR30 Series Carted Wheel Rakes



Raise and lower the rake wings using the single-acting hydraulic cylinder – all from the convenience of your operator's seat.



Standard clevis hitch-link allows you to adjust the rake to the drawbar height of your tractor. Maintaining a level frame provides uniform weight distribution on the front and back rake wheels for equal ground pressure. Safety chain comes standard.



Field adjusting the angle of the rake beam for varying hay conditions is simple thanks to this pin adjustment and turnbuckle screw. Angle the rake beam to collect a greater volume of hay.



Change your working width by sliding the rake beam in or out. Adjusting the working width also lets you easily adjust the width of the windrow for your baler.



With the adjustable rake wheel down-pressure spring, you can match the rake to your crop conditions. Use less down-pressure for light hay or more down-pressure for heavier hay. By minimizing down pressure, you extend the life of your rake tines and decrease the amount of debris collected in your windrow.

Frontier Carted Wheel Rakes

Higher quality hay in every gathering.

Specifications

Model	WR3008	WR3010	WR3012
Number of Rake Wheels	8	10	12
Wheel Diameter (inches)	55	55	55
Teeth Per Wheel	40	40	40
Tooth Diameter	7.0 mm (.275 in.)	7.0 mm (.275 in.)	7.0 mm (.275 in.)
Transport Width	8 ft. 6 in.	9 ft. 6 in.	9 ft. 6 in.
Transport Length	13 ft.	15 ft. 6 in.	18 ft.
Windrow Width Adjustment	3 ft.-5 ft.	4 ft.-6 ft.	4 ft.-6 ft.
Raking Width	15 ft.-19 ft.	18 ft.-22 ft.	20 ft.-24 ft.
Raking Wheel Hubs	Tapered Roller Bearings	Tapered Roller Bearings	Tapered Roller Bearings
Wing Flex	Limited	Limited	Limited
2nd Hose Kit	Optional	Optional	Optional
Hitch Jack	Standard	Standard	Standard
Center Kicker Wheels	N/A	Optional	Optional
Transport Wheels	Two - ST175/80D13	Two - ST175/80D13	Two - ST175/80D13
Weight (lbs.)	1125	1275	1440
Horsepower Requirements	30 HP (22 kW)	30 HP (22 kW)	30 HP (22 kW)
Hydraulic Requirements	1 Single Acting Remote for Raising Wing 1 Double Acting Remote for Optional 2nd Hose Kit		

Frontier Carted Wheel Rakes meet ASABE safety standards. Please make sure to always operate rakes with the appropriate shielding in place. DO NOT operate rakes near people or animals. Be certain that you are clear of any discharging material.

For quick and easy haymaking.

The Frontier WR30 Series Carted Wheel Rakes let you quickly windrows so you get higher quality hay when it's time to bale. These rakes get the job done in a variety of conditions. Choose from three durable models with 15- to 24-foot working widths.



This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL JOHN DEERE DEALER FOR DETAILS. Frontier Equipment reserves the right to change specifications, design and price of products described in this literature without notice. Copyright 2008, Frontier Equipment.

www.BuyFrontier.com