

# Frontier High-Capacity Carted Wheel Rakes



WR6008 • WR6010 • WR6012

# Get in and get it done

After mowing or cutting and dry down, raking hay into large windrows for baling and storing as quickly as possible is important for maximizing hay quality and retaining feed value. The WR60 Series High-Capacity Carted Wheel Rakes help producers get it done by increasing raking speed without sacrificing performance.

The WR60 Series gives producers exactly what they are looking for in a high-capacity rake:

- **High operating speeds.** The robust design and individual rake arms help maintain operation speed, even on contours.
- **Capacity for more crop.** Rake arms and beams are designed for higher ground clearance to maximize volume.
- **Flexibility for various crop conditions.** Rake with one or both arms as needed.
- **Simple, time-saving adjustability.** Three adjustment points help fine-tune the rake to control windrow size. No tools are needed to adjust down pressure or windrow width.

This innovative rake series is ideal for larger hay or livestock producers looking to maximize productivity and efficiency on each acre. Parts and service for WR60 Series rakes are as close as your local John Deere dealership.

This season, don't let slow, inefficient raking hinder production. Find out how you can do more – and do it faster – at your local John Deere dealer, the exclusive source for Frontier Equipment.

[www.BuyFrontier.com](http://www.BuyFrontier.com)  
[www.JohnDeere.ca](http://www.JohnDeere.ca)

U.S.A.  
Canada

# Take a closer look

One glance at the WR60 Series High-Capacity Carted Wheel Rakes, with their 8, 10, or 12 high-capacity wheels, shows that Frontier means business. A closer look reveals design elements that may seem minor, but can have a major impact on raking speed, volume and convenience.





Choose among models with 8, 10, or 12 wheels to match the capacity and speed you desire.



Shock-absorbing springs provide smooth performance on uneven terrain.



Hydraulic cylinders enable the operator to raise or lower rake frames while on the go.



The cam and pin are easy to adjust to obtain proper rake arm ground pressure for the crop type and volume.



The transport lock pin can secure either side of the rake in the transport position to make a single windrow.




Rugged teeth resist bending or breaking, while grabbing as much hay as possible.



Because of the wide range of tractor tire sizes and drawbar heights, the adjustable hitch adds convenience for large hay operations.



Independently mounted wheels help maintain rake speed on rough fields.



Flip-up front wheels let you adjust the hay volume in windrows to reduce dry down time and bale easier in heavy crop conditions. Available on WR6010 and WR6012.



Operators can easily raise either the left or right side for raking through a small waterway or ditch.



Optional wind shield made of ABS plastic helps block the effects of cross winds while raking.



Fold the rake to less than 11 feet (3.35 m) wide for easy transport and convenient storage.



A center kicker wheel rakes the center of your windrow, helping keep its density consistent.





## Specifications

Model	WR6008	WR6010	WR6012
Number of rake wheels	8	10	12
Wheel diameter	55 in. (139.7 cm)	55 in. (139.7 cm)	55 in. (139.7 cm)
Teeth per wheel	40	40	40
Tooth Diameter	.275 in. (7.0 mm)	.275 in. (7.0 mm)	.275 in. (7.0 mm)
Raking wheel hubs	Ball bearing	Ball bearing	Ball bearing
Transport width	9.83 ft. (3 m)	10.3 ft. (3.2 m)	11 ft. (3.4 m)
Transport length	21.75 ft. (6.6 m)	23.3 ft. (7.1 m)	25.75 ft. (7.6 m)
Windrow width adjustment	16 - 90 in. (40.6 - 228.6 cm)	16 - 90 in. (40.6 - 228.6 cm)	26 - 99.6 in. (66 - 253 cm)
Raking width	15.42 - 16.75 ft. (4.7 - 5.1 m)	17.2 - 20 ft. (5.2 - 6.1 m)	19.75 - 24 ft. (6.0 - 7.3 m)
Hitch jack	Standard	Standard	Standard
Center kicker wheels	Optional	Optional	Optional
Transport wheels	Two - 205/75 -15	Two - 205/75 -15	Two - 205/75 -15
Weight	1826 lb. (830 kg)	2046 lb. (930 kg)	2290 lb. (1041 kg)
Horsepower requirements	30 hp (22.4 kW)	30 hp (22.4 kW)	50 hp (37.3 kW)
Hydraulic requirements	1 SCV	1 SCV	1 SCV
Warranty*	1 year	1 year	1 year

\*Hour and/or usage limitations may apply. See WARRANTY FOR NEW JOHN DEERE AGRICULTURAL EQUIPMENT AND LIMITED WARRANTY FOR NEW TURF & UTILITY EQUIPMENT or contact your local dealer for details.



### Rake more hay and do it faster.

Make sure your raking operation is running as efficiently as it can and delivers the hay quality and value you want. Talk to your John Deere dealer today about the new WR60 Series High-Capacity Carted Wheel Rakes and learn how one of these high-efficiency rakes can help you retain as much hay quality and value as possible.

Note: models/items may not be exactly as shown. See disclaimer below.

This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL JOHN DEERE DEALER FOR DETAILS. Frontier Equipment reserves the right to change specifications, design and price of products described in this literature without notice. John Deere, the leaping deer symbol and John Deere's green and yellow trade dress are the trademark of Deere & Company. Copyright 2013, Frontier Equipment.



U.S.A.  
Canada

[www.BuyFrontier.com](http://www.BuyFrontier.com)  
[www.JohnDeere.ca](http://www.JohnDeere.ca)