

EZtrak™

RESIDENTIAL ZERO-TURN-RADIUS

MOWERS

Z235 | Z255 | Z425 | Z435 | Z445 | Z465 | Z625 | Z645 | Z655 | Z665



This is how cut quality
comes full circle.

EZtrak™ Series Z600 / Z400 / Z200

This is how we run.

A lot goes into our EZtrak mowers beginning with a very approachable design. But an approachable design only scratches the surface of what makes these mowers great. Here are a few other things:

We test EZtrak mowers hundreds of hours to make sure they can take it.

We use a 12-step paint process that stands up to wear, time and weather. Because it's the right thing to do.

We stamp our mower decks out of pure steel in one piece according to a design that's shaped purposefully to maximize airflow, cut quality and durability.

And we have mowers that cut at ground speeds of 9 MPH (14.5 km/h), 8.5 MPH (13.7 km/h) and 7 MPH (11.3 km/h) on pages 4-8. Among the fastest speeds in the industry.

All to get ready for your yard. That's how we run. And nothing runs like a Deere.

To learn more about how we run, turn the page. Or visit us at JohnDeere.com/EZtrak or JohnDeere.ca/EZTrak.





TABLE OF CONTENTS

How We Run	2-3
Z600 Series	4-5
Z400 Series	6-7
Z200 Series	8-9
Specifications	10-11

EZtrak means it's easy to operate.

Down to the tiniest detail. Designed with you in mind.

All EZtrak mowers feature 1-4" height-of-cut range, which can be done in ¼" increments. The same tool used for cut height is also used to adjust the tracking from the comfort of your seat.

With wide rear tires, your overall ride is smoother and much more comfortable.

Offset caster wheel optimizes inside corner trim performance and also reduces striping.



BUMPER-TO-BUMPER
4-YEAR /500-HOUR
WARRANTY**

Stamping is the backbone of our mowers.

Stamping out mower decks for our Z600 Series Mowers from a sheet of high quality steel is an important part of how we run. It's an example of how we build our Z600 Series the right way. Still, remarkable power and exceptional performance are just as important.

With the Z600 Series, you'll get the high-performance, Edge™ High-Capacity decks for a superior cut in all conditions, large, 23-inch drive tires for a smooth ride and a 9-mph (14.5 km/h) ground speed. All providing you with one of the quickest, most efficient residential zero-turn mowers you'll find today.

In addition to running fast, performance is made easy with features like controls with thick, padded grips and

smooth shock absorbers. In other words, the way these mowers can effortlessly make turns is guaranteed to turn heads.

Those are the big things. But the Z600 Series is stocked with super-smart small elements, too. Like onboard storage for keeping what's important to you, close to you. Or a heavy-duty transmission with no external lines that keeps everything running at a comfortable pace. With an emphasis on comfortable.

That's how we run. And nothing runs like a Deere.

Available in 48-, 54 and 60-in. widths, the Edge™ High-Capacity deck processes more thick, lush grass for an unmatched superior cut. Stamped from thick, 9-gauge steel, this deck will handle large volumes of grass. Its deep shell design provides for superior air flow while standing grass up, so you're always getting the most level cut possible.





Large 21-in-high-back seat with spring suspension and adjustable arm rests provide a comfortable ride.



NEW Z625. The 54-in, 9-gauge steel, three-blade, Edge High Capacity Mower Deck cuts with precision. The 25-hp (18.6 kW) V-Twin engine was specially designed to handle the heavier demands of zero-turn mowing.



Heavy-duty integrated transmission provides both increased performance and durability with an integrated expansion tank and no more external lines.

Z425 / Z435 / Z445 / Z465

BUMPER-TO-BUMPER
4-YEAR / 300-HOUR
WARRANTY†**



†Available on Z435, Z445 and Z465 models only. Z425 features a 2 year/120 hour limited warranty.



Our transmissions deliver speed and durability.



Wide 22x9.50-10 rear tires make for a smoother ride at a faster pace.

Built the right way, to last.

We don't take shortcuts. We do things the right way. With the Z400 Series, making your yard look great is a natural result of how we run. Get into the seat and see what it feels like to hit the grass running with a swift 8.5 mph (13.7 km/h) ground speed and a cut that's unbelievably precise with a 48-, 54-, or 62-in. Edge mower deck.

We know that when an EZtrak comes off the assembly line we're going to make a customer happy down the road. One reason why is that these zero-turn mowers are driven by powerful engines and integrated transmissions.

But beyond being comfortably ahead of the competition, the Z400 Series is also just... comfortable. Wide rear tires provide a smooth ride across your lawn. Onboard storage lets you keep important items close at hand. While 15- or 17-inch seats with armrests, thick cushions and standard seat suspension mean your time in the sun is time comfortably spent.

Another reason for happiness? Attention to detail. Critical maintenance areas are conveniently accessed, so servicing is faster and easier, too.

No shortcuts. Built the right way. Intentional design. That's how we run. And nothing runs like a Deere.

NEW Z435. The 25-hp (18.6 kW) V-Twin engine is the highest horse power in the 400 Series family. The 48- and 54-in Edge™ mower decks, available for the Z435, offer exceptional cut quality.



Easy to start, these smooth running V-Twin engines—the 22-hp (16.4 kW) in the Z425 and the 24-hp (17.9 kW) in the Z445 and Z465—are ready for your yard. (Z445 engine shown here).





Taller foot rests and large platform provide increased comfort for taller operators.



New low fuel level warning light lets you know when it's time to fill up.



Low seat position and a 15-in. seat back height with armrests (Z255 only) provide even more comfort.



All EZtrak mowers feature a 1-4 in. height-of-cut range, which can be adjusted in 1/4-in. increments.



This is how you make time to smell the flowers.

Having time to smell the flowers is fine and good, but providing a quality cut is where it's at. That's where stamped steel and carefully shaped mower decks come in. You'll get one of the best cuts in the industry, every time with our Z200 Series mowers.

Plus the Z200 Series has been designed to take the hard work out of yard work. Both the Z235 and the Z255 mowers offer a thick frame for durability and long life, while the EZT transmission delivers maintenance-free reliability.

Every mow is steady and straight, thanks to easy-to-use on-board tracking and skillfully engineered steering design for comfortable operation. Covered

storage gives you easy access to your gear and all operator controls are right at your fingertips.

The Z200 Series also features large 18-inch rear-drive tires for a smooth ride, and a fully adjustable height-of-cut range (in 1/4-inch increments) that delivers a consistently superior cut. All with 7 mph (11.3km/h) ground speed.

In other words, what comes standard in the Z200 Series is hardly standard at all. But that's just how we run. And nothing runs like a Deere.

BUMPER-to-BUMPER
2-YEAR / 120-HOUR
WARRANTY**



42-in and 48-in stamped steel mower decks are shaped and designed to deliver a true flawless finish. Nobody has a better cut. Nobody.



Get around your yard at a quick 7-mph (11.3km/h) pace, delivered in part by 20- and 22-hp V-Twin engines.

6.5 bushel baggers make quick work of clippings. Available for the Z235 and Z255.



EZtrak™ Series

Specifications

	EZtrak Z235	EZtrak Z255	EZtrak Z425
Engine			
Model	M40	M44	M44
Horsepower*	20 hp (14.9 kW)	22 hp (16.4 kW)	22 hp (16.4 kW)
Displacement	40.0 cu in. (656 cc)	44.2 cu in. (724 cc)	44.2 cu in. (724 cc)
Cylinders	V-twin	V-twin	V-twin
Oil Filter	Yes	Yes	Yes
Lubrication	Full pressure, 2 qt (1.9 L)	Full pressure, 2 qt (1.9 L)	Full pressure, 2 qt (1.9 L)
Cooling	Air	Air	Air
Fuel System			
Fuel Type	Gas	Gas	Gas
Fuel tank capacity	2.1 U.S. gallon (8 L)	2.1 U.S. gallon (8 L)	3.5 U.S. gallon (13.2 L)
Fuel Indication	Low fuel indicator	Low fuel indicator	Yes
Electrical System			
Battery Voltage	12 V	12 V	12 V
Cold Cranking Amps	340	340	340
Hourmeter	Standard	Standard	Standard
Drive Train			
Dual hydros	Hydro-Gear; EZT w/1-in.(2.5 cm) axles	Hydro-Gear; EZT w/1-in. (2.5 cm)axles	Tuff Torq TZT7-D
Travel speed			
Forward	7 mph (11.3 km/h)	7 mph (11.3 km/h)	8.5 mph (13.7 km/h)
Reverse	3.5 mph (5.6 km/h)	3.5 mph (5.6 km/h)	4.0 mph (6.4 km/h)
Speed and Direction Control	Twin levers	Twin levers	Twin levers
Tires			
Front Caster Tires	11x4.0-4	11x4.0-4	13x5.0-6
Drive Tires	18x8.50-8	18x8.50-8	22x9.50-10
Seat			
Height	15 in. (38.1 cm)	15 in. (38.1 cm)	15 in. (38.1 cm).
Armrests	No	Yes	Yes
Suspension	Standard	Standard	Standard
Mower deck			
Cutting Width	42 in. (107 cm)	48 in.(122 cm)	48 in.(122 cm)/54 in. (137 cm)
Cutting Height	1-4 in. (2.5-10.2 cm)	1-4 in. (2.5-10.2 cm)	1-4 in. (2.5-10.2 cm)
Discharge	Top	Top	Side
PTO			
Type	Electric, 105 lb-ft	Electric, 105 lb-ft	Electric, 125 lb-ft
Drive	Belt	Belt	Belt
Dimensions			
Wheelbase	47.5 in. (1207 mm)	50.3 in. (1278 mm)	47.2 in. (120 cm)
Overall length	72.2 in. (1835 mm)	75.1 in. (1907 mm)	74.7 in. (190 cm)
Height	36.3 in. (92.2 cm)	36.3 in. (92.2 cm)	38.6 in. (98 cm)
Weight (no fuel)	460 lb (209 kg)	500 lb (227 kg)	645 lb (293 kg)/660 lb (299 kg)
Limited Warranty**	2 years/120 hours	2 years/120 hours	2 years/120 hours

*The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's website for additional information.

**Term limited to years or hours used, whichever comes first, and varies by model. See the LIMITED WARRANTY FOR NEW JOHN DEERE TURF AND UTILITY EQUIPMENT at JohnDeere.com/Warranty or www.JohnDeere.ca/TUWarranty for details.

EZtrak Z435 / Z445**EZtrak Z465****EZtrak Z645****EZtrak Z625 / Z655****EZtrak Z665**

M44 Cyclonic® / FS730V

FS730V

FS730V

M44 Cyclonic® / FS730V

FS730V

25 hp (18.6 kW) / 24 hp (17.9 kW)

24 hp (17.9 kW)

24 hp (17.9 kW)

25 hp (18.6 kW) / 24 hp (17.9 kW)

24 hp (17.9 kW)

44.2 cu in. (724 cc) / 44.3 cu in. (726 cc)

44.3 cu in. (726 cc)

44.3 cu in. (726 cc)

44.2 cu in. (724 cc) / 44.3 cu in. (726 cc)

44.3 cu in. (726 cc)

V-twin

V-twin

V-twin

V-twin

V-twin

Yes

Yes

Yes

Yes

Yes

Full pressure, 2 qt. (1.9L) /
Full pressure, 2.2 qt (2.1 L)

Full pressure, 2.2 qt (2.1 L)

Full pressure, 2.2 qt (2.1 L)

Full pressure, 2 qt. (1.9L) /
Full pressure, 2.2 qt (2.1 L)

Full pressure, 2.2 qt (2.1 L)

Air

Air

Air

Air

Air

Gas

Gas

Gas

Gas

Gas

3.5 U.S. gallon (13.2 L)

Yes

Yes

Yes

Yes

Yes

12 V

12 V

12 V

12 V

12 V

340

340

340

340

340

Standard

Standard

Standard

Standard

Standard

Tuff Torq TZT7-D

Tuff Torq TZT7-D

Tuff Torq TZT7-M

Tuff Torq TZT7-M

Tuff Torq TZT7-M

8.5 mph (13.7 km/h)

8.5 mph (13.7 km/h)

9 mph (14.5 km/h)

9 mph (14.5 km/h)

9 mph (14.5 km/h)

4.0 mph (6.4 km/h)

4.0 mph (6.4 km/h)

4.5 mph (7.2 km/h)

4.5 mph (7.2 km/h)

4.5 mph (7.2 km/h)

Twin levers

Twin levers

Twin levers

Twin levers

Twin levers

13x5.0-6

13x5.0-6

13x6.5-6

13x6.5-6

13x6.5-6

22x9.50-10

22x9.50-10

23x10.50-12

23x10.50-12

23x10.50-12

17 in. (43.2 cm)

17 in. (43.2 cm)

21 in. (53.3 cm)

21 in. (53.3 cm)

21 in. (53.3 cm)

Yes

Yes

Yes

Yes

Yes

Standard

Standard

Standard

Standard

Standard

48 in.(122 cm)/54 in. (137 cm)

62 in. (157 cm)

48 in.(122 cm) High-capacity

54 in. (137 cm) High-capacity

60 in. (152 cm) High-capacity

1-4 in. (2.5-10.2 cm)

Side

Side

Side

Side

Side

Electric, 125 lb-ft

Belt

Belt

Belt

Belt

Belt

47.2 in. (120 cm)

49.2 in. (125 cm)

48 in. (122 cm)

48 in. (122 cm)

49.2 in. (125 cm)

74.7 in. (190 cm)

75.9 in. (193 cm)

74.7 in. (190 cm)

74.7 in. (190 cm)

75.9 in. (193 cm)

42.5 in. (108 cm)

42.5 in. (108 cm)

45.3 in. (115 cm)

45.3 in. (115 cm)

45.3 in. (115 cm)

665 lb (302 kg)/680 lb (308 kg)

712 lb (323 kg)

750 lb (340 kg)

738 lb (335 kg)/755 lb (343 kg)

765 lb (347 kg)

4 years/300 hours

4 years/300 hours

4 years/500 hours

4 years/500 hours

4 years/500 hours



JohnDeere.com | JohnDeere.ca

This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification, design and price of the products described in this literature without notice. John Deere's green and yellow color scheme, the leaping deer symbol, and JOHN DEERE are trademarks of Deere & Company.

DSTA61994 (15-01)



Nothing runs like a Deere™