

# 2R Series

2025R and 2032R Compact Utility Tractors



Work ... with the power of 2.

2025R & 2032R

# The best things come in 2's.

Big-tractor features meet intuitive, easy-to use controls behind the wheel of the John Deere 2R Series Compact Utility Tractors. With some of the best standard features in the class, like four wheel drive (4WD), hydrostatic transmission with cruise control, power steering, and drive-over mower deck compatibility, the 2025R (25 hp<sup>†</sup>) and 2032R (32 hp<sup>§</sup>) pack quite a punch in a variety of jobs and applications. From finish-mowing to loader chores, to backhoe work and snow removal, the 2R Series will help your property, or your business, reach its full potential.

Add up all those standard features with smart options like Quik-Park™ loaders and iMatch™ quick attach hitch and you'll agree... the best things really do come in 2's.

Read on to learn more or visit [deere.com/2R](https://deere.com/2R) to build your own.



# 2025R

Capable. Reliable. Affordable.

It may be a compact utility tractor, but when you consider all the features it packs into one affordable package, the term “entry-level” doesn’t do it justice. Strap in and see for yourself just how capable and easy-to-use the 2025R really is.



# 2032R

More power for tougher jobs

Sometimes you just need a little more horsepower. For those tougher jobs, consider the 32 horsepower<sup>s</sup> 2032R. Your tractor will thank you when you’re dealing with heavier loader work, tall grass, or PTO intensive applications. We’ve said it for years ... life’s just a little easier with a bit more horsepower.



# 2R Series Features & Options

Designed for practicality. Engineered for performance.



**A.** 2-speed, 2-pedal hydrostatic transmission with cruise control means simple operation, even for inexperienced drivers.

**B.** Folding ROPS comply with ASABE and OSHA standards and provides convenient storage.

**C.** Operator station gives convenient access to loader joystick and hitch lever while independent hydrostatic power steering provides smooth and steady maneuvering, no matter the load.

**D.** On-Ramp™ Drive Over Deck means mower deck attachment in mere minutes. Decks available up to 72 inches.

**E.** H130 Quik-Park™ loaders attach and detach in under 3 minutes – with no tools. Easily switch between front-end attachments like buckets and loader forks for whatever the job demands.

**F.** iMatch™ compatibility means hitch-mounted implements can be swapped in seconds. While the position control hitch feature provides uniform implement depth.



## H130 Loaders Smart efficiency... built in.

Pair your 2R Series Tractor with a Quik-Park™ H130 Loader and enjoy premium loader features like faster cycle times, impressive lift capacity, and an integrated parking stand for simple, no-tool attaching and detaching in 3 minutes or less.

Reduce your time between chores with a Quik-Park H130 Loader and get more done ... your property will thank you.

	2025R w/ H130	2032R w/ H130
Lift Capacity @ pivot pin (max height)	1023 lb. (465 kg)	1027 lb. (467 kg)
Lift capacity to 59" at pivot pin	1247 lb. (567 kg)	1245 lb. (566 kg)
Max lift height at pivot pin	78.7 in (1999 mm)	78.5 in (1993 mm)
Breakout force at pivot pin	2508 lb. (1140 kg)	2363 lb. (1074 kg)
Dump angle	38°	38°
Rollback angle	24.5°	25°
Loader raise/lowering time	4.73 / 2.88 sec	3.19 / 1.95 sec
Bucket dump time	4.73	3.19
Bucket rollback time	2.88 sec	1.95 sec

You may want to sit down for this.



To quickly change implements with the iMatch Quick-Hitch, you simply back in, hydraulically lift the unit and secure the latches.

Once you're connected and the unit is in place, there's an even easier way to automatically hook up PTO-driven attachments. The iMatch™ Auto-Hitch is the answer. To hook up the drive shaft to the secure unit, just rotate the handle, then turn and pull the AutoHitch lever... all from the seat of your tractor.



**More than 50 implements** are ready and waiting for you to give them a spin. From backhoes to wheel rakes and every task in between, John Deere and Frontier commercial-grade implements not only do it all, they do it better and quicker. The time between starting up your tractor and getting work done is considerably shorter, thanks to John Deere iMatch™ AutoHitch™, Quik-Park™ loaders and drive-over OnRamp™ decks. Need the right tools for the job? Visit [Deere.com](http://Deere.com) or talk to your John Deere dealer today.

**1. Rotary Cutters** – Designed to cut wide areas fast and those hard-to-reach areas easier.

**2. Mid-PTO/Mechanical Diverter** – With standard mid-PTO, the 2R can run mid-PTO-powered implements like John Deere drive-over mower decks. Add a mechanical diverter to make it easier to switch between deck height adjustment and loader hydraulics.

**3. Front Blades** – From moving dirt and gravel, to clearing snow, these versatile front blades can angle right or left to make your job easier.

**4. Tiller** – Commercial-duty with heavy-duty tine shafts for excellent performance and durability even in packed down soil conditions.

**5. Backhoes** – Powerful double-acting cylinder swing system provides a 150-degree swing, precise control and extra torque when backfilling. Boom cylinders are mounted on top for superior visibility to the trench. Powerful digging force makes quick work in tough conditions. (270A backhoe is compatible with the 2025R; 46 backhoe is compatible with the 2032R)



Whether it's enhanced productivity, stability, visibility, or hours in the field, these attachments will help you get the most out of your John Deere Tractor.



#### Hood Guard

Protect your grill from brush, debris, and those unexpected "bumps" that happen when getting too close while dumping your load.

**BW15634** (2032R, 2520, 2720)



#### Forward Lighting Kit

Enjoy increased visibility up front when working in dark conditions. Two lights mount to brush guards located on the ROPs.

**LVB25546** (2 lights) (2025R, 2032R)



#### Rear Work Light Kit

Shed some light, especially when working with rear implements.

**LVB25547** (2 lights) (2025R, 2032R)



#### Engine Coolant heater

Engine coolant heaters allow for easier starts during cold months, which translates into saved time, money, and less engine wear. (110V)

**AR87167** (2025R, 2032R)



#### Weather Protection Umbrella

Protect yourself from the elements and get out of the sun and into some shade with this easily removable umbrella.

**TY25324** (2025R, 2032R)



#### Rear Fender Extensions

Keep it clean by protecting yourself, the tractor and the implements from debris flying off the rear tractor tires.

**LVB25652** (2025R, 2032R)

	2025R	2032R
<b>ENGINE</b>		
Type	Yanmar 3TNV80F	Yanmar 3TNV88
HP	24.2 (17.8 kw) †	31.7 (23.3 kw) †
PTO HP	18.0 (13.4 kW)	23.5 (17.5 kW)
Rated Speed, rpm	3,000	2,500
Engine displacement	77.3 cu. in. (1.267 L)	100 cu. in. (1.642 L)
Battery power	12V, 500 CCA	12V, 500 CCA
Alternator	40 A	40 A
<b>HYDRAULICS</b>		
Steering	2.2 gpm (8.5 L/min)	5.5 gpm (20.8 L/min)
Implement	3.4 gpm (12.7 L/min)	5.0 gpm (18.8 L/min)
Total capacity	5.6 gpm (21.2 L/min)	10.5 gpm (39.6 L/min)
Lift capacity (24 in. behind lift point)	1,150 lb. (522 kg)	1,181 lb. (535.6 kg)
<b>TRANSMISSION</b>		
Standard	Hydrostatic - 2 Range	Hydrostatic - 2 Range
Optional	NA	NA
Final drive	Spur Gear	Spur Gear
Brakes	Wet disk	Wet disk
Steering	Power	Power
<b>PTO</b>		
PTO type	Independent	Independent
PTO options	Mid and Rear standard	Mid and Rear standard
<b>REAR HITCH</b>		
Type	Category 1	Category 1
Control type	Position	Position
<b>WEIGHT</b>		
With all fluids	1,660 lb. (753 kg)	1,973 lb. (895 kg)
<b>LOADER</b>		
<b>H130</b> Lift capacity at full height (pivot point)**	1,023 lb. (465 kg)	1,027 lb. (467 kg)

† Manufacturer's estimate of power (ISO) per 97/68/EC.

\*\* For a complete list of loader specifications see your dealer.

† The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the manufacturer's web site for additional information.

## Dimensions\*



Wheelbase – 63 in. (1600 mm) (2025R)  
65.2 in. (1655 mm) (2032R)

Length – 109.2 in. (2774 mm) (2025R)  
108.9 in. (2766 mm) (2032R)

Hood height - 48.7 in. (1238 mm) (2032R)  
46.5 in. (1181 mm) (2025R)



Min. width – 46.38 in. (1178 mm) (2025R)  
51 in (1295 mm) (2032R)

Max. Width – 51 in. (1295 mm) (2025R)  
53.5 in. (1359 mm) (2032R)

Folded ROPS height - 68.39 in. (1737 mm) (2025R)  
69.41 in. (1763 mm) (2032R)

ROPS Height - 89 in. (2261 mm) (2025R)  
89.7 in. (2279 mm) (2032R)

\*Dimensions with R3 Tires



## POWERGARD™ MAINTENANCE PLAN

While PowerGard Protection Plan ensures you're covered when something goes wrong, PowerGard Maintenance Plan helps reduce the likelihood that something will and keeps your tractor investment running strong. Typical maintenance includes changing oil, checking fluid levels and swapping out filters. Because usage patterns vary, your dealer can help customize a plan that suits your needs. You can choose your time and hour options, as well as whether you want to include break-in service. The plan includes the cost of parts, labor and travel. Ask about onsite maintenance to save yourself the hassle of equipment transportation.

\* Hour and/or usage limitations apply and vary by model. See the LIMITED WARRANTY FOR NEW JOHN DEERE COMMERCIAL AND CONSUMER EQUIPMENT at dealer for details.



This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification, design and price of the products described in this literature without notice. John Deere's green and yellow color scheme, the leaping deer symbol, and JOHN DEERE are trademarks of Deere & Company. Model/items shown may not be exactly as shown.

DSTA62028 Litho in U.S.A. (15-02)

