

2027 OUTLANDER PRO DPS



- Sandstone
- Granite Grey (US only)

PACKAGE HIGHLIGHTS

HD5	HD7
• Tri-Mode Dynamic Power Steering (DPS) • Visco-Lok[†] QE auto-locking front differential • 26 in. 6-ply rating tires • Heavy-duty front bumper, rear bumper, full skid plate • Glovebox • Front dropdown storage • Fender flares • Handguards • Footwell protectors • Trailer hitch mount	• Tri-Mode Dynamic Power Steering (DPS) • Visco-Lok[†] QE auto-locking front differential • 26 in. 6-ply rating tires • Heavy-duty front bumper, rear bumper, full skid plate • Glovebox • Front dropdown storage • Fender flares • Handguards • Footwell protectors • Trailer hitch mount

ENGINES	HD5	HD7
Type	40 hp / 37 lb-ft, Rotax [®] ACE™ (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid-cooled	50 hp / 41 lb-ft, Rotax ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)	
Transmission	pDrive primary CVT with work calibration Extra low L / H / N / R / P	
Drive Train	Selectable 2WD / 4WD with Visco-Lok [†] QE auto-locking front differential	
Driving Assistance	Work / Standard modes Intelligent Engine Braking (iEB™) Speed limiter	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	

SUSPENSIONS

Front Suspension	Double A-arm 9.75 in. (24.8 cm) travel
Front Shocks	Twin Tube
Rear Suspension	Double A-arm 10.25 in. (26 cm) travel
Rear Shocks	Twin Tube

TIRES & WHEELS

Front / Rear Tires	XPS Trail King, 6-ply rating, 26 x 8/10 x 12 in.
Wheels	12 in. Steel

BRAKES

Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

DIMENSIONS & CAPACITIES

	HD5	HD7
Estimated Dry Weight*	816 lb (370.1 kg)	
L x W x H	90.9 x 48.2 x 48 in. (230.9 x 122.4 x 122 cm)	
Wheelbase	53 in. (134.5 cm)	
Ground Clearance	13 in. (33 cm)	
Seat Height	38.6 in. (98 cm)	
Rack Capacity	Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg)	
Storage Capacity	9 gal (34 L)	
Towing Capacity	1,830 lb (830 kg)*	
Bed Capacity	N/A	
Fuel Capacity	5.1 gal (19.5 L)	

*Braked trailer.

FEATURES

Gauge	4.5 in. digital display
Magneto	500 watt
Instrumentation	N/A
Ignition	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	LED headlights and taillights
Winch	N/A
Seat	Standard
Handlebar	Standard
Protection	Heavy-duty front bumper Rear bumper HMWPE front and rear A-arm protection (5 mm) Full skid plate
Hitch Type	2 in. hitch receiver with trailer hitch mount

WARRANTY & EXTENDED SERVICE

Factory Warranty	1-year BRP Limited warranty
Extended Service Terms	B.E.S.T. term available up to 48 months



© 2026 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. † Visco-Lok is a trademark of GKN Viscodrives GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in the U.S.A. call the ATV Safety Institute at 1-800-887-2887. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

