

Fertilizer Applicator

MODEL	1860	MODEL	2460
Tank size	1800 US gallon tank, stainless steel baffle, hopper bottom sump w/ 3" fill	Tank size	2400 US gallon tank, stainless steel baffle, hopper bottom sump w/ 3" fill
Tool bar	- Available in 24/30" (25), 32/22" (33), 36/20" (37) widths - Active hydraulic down pressure. - Four (4) gauge wheels. - Double 5 x 7 mainframe with ground contour following wing sections	Tool bar	- Available in 24/30" (25), 32/22" (33), 36/20" (37) widths - Active hydraulic down pressure. - Four (4) gauge wheels. - Double 5 x 7 mainframe with ground contour following wing sections
Tire size	Dual tire 380/90R54 Single tire/rim 380/90R54 Single tire/rim 480/80R42	Tire size	Dual tire 380/90R54
Wheel spacing	60"/120", 80"/120", 88"/132" Duals	Wheel spacing	60"/120", 80"/120", 88"/132" Duals
Plumbing	- Ace hydraulic driven centrifugal pump kit. - 5 section control valves - Raven 450 or Envisio Pro rate controller	Plumbing	- Ace hydraulic driven centrifugal pump kit. - 5 section control valves - Raven 450 or Envisio Pro rate controller
Coulters	20" ripple, spring-cushioned Knives or injectors Hydraulic depth control assist	Coulters	20" ripple, spring-cushioned Knives or injectors Hydraulic depth control assist
Ground clearance ¹	36" in field operation, 54" on turn rows	Ground clearance ¹	36" in field operation, 54" on turn rows
Transport width ¹	18' 6"	Transport width ¹	18' 6"
Transport height ¹	13' 6"	Transport height ¹	13' 6"
Transport length ¹	24' 3"	Transport length ¹	24' 3"
Pin to Axle	185"	Pin to Axle	185"
Fresh water safety tank	9 gallon	Fresh water safety tank	9 gallon
Quick fill	3"	Quick fill	3"
Empty weight ¹	16,800 lb	Empty weight ¹	16,800 lb
Tongue weight, loaded ¹	4,975 lb	Tongue weight, loaded ¹	4,975 lb
Tongue weight, empty ¹	4,975 lb	Tongue weight, empty ¹	4,975 lb

¹ Approximate measurement