

# Farm King

## GRAIN CART

Models 1060 & 1360





The Farm King grain cart builds on decades of high quality grain handling equipment manufacturing. Farm King products handle grain from the combine to market. Featuring a high capacity 21.5" unloading auger, standard roll tarp and a rotating unload spout. The Farm King grain cart also features a gravity flow discharge designed to unload directly into pits and auger hoppers. The 1060 and 1360 carts use high quality components and are built to handle the toughest harvest conditions.



#### Direct Driven Augers

Farm King grain carts do not require hydraulic flow to operate the unload auger or floor drag auger. The floor auger is belt driven off of the PTO and the unload auger is driven directly through a gearbox. This eliminates the use of chains and sprockets for auger drives which minimizes downtime and maximizes productivity.



#### Gravity Flow Discharge

The Farm King 1060 and 1360 feature a gravity flow discharge door designed to fill pits and auger hoppers.



#### Floor Drag Auger

A floor drag auger is standard on both models. The 1060 and 1360 carts are able to unload smoothly and efficiently as grain is consistently fed into the unload auger. Hydraulic gates control the flow of grain to the augers.

# Farm King

301 Mountain Street South  
Morden, Manitoba Canada R6M 1X7  
Ph.: 204.822.4467 | Fax: 204.822.6348  
Toll Free: 888.524.1004  
E-mail: [info@buhler.com](mailto:info@buhler.com)  
[www.farm-king.com](http://www.farm-king.com)

Equipment shown is subject to change without notice. TSX:BUI  
©2012 Buhler Trading Inc. Printed in Canada. Ref: 062012-1500-LM

MODEL	1060	1360
Capacity	1,060 bushels	1,360 bushels
Width w/o load cells	12' 3"	12' 8"
Length	34' 9"	34' 9"
Height, transport	11' 9"	12' 5"
Tires	900/60R32	520/85R38
Unload auger	21.5"	21.5"
Floor drag auger	13"	13"
PTO	1000 rpm	1000 rpm
Drawbar in short position	Category IV	Category V
Recommended hp	275 hp	275 hp
Weight	18,520 lb	21,280 lb