

JUST WHAT YOU NEED TO BREAK THE ICE.

Arctic's galvanized spreaders are engineered with two things in mind: ease and durability. Our spreaders are easy to operate and maintain, offering an unmatched level of toughness. Electric, gas and hydraulic options are available.

STANDARD EQUIPMENT includes drop-in screen, bolt down brackets, and forward slide stop bracket, adjustable chute, and ratchet tie downs.

OPTIONAL Side extensions to hold up to 2x8 planks

OPTIONAL LED service light


ACCESSIBILITY TO ALL COMPONENTS makes it easier to remove the gear box without removing the spreader drive

COMPLETELY GALVANIZED BODY superior durability and resistance to abrasion, water and rust means your investment has a longer service life

TIE-DOWN STRAPS AND FORWARD MOTION STOP PLATE secure the spreader and its load to the vehicle.

TRUCK SIDE AND SPREADER SIDE WIRING AND IN-CAB CONTROLS allows the spreader to be unplugged and removed from the truck, leaving each side ready to be plugged in when reinstalled

TWO-PIECE SPINNER SHAFT allows for easy removal and access to trailer hitch



TOUGHER THAN A CANADIAN WINTER

Your choice of gas, hydraulic or electric drive. Take your pick.



GAS ENGINE – AG
Our gas engine spreader is powered completely by a belt-driven motor, and features in-cab controls, electric start, electric throttle, electric clutch and truck battery attaching harness. Select from 13 HP Briggs and Stratton or 11 HP Honda engines.



HYDRAULIC – AGH
Our hydraulic powered spreader requires a central hydraulic pump system with a 5 to 8 Gallon/Min pump, plus suction and pressure hoses. Available in single and double motor drives, with either cab- or tank-mounted flow divider controls.



ELECTRIC – AGE
Our 12v 3/4 HP electric spreader comes standard with on/off in-cab controls and has a variable speed controller as an option. It also features a stainless steel drive chain and hardened sprockets.



ELECTRIC – DUAL
AGE Dual Option with variable speed controller. Includes second motor for independent operation of spinner & drag chain to better control the flow of the material.

Galvanized Spreader Specifications				
Model	AG4	AG6	AG8	AG10
Model Size	4'	6'	8'	10'
Length Inside	47"	71"	95"	119"
Length Overall	70 3/8"	94 3/8"	118 3/8"	142 3/8"
Width	50"	50"	50"	50"
Body Height	32"	32"	32"	32"
Capacity*	0.8 yd ³	1.22 yd ³	1.64 yd ³	2.07 yd ³
Capacity with Sideboards*	1.02 yd ³	1.45 yd ³	1.96 yd ³	2.7 yd ³
Weight AG	n/a	775 lbs	903 lbs	1006 lbs
Weight AGH	n/a	623 lbs	751 lbs	854 lbs
Weight AGE	634 lbs	760 lbs	888 lbs	991 lbs
Warranty	1 year	1 year	1 year	1 year

* Water level using 2"x 4" Nominal Board Size



OPTIONAL ACCESSORIES



SPINNER GUARD



VIBRATOR KIT



HOPPER EXTENSIONS



TARP KIT



LEGAL DISCLAIMER: Vehicles intended to be equipped with Arctic equipment must comply with the vehicle manufacturers' specifications for equipment application. Please consult your vehicle dealer before purchase and installation. The purchaser assumes all vehicle risk associated with the attachment and operation of Arctic equipment. Arctic reserves the right to change specifications without prior notification.