



40' STACK-FOLD BULK-FILL

The 40' Stack-Fold Planter from Great Plains is truly in a class by itself, with the versatility of multiple row-spacing configurations and the productivity of a bulk seed hopper. Great Plains Stack-Fold Planters are equipped with an 82-bushel poly hop-


per. The Air-Pro® metering system offers the highest level of singulation on the market today. Finally, the unit was designed to stack-fold to a transport width of 25', with extra clearance down low for bridges, signs, and gate openings.



40' STACK-FOLD BULK-FILL

40' Stack-Fold	Working Width	Transport Width	Transport Height	Engine H.P. Required	Row Spacing	Base Weight	Seed Capacity
3PYPA	36' - 40'	24' 6" - 25' 2"	12' 6"	220+	15", 30", 36", 38", 40", TR30", TR36", TR38", TR40"	14,500 - 18,700	82 bu.

See www.greatplainsag.com for complete specifications.
 Specifications are subject to change without prior notification.
 Images may not depict current or standard production models.



FEATURES & BENEFITS

25 SERIES ROW UNIT




The 25 Series row unit utilizes ductile cast parallel arms for long-term row unit stability. 15", 4mm blades turning on 205 triple-lip sealed bearings ensure long life and accurate seed depth. Blades are offset 1/2" to slice residue and form a perfect seed trench.



ADDITIONAL STANDARD FEATURES

- Advanced air delivery system
- Side-depth wheels (2 1/2" -wide on twin-row models; 3" -wide on 15" models; 4" spacing on 30", 36", 38", and 40" models)
- Narrow transport width (25' 2" on 30" twin-row models; 24' 6" on all other models)
- Ground or hydraulic drive
- Heavy-duty row unit down-pressure springs (up to 500 lbs./row)
- Wide walkboard and steps
- Hydraulic steering (must have Power Beyond setup)
- 3-section point row control
- Single or dual caster wheels
- Wing lock, wing flex, or hydraulic down-pressure choices
- LED safety lighting



AIR-PRO® METER

This simple, positive air pressure meter offers the highest level of singulation on the market today, and achieves uniform spacing by "dead-dropping" seed into the patented Clear-Shot® seed tube. Gentle on seeds, it is more efficient than a vacuum meter and requires less maintenance.



CHOOSE A PRESS WHEEL

Choose (from left) cast for sticky Delta soils, wedge wheels that pinch the seed trench together but provide a wide footprint; 1" x 12" double-V for all-around performance; or spider wheels with drag chains that aggressively close the seed trench.

OPTIONS (see website for complete list of features & options)



ROW-PRO™



SWATH COMMAND™



HYDRAULIC WING DOWN PRESSURE



COULTERS & ROW CLEANERS



ISO-6 CONTROL SYSTEM



CENTRAL-FILL BULK HOPPER

82 bu. of onboard seed capacity on this semi-mounted planter. Lift-assist wheels carry the seed weight and help lift the planter on end rows and during transport.



AVAILABLE ROW SPACINGS

Multiple row spacings are available to match a variety of needs, including 30", 36", 38", and 40" single- or twin-row configurations.



HYDRAULIC STEERING

Hydraulic steering, standard on either single or dual casters, allows the rear caster wheels to turn with the tractor steering to aid in end-row turns.