

MODELS AVAILABLE



MODEL INFO	4-Row Pull-Type & 3-Point Mounted (pg 12-13)		6-Row Pull-Type & 3-Point Mounted (pg 12-13)		8-Row Pull-Type & 3-Point Mounted (pg 12-13)		20' & 25' 3-Point Mounted (pg 14-15)		12-Row Yield-Pro (pg 16-17)		16-Row Yield-Pro (pg 16-17)			
MODELS	YP-425A	YP-425A3P	YP-625A	YP-625A3P	YP-825A	YP-825A3P	2025A	2525A	YP-1225	YP-1225A	YP-1625	YP-1625A		
ROW SPACINGS	30", TR30", 36", TR36", 38", TR38", 40", TR40"		30", TR30", 36", TR36", 38", TR38", 40", TR40"		30", TR30", 36", TR36", 38", TR38", 40", TR40"		TR30", TR36", TR38", TR40", TR36"15"		TR30", TR36", 15", 20", 30"		TR30", TR36", 15", 20", 30", 36"			
ROW UNITS	4-30", 8-TR30", 4-36", 8-TR36", 4-38", 8-TR38", 4-40", 8-TR40"		6-30", 12-TR30", 6-36", 12-TR36", 6-38", 12-TR38", 6-40", 12-TR40"		8-30", 16-TR30", 8-36", 16-TR36", 8-38", 16-TR38", 8-40", 16-TR40"		16-TR30", 12-TR36", 12-TR38", 12-TR40", 12-TR36"15"		20-TR30", 16-TR36", 16-TR38", 16-TR40", 16-TR38"15", 30-9.5", 20-15"		24-TR30", 16-TR36", 23-15", 18-20", 12-30"		32-TR30", 24-TR36", 31-15", 24-20", 16-30", 12-36"	
TIRE SIZE	8R19.5 LT		8R19.5 LT		8R19.5 LT		11Lx15.5L 12-Ply		Rear 380/90R46, Wing 395/55B16.5		Rear 380/90R46, Wing 395/55B16.5			
*H.P. REQUIREMENTS (min)	75-120		95-160		115-200		210-300		140-205		165-275			
<b>DIMENSIONS</b>														
WIDTH (no markers)	10' 0.5"		15' 0.5"		20' 0.5"		21'		25' 2"		30'		40'	
WIDTH (markers)	11' 3"		16' 3"		21' 3"		21'		25' 2"		30'		40'	
WIDTH (transport)	11' 3"		16' 3"		21' 3"		21'		25' 2"		13' 6"		13' 6"	
LENGTH (transport)	12' 10"      5' 10"		12' 10"      5' 10"		12' 10"      5' 10"		5' 2"		36' 2"		41' 2"		41' 2"	
CLEARANCE (transport)	depends on tractor hitch, approx. 14"		depends on tractor hitch, approx. 14"		depends on tractor hitch, approx. 14"		depends on tractor hitch		22"		22"		22"	
HEIGHT (transport)	6' 6" (at 14" ground clearance)		6' 6" (at 14" ground clearance)		6' 6" (at 14" ground clearance)		8' 4"		12' 6"		12' 6"		12' 6"	
<b>OPENER INFO</b>														
OPENER SERIES	25 Series		25 Series		25 Series		25 Series		25 Series		25 Series			
OPENER DOWN PRESSURE	125-250 lbs		125-250 lbs		125-250 lbs		250-500 lbs		250-500 lbs		250-500 lbs			
OPENER TRAVEL (up-down)	10"		10"		10"		10"		10"		10"			
OPENER DEPTH RANGE	0-3.5"		0-3.5"		0-3.5"		0-3.5"		0-3.5"		0-3.5"			
<b>CAPACITIES</b>														
SEED CAPACITY	6.4 bushels (30"), 12.9 bushels (TR30")		9.6 bushels (30"), 19.2 bushels (TR30")		12.8 bushels (30"), 25.6 bushels (TR30")		48 bushels		57 bushels		Seed Company Bulk Box, 82 bu Poly Hopper, 150 bu Poly Hopper		Seed Company Bulk Box, 82 bu Poly Hopper, 150 bu Poly Hopper	
FERTILIZER CAPACITY	200 gal (1x200) Liquid 18 cu ft (2x9) Dry		300 gal (2x150) Liquid 27 cu ft (3x9) Dry		400 gal (2x200) Liquid 36 cu ft (4x9) Dry		N/A		N/A		**Optional 400 gal fertilizer tank (2x200)		**Optional 400 gal fertilizer tank (2x200)	

MODELS AVAILABLE



MODEL INFO	30' Yield-Pro (pg 18-19)			40' Yield-Pro (pg 18-19)			44' Pull-Type Yield-Pro (pg 20-21)	40' Stack Fold (pg 22-23)		60' Bulk Yield-Pro (pg 24-25)	
MODELS	YP-3010HDP	YP-3020P	YP-3025A	YP-4010HDP	YP-4020P	YP-4025	YP-4425	3PYP	3PYPA	YP-2425	YP-2425A
ROW SPACINGS	7.5", 10"	10"	10", 15", 15" even, 20", 30", TR30", TR36"	7.5", 10"	8", 10"	10", 15", 15" even, 20", 30", TR30"	22"	TR30", TR36", TR38", TR40", 15", 30", 36", 38", 40"		TR30", 15", 20", 30"	
ROW UNITS	44-7.5", 36-10"	36-10"	36-10", 23-15", 24-15" even, 18-20", 12-30", 24-TR30", 16-TR36"	60-7.5", 48-10"	58-8", 48-10"	48-10", 31-15", 32-15" even, 24-20", 16-30", 32-TR30"	24	32-TR30", 24-TR36", 24-TR38", 24-TR40", 31-15", 16-30", 12-36", 12-38", 12-40"		48-TR30", 47-15", 36-20", 24-30"	
TIRE SIZE	(4) 15x19.5 NHS & (2) 15x16.5 Skid Steer			(10) 15x16.5 Skid Steer			(10) 15x16.5 Skid Steer; Optional: (10) 15x19.5 Skid Steer	(2) 32x15.5x16.5		15-19.5 NHS 12-Ply	
*H.P. REQUIREMENTS (min)	250-350	280	150-220	350+	300+	200-320	N/A	220-300+		280-440	
<b>DIMENSIONS</b>											
WIDTH (no markers)	30'			40'			44'	40'		60'	
WIDTH (markers)	30'			40'			44'	40'		60'	
WIDTH (transport)	14' 10"			14' 10"			14' 10"	25' 2"		13' 6"	
LENGTH (transport)	39' 6"			42'			45'	16' 10"		36' 2"	
CLEARANCE (transport)	22"			22"			21"	depends on tractor hitch		22"	
HEIGHT (transport)	12' 4"			12' 4"			12' 6"	12' 6"		12' 6"	
<b>OPENER INFO</b>											
OPENER SERIES	10HDP Series	20P Series	25 Series	10HDP Series	20P Series	25 Series	25 Series	25 Series		25 Series	
OPENER DOWN PRESSURE	250-500 lbs			250-500 lbs			250-500 lbs	250-500 lbs		250-500 lbs	
OPENER TRAVEL (up-down)	10"			10"			10"	10"		10"	
OPENER DEPTH RANGE	0-3.5"			0-3.5"			0-3.5"	0-3.5"		0-3.5"	
<b>CAPACITIES</b>											
SEED CAPACITY	Seed Company Bulk Box, 82 bu Poly Hopper, 150 bu Poly Hopper			Seed Company Bulk Box, 82 bu Poly Hopper, 150 bu Poly Hopper			Seed Company Bulk Box, 82 bu Poly Hopper, 150 bu Poly Hopper	Optional 82 bu Hopper or Seed Company Bulk Box		Optional 82 bu Hoppers (2) or Seed Company Bulk Boxes (2)	
FERTILIZER CAPACITY	**Optional 400 gal fertilizer tank (2x200), semi-mounted 500 gal (SML-500)			**Optional 400 gal fertilizer tank (2x200), semi-mounted 735 gal (SML-735), semi-mounted 500 gal (SML-500)			**Optional 400 gal fertilizer tank (2x200), semi-mounted 735 gal (SML-735), semi-mounted 500 gal (SML-500)	N/A		Optional Starter Fertilizer w/2000 gallon cart, semi-mounted 1000 gal (SML-1000), semi-mounted 735 gal (SML-735), semi-mounted 500 gal (SML-500)	

\*H.P. requirements are dependent on row spacing and optional equipment. See your local Great Plains dealer for more detailed information. \*\*Will not work on 150 bushel hopper.

Note: All specifications subject to change without notice.