

SEED

YIELD-PRO® PLANTERS

PLACEMENT

LIQUID OR
DRY



Great Plains introduces our new Yield-Pro® Planter model YP-1625AHD/AHL. Designed for the operator who needs high-capacity onboard fertilizer, either liquid or dry, but wants a planter that is **simple** to operate.

This planter has a unique design that incorporates a rugged frame with the Great Plains field-proven 25 Series Opener to achieve the planting accuracy needed by today's producer for uniform emergence and higher yields.

Multiple row spacing configurations (from 15" to 36" Twin Row) allow producers to fine tune this planter to complement their operations, while maintaining the accuracy that has come to be expected by Great Plains.



Dry Fertilizer Model (AHD)



Liquid Fertilizer Model (AHL)


Great Plains
"Harvest Starts Here."

Type:

High-Capacity Fertilizer Planter

Model / Availability:

YP-1625AHD/AHL - 3115 (15" Rows)
YP-1625AHD/AHL - 2420 (20" Rows)
YP-1625AHD/AHL - 1630 (30" Rows)
YP-1625AHD/AHL - 32TR30 (Twin-Row 30")
YP-1625AHD/AHL - 1636 (36" Rows)
YP-1625AHD/AHL - 32TR36 (Twin-Row 36")

Availability: Spring 2014 (Limited)

MODEL INFO	YP-1625AHD (dry) & YP-1625AHL (liquid)					
	-3115	-2420	-1630	-32TR30	-1636	-32TR36
WORKING WIDTH	38' 9"	40'	40'	40'	48'	48'
TRANSPORT WIDTH	13' 6"					
TRANSPORT HEIGHT	12' 6"					
H.P. REQUIREMENTS	165 - 275					
NUMBER OF OPENERS	31	24	16	32	16	32
ROW SPACING	15"	20"	30"	Twin-Row 30"	36"	Twin-Row 36"
SEED CAPACITY	1.6 Bushel per Row					
FERTILIZER CAPACITY	750-Gallon Liquid Fertilizer or 100-Bushel Dry Fertilizer					
MAIN TIRES	380/90R46					
GAUGE WHEEL TIRES	15-19.5 NHS					

Specifications are subject to change without prior notification.

Standard Equipment:

- DICKEY-john® Monitor
- Ground Drive Fertilizer Metering
- 2-Section Ground Drive (Seed Meter)
- 25 Series Row Units:
 - Air-Pro® Meters
 - 1.6 bu/row Seed Hopper
 - 205 Triple Lip Seal Bearings
 - 4mm Double Disc Blades
 - Cast Blade Separator with Fertilizer Tube
 - Heavy-Duty Down Pressure (up to 500 lbs./row)
 - Clear-Shot® Seed Tubes
- 380/90R46 Main Tires
- 15-19.5 NHS Gauge Wheel Tires
- Hydraulic Flat Fold Markers

Optional Equipment:

- 750 Gal. Liquid Fertilizer
- 100 Bu. Dry Fertilizer
- Unit-Mounted Coulters w/ Fluted or Turbo Blades
- Coulters-Mounted Row Cleaners
- Unit-Mounted Stand-Alone Row Cleaners
- Liquid Fertilizer Coulters
- Dry Fertilizer Coulters
- Ground Drive Liquid Fertilizer Pump
- Liquid Fertilizer Manifold
- Keeton Seed Firmer®
- Seed-Lok®
- Closing Wheels:
 - 1 x 12 Double-V (rubber)
 - 1.25 x 13 Wedge
 - 1 x 12 Double-V Cast
 - Spider with Drag Chain

Features & Benefits



25 SERIES ROW UNIT - Opener body and cast iron parallel arms are narrower, yet stronger, than conventional 30" openers. The narrow profile allows this row unit to plant twin-row crops with each pair being only 8" apart.



TELESCOPING TONGUE - Puts the planter closer to the tractor in field position, allowing tighter turns on end rows.



380/90 R46 TIRES - Provide great flotation while being narrow enough to avoid running over any planter rows on 30" or Twin-Row 30".



POSITIVE GROUND DRIVE FERTILIZER - Large diameter spring-loaded steel wheel provides positive ground contact for excellent fertilizer metering accuracy.