

Type:

High-Capacity Fertilizer Planter

Model / Availability:

YP-1625AHD/AHL - 3115 (15" Rows)
YP-1625AHD/AHL - 2420 (20" Rows)
YP-1625AHD/AHL - 1630 (30" Rows)
YP-1625AHD/AHL - 32TR30 (Twin-Row 30")
YP-1625AHD/AHL - 1636 (36" Rows)
YP-1625AHD/AHL - 32TR36 (Twin-Row 36")

Availability: Spring 2014 (Limited)

MODEL INFO	YP-1625AHD (dry) & YP-1625AHL (liquid)					
	-3115	-2420	-1630	-32TR30	-1636	-32TR36
WORKING WIDTH	38' 9"	40'	40'	40'	48'	48'
TRANSPORT WIDTH	13' 6"					
TRANSPORT HEIGHT	12' 6"					
H.P. REQUIREMENTS	165 - 275					
NUMBER OF OPENERS	31	24	16	32	16	32
ROW SPACING	15"	20"	30"	Twin-Row 30"	36"	Twin-Row 36"
SEED CAPACITY	1.6 Bushel per Row					
FERTILIZER CAPACITY	750-Gallon Liquid Fertilizer or 100-Bushel Dry Fertilizer					
MAIN TIRES	380/90R46					
GAUGE WHEEL TIRES	15-19.5 NHS					

Specifications are subject to change without prior notification.

Standard Equipment:

- DICKEY-john® Monitor
- Ground Drive Fertilizer Metering
- 2-Section Ground Drive (Seed Meter)
- 25 Series Row Units:
 - Air-Pro® Meters
 - 1.6 bu/row Seed Hopper
 - 205 Triple Lip Seal Bearings
 - 4mm Double Disc Blades
 - Cast Blade Separator with Fertilizer Tube
 - Heavy-Duty Down Pressure (up to 500 lbs./row)
 - Clear-Shot® Seed Tubes
- 380/90R46 Main Tires
- 15-19.5 NHS Gauge Wheel Tires
- Hydraulic Flat Fold Markers

Optional Equipment:

- 750 Gal. Liquid Fertilizer
- 100 Bu. Dry Fertilizer
- Unit-Mounted Coulters w/ Fluted or Turbo Blades
- Coulters-Mounted Row Cleaners
- Unit-Mounted Stand-Alone Row Cleaners
- Liquid Fertilizer Coulters
- Dry Fertilizer Coulters
- Ground Drive Liquid Fertilizer Pump
- Liquid Fertilizer Manifold
- Keeton Seed Firmer®
- Seed-Lok®
- Closing Wheels:
 - 1 x 12 Double-V (rubber)
 - 1.25 x 13 Wedge
 - 1 x 12 Double-V Cast
 - Spider with Drag Chain

Features & Benefits



25 SERIES ROW UNIT - Opener body and cast iron parallel arms are narrower, yet stronger, than conventional 30" openers. The narrow profile allows this row unit to plant twin-row crops with each pair being only 8" apart.



TELESCOPING TONGUE - Puts the planter closer to the tractor in field position, allowing tighter turns on end rows.



380/90 R46 TIRES - Provide great flotation while being narrow enough to avoid running over any planter rows on 30" or Twin-Row 30".



POSITIVE GROUND DRIVE FERTILIZER - Large diameter spring-loaded steel wheel provides positive ground contact for excellent fertilizer metering accuracy.