

Easy Transport

SEED

YIELD-PRO® PLANTERS

PLACEMENT



New Products

YP-825AR-0822 (8) 22" Rows
YP-825AR-0830 (8) 30" Rows
YP-825AR-1630 (16)
Twin Row 30"

Great Plains introduces the YP-825AR Yield-Pro® Planter. This unique answer to the 8-Row 30" planter transport issue is sure to provide customers with ease of operation, safe transport, and seed placement accuracy that has become the standard in the industry. The YP-825AR has row spacing capabilities of 22", 30", and 30" Twin Row to match or enhance each producer's farming practices. This lift-and-rotate design uses our proven 25 Series Row Unit and Air-Pro® Meter to ensure the ultimate seed placement and spacing, regardless of row spacing.



**Great Plains**
"Harvest Starts Here."

Type:

YP-825AR-0822 (8 row) 22" Rows
YP-825AR-0830 (8 row) 30" Rows
YP-825AR-1630 (16 row) Twin Row 30"

Model / Availability:

Spring 2013 (Limited)

Standard Equipment:

25 Series Row Units:
4mm Blades
Hardened Cast Blade Separator with Liquid Fertilizer Tube
205 Triple-Lip-Seal Bearings
1.6 Bu. Seed Hopper per Row
Contact Drive
Safety Lights
DICKEY-john® PM 300 Population Monitor

Optional Equipment:

Variable Rate Hydraulic Drive
Low-Profile Flat Fold Markers
Unit-Mount Coulters
Unit-Mount Row Cleaners
Keeton Seed Firmers
Seed-Lok® Seed Firmers
Dry Granular Fertilizer
Vantage II Fertilizer Opener
Liquid Fertilizer
Placement in Row with Keeton or Blade Separator Tube
Placement off Row (Vantage I Coulters)
Swath Command™ (Point Row Shut Off)
Row-Pro™ (Pneumatic Down Pressure Control)
DICKEY-john® IntelliAg™ Monitor (Required for Hydraulic Drive,
Swath Command™ and/or Row-Pro™.)

MODEL INFO	20' NARROW TRANSPORT YIELD-PRO® PLANTER
MODELS	YP-825AR
TYPE	3-Section Folding
TIRE SIZE	8R 195 LT
H.P. REQUIREMENTS (min)	125
WEIGHT (approx. range)	15,300 Lbs. (Estimated)
DIMENSIONS	
WORKING WIDTH	20'
WIDTH (transport)	11' 10" with markers
CLEARANCE (transport)	10" Under Axle
HEIGHT (transport)	10' 5"
OPENER SERIES	25 Series
COULTERS	Optional
CAPACITY	
SEED CAPACITY	1.6 bu/row

Pricing and specifications are subject to change without prior notification. All pricing is considered U.S. funds unless otherwise stated.

Features & Benefits



LIFT-AND-ROTATE DESIGN - Folds to a narrow 11' 10" for safe, convenient transporting.



POSITIVE AIR SYSTEM - The 6" hydraulic fan provides positive air pressure to meter seeds without the worry of leaks.



25 SERIES ROW UNIT - Cast iron parallel arms are narrower, yet stronger, than conventional 30" openers which allow this unit to plant twin-row crops.



AIR-PRO® METER - For unmatched singulation. As the meter rotates, seed is held in the disc, then "dead dropped" into the seed tube, resulting in even, consistent spacing.