



P-7400 AUTO-LOAD SQUARE BALE HANDLER



Patented

The fastest and most versatile loading arm on the market.

Designed to transport one layer of bales.

- Allows you to pick up the bales while moving up to 12 mph.
- Unloads in less than 2 minutes.
- For silage or dry hay.
- Can handle 32" x 36", 24" x 48", 36" x 48" and 48" x 48" bales.
*For bales 48" x 48", must be specified when ordering.
- Adjustable sides for storage or transport.
- Easily adjustable for bales from 5' to 8' long.
- Carries up to 18 bales depending on their dimensions.
- Full load indicator.
- Requires only one operator to load and transport the bales.

Rapidity - Efficiency - Simplicity - Performance



Easy adjustment of the pusher stroke according to bale length.



Adjustable sides for storage or transport on a flatbed truck.



Heavy-duty tandems and different choice of tires.



info@pronovost.qc.ca
www.pronovost.qc.ca

Les Machineries PRONOVOST INC.
260, Haut du Lac Sud, St-Tite, Quebec, Canada, GOX 3H0
Tel.: (418) 365-7551 Fax: (888) 652-9270

MODEL		P-7400 MANUAL
Functions control		By 3 hydraulic outlets
Qty of bales according to bales dimensions: dry hay or silage	32" x 36" x 60" to 66"	18
	32" x 36" x 68" to 80"	15
	32" x 36" x 82" to 102"	12
	24" x 48" x 60" to 66"	12
	24" x 48" x 68" to 80"	10
	24" x 48" x 82" to 102"	8
	36" x 48" x 60" to 66"	12
	36" x 48" x 68" to 80"	10
	36" x 48" x 82" to 102"	8
	48" x 48" x 60" to 66"	12
	48" x 48" x 68" to 80"	10
	48" x 48" x 82" to 102"	8
Over-all length	36'-6"	
Over-all width	102" in transport position - 112" + in working position	
Platform height	53"	
Dumping angle	45°	
Dumping cylinder	2 double action	
Tread width (c/c)	83 3/8"	
Swivel hitch	Standard	
Manual jack	Standard	
Oil flow required	57 to 76 liters / min. - 15 to 20 gal. US / min.	
Oil volume required at the initial filling	60 liters - 16 gal. US transhyd. oil (initial filling done by Pronovost)	
Maximum oil reserve required in operation	9.7 liters - 2.55 gallons US	
Full load indicator	Mechanical rod	
Parking and signal lights	Included	
Axle	Tandem	
Hub capacity	10 000 lbs	
Spindle diameter	3 1/4"	
Number of wheel bolts	8 bolts	
Included tires	16.5L16.1	
Optional tires	21.5L16.1	
Recommended tractor HP	125 HP or more	
Total capacity 12 tons ¹ (GVWR)	Standard tires 16.5L16.1 with wheels W14C16.1 (280 x 404 mm)	
Total capacity 16 tons ¹ (GVWR)	Optional tires 21.5L16.1 with wheels W16C16.1 (403 x 404 mm)	
Total weight	8 970 lbs approx.	

¹For speeds not exceeding 10 MPH.
Design and specifications subject to change without notice.

Dealer: