



Premium Pintle Deckover Trailers (20,000 lbs. GVWR)



Standard Sizes

Size	Model
102" x 20'	PHFT20-20KD
102" x 25'	PHFT25-20KD
102" x 28'	PHFT28-20KD
102" x 30'	PHFT30-20KD
102" x 32'	PHFT32-20KD

Standard Specifications

Tire Size	ST235/80R16 LRE
Deck Height	34"
Tongue Length	62"
Beavertail & Ramps	5' + 5'

Standard Features

- Tandem Dually, 10,000 lbs. Axles
- 16" Radial Tires
- Electric Brakes on Both Axles
- Slipper Suspension
- 12,000 lbs. Jack
- Adjustable 3" Lunette Eye
- 5' Beavertail with Checkerplate Steel Floor
- Spring Assisted Wedge Ramps
- Beavertail Pop-up Centre, Spring Assisted
- 12" @ 19 lbs. Heavy Wide Flange Beams
- Flex Resisting Bridge
- Stake Pockets & Rub Rail
- Side Step
- Spare Tire Mount
- Powder Coated
- Pressure Treated Wood Floor
- Sealed Beam L.E.D. Lights and Harness System
- Transport Canada & DOT Approved Lighting

Options

- Spare Tire
- Torsion Axles
- Sliding Winch & Strap
- Lockable Toolbox
- Additional D-Rings
- Hydraulic Brakes
- Aluminum Wheels

Request more information: **TEL** 1-877-565-3714 **EMAIL** info@canadatrailers.com