

2027 COMMANDER X MR



Loft Green Satin

PACKAGE HIGHLIGHTS

- Smart-Lok* front differential
- Strategically positioned engine air intake and CVT inlet / outlet
- Special edition seats
- 7.6 in. digital display with keypad
- LED headlight & Can-Am LED signature
- 64 in. wide with arched A-arm
- 30 in. XPS Swamp Force tires
- 14 in. cast-aluminum wheels
- Heavy-duty front steel bumper
- Relocated 4,500 lb (2,041 kg) winch with synthetic cable and roller fairlead
- Mudguard extensions

ENGINE	1000R
Type	100 hp, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation. Strategically positioned CVT air intakes and exhaust. Lower gearing ratio and Electronic Drive Belt Protection.
Drive Train	Extra-L / H / N / R / P
Driving Assistance	Lockable front differential with exclusive Smart-Lok* technology True 4-mode traction system: 2WD / 4WD with front diff. lock / 4WD MUD / 4WD TRAIL *Smart-Lok* developed in conjunction with TEAM Industries, a market leader in the drive train industry
Power Steering	CVT Engine Braking SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar / 14 in. (35.6 cm) suspension travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with sway bar / 14 in. (35.6 cm) suspension travel
Rear Shocks	Twin tube gas charged shocks

TIRES & WHEELS

Front / Rear Tires	XPS Swamp Force 30 x 9/11 x 14 in.
Wheels	14 in. cast-aluminum

BRAKES

Front	Twin piston caliper (32 mm) / 220 mm discs
Rear	Twin piston caliper (28 mm) / 220 mm discs

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,827 lb (829.1 kg)
Cage	Profiled cage ROPS approved
L x W x H	132 x 64 x 74.2 in. (335.2 x 162.6 x 188.5 cm)
Wheelbase	90.6 in. (230.1 cm)
Ground Clearance	15 in. (38.1 cm)
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Power Tilt Bed	Manual tilt
Storage Capacity	Total: 7.3 gal (27.6 L)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,030 lb (467.2 kg)
Fuel Capacity	10 gal (38 L)
Person Capacity	2

FEATURES

Gauge	7.6 in. display
Battery	18 Ah (270 CCA)
Magneto	650 watts
Instrumentation	DC outlet (10-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	LED headlight LED signature LED taillights
Winch	Relocated 4,500 lb (2,041 kg) winch with synthetic cable and roller fairlead
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors • Full heavy-duty HMW plastic skid plate • Mudguards / mudguard extensions • Heavy-duty front steel bumper
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	1-year BRP Limited warranty
Extended Service Terms	B.E.S.T. term available up to 48 months



© 2026 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. † Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SxS) operator's guide and watch the safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SxSs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold hand grips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly.

