

makes a difference

Metal Paint & Prep Phosphatizer

Metal Paint and Prep Phosphatizer is a complete and economical phosphatizing agent for the phosphatizing of iron and steel parts prior to painting. Effective in spray, dip and wipe-on applications. Metal Paint and Prep Phosphatizer works well in hard or soft water and rinses completely.

Benefits

- Spray, Dip or Wipe Application
- Excellent Paint Preparation
- Rinse Easily and Completely









Dilution Ratio: 4 - 8 ounces per gallon (1:32 1:16), 5 gallons makes 165 gallons

To Apply: Apply using a pressure washer, dip tank or by hand application. Rinse thoroughly with water.

Directions: INDUSTRIAL USE ONLY. Read the Safety Data Sheet thoroughly before using this product. Use 4 - 8 ounces per gallon per gallon of 120 to 180°F water (pH 6.6 at dilution), depending on the method of application, the weight of the coating desired and the temperature.

Product Information

Part No.	Size	Gross weight	Dimensions (L x W x H) inches	Ship UPS
8.698-197.0	5 gal	51 lb.	12.5 x 12.5 x 15	Yes
8.698-198.0	55 gal	535 lb.	23.5 x 23.5 x 35	NO

Technical Data

Color: Colorless

Scent: Detergent - solvent

Foam 1-5: 1 = Low

Reaction in Hard Water 1-5: 5 = Best

pH at Full Strength: 3.1

pH at Use Dilution (4 - 8 oz per gallon): 4.4 - 6.6

Surcty	
HMIS Safety Rating: Health	1
HMIS Safety Rating: Flammability	1
HMIS Safety Rating: Reactivity	0

OSHA/WHMIS/GHS-Compliant SDS available, listed with Infotrac. For emergency spills call 1-800-535-5053, International 1-352-323-3500.

Certifications

Kosher Certified: Use year round, not including Passover.

Smog & Ozone: In accordance with AQMD Rule 102, this product contains 0% photochemically reactive ingredients to contribute to smog or attack the earth's ozone layer.

VOC: This product contains 0.03% California Consumer Products VOC at 2 oz. / gal.

Safety

Personal Protective Equipment