KÄRCHER MC 80



Engine

Yanmar three-cylinder engine

Drive type

Power

Emission standard

Diesel 42 HP (31 kW)

Tier 4 Final

Diesel particulate filter

Fuel tank

Diesel 11 gal (42 l)

Drive & Brakes

Steering Articulating
Speed 16 mph (25 km/h)

Climbing ability 25 %

Brakes Hydrostatic brake acting on rear wheels; additional hydraulic brake (drum brake)

acting on front and rear axle.

Hydraulics & Electrical

Hydraulic reservoir 7.9 gal (30 l)
Voltage 12 volt system

Weight & Dimensions

Unladen/tare weight (empty) 4,133 lb (1,875 kg)
Total permissible weight 5,525 lb (2,500 kg)
Axle load 1,378 lb (625 kg)

(L x W x H) 127" x 42" x 78" (3,237 mm x 1,075 mm x 1,980 mm)

Turning radius inside | outside 2.99' (0.91 m) | 6.5' (1.98 m)

Hopper & Water System

Container capacity 1 cu. yd. (0.8 m³)
Standard emptying height 61" (1,565 mm)
Hopper liner Stainless steel
Fresh water tank 50 gal (190 l)

Recyling water Yes

Tires

Tires 23x10.5-12

Brushes

Material Polypropylene - steel wire

Working width (2-brush-system) 73" (1,850 mm)

Area performace (2-brush-system) 18,500 m²h @ working speed of 6 mph (10 km/h)

Working width (3-brush-system) 88" (2,240 mm)

Area performance (3-brush-system) 22,400 m²h @ working speed of 6 mph (10 km/h)