2026 MAVERICK R X RS



PACKAGE OPTIONS

- Smart-Shox™ Technology featuring Live Valve Gen 3

PACKAGE HIGHLIGHTS

- 77 in. 4-link trailing arm with aluminum HD tall knuckle
- Smart-Lok™* front differential
- FOX[†] 3.0 PODIUM RC2[†] Piggyback with bypass, dual speed compression and rebound adjustments
- 10.25 in. touchscreen display
- 32 in. ITP XNR Tenacity tires
- 16 in. flow formed beadlock wheels
- · Front and rear cameras
- · Telescopic steering wheel with infotainment controls
- Full hard roof
- · Full heavy-duty HMW plastic skid plate
- 4-point harness with shoulder pads
- Premium high-performance LED headlights
- Can-Am LED signature
- · Center dashboard storage with cellphone holder
- X-package graphics/seats
- 1700 W magneto

Terms

999T DCT
240 hp, Rotax* 999T engine, 999 cc Turbocharged Triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Rotax DCT, 7-speed with High & Low range
Lockable front differential with exclusive Smart-Lok True 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL
High torque Gen 2 Tri-Mode DPS™
Forged aluminum heavy-duty tall knuckle Double A-arm with sway bar / 25 in. (63.5 cm) suspension travel
FOX 2.5 PODIUM RC2 Piggyback with bypass, dual speed compression and rebound adjustments OR FOX 2.5 PODIUM† Piggyback with bypass and Smart-Shox™ Technology featuring Live Valve Gen 3 (Dual Valve compression & rebound)
4-link trailing arm with forged aluminum heavy-duty tall knuckle / 25.5 in. (64.8 cm) suspension travel
FOX 3.0 PODIUM RC2 Piggyback with bypass, dual speed compression and rebound adjustments OR FOX 3.0 PODIUM† Piggyback with bypass and Smart-Shox Technology featuring Live Valve Gen 3 (Dual Valve compression & rebound)
ITP XNR Tenacity 32 x 10 x 16 in.
16 in. aluminum flow formed beadlock
32 mm hydraulic triple-piston calipers with a 265 mm disc
30 mm hydraulic twin-piston calipers with a 255 mm disc

DIMENSIONS & CAPACITIES

DIMENSIONS & CAPACITIES		
Estimated Dry Weight	2,274 lb (1,031 kg) 2,284 lb (1,035 kg) with Smart-Shox	
Chassis/Cage	High strength (dual phase) steel tubing and stampings	
LxWxH	140 x 78.1 x 71.5 in. (355.6 x 198.5 x 181.5 cm)	
Wheelbase	108 in. (274.3 cm)	
Ground Clearance	17 in. (43.2 cm)	
Rack Capacity	200 lb (90 kg)	
Storage Capacity	Total: 2.1 gal (8.1 L)	
Fuel Capacity	13.2 gal (50 L)	
FEATURES		
Gauge	4.5 in. wide digital display with keypad & 10.25 in. touchscreen display	
Instrumentation	USB-A (2 charging ports & 1 communication port) DC outlet (10 A)	
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button	
Lighting	Premium high-performance LED headlights Can-Am LED signature	
Winch	Winch-ready bumper (4,500 lb / 2,041 kg winch not installed)	
Magneto	1700 W	
Protection	Full hard roof Premium half doors Front lower deflector Front / Rear anchor Full plastic skid plate	
WARRANTY & EXTEN	DED SERVICE	
Factory Warranty	1-year BRP limited warranty	
Extended Service	B.E.S.T. term available up to 30 months	



