

Technical sheet :

# **TMM 20 4W**


---



Technical characteristics			Metric	Imperial
1.1	Manufacturer		Manitou	Manitou
1.2	Model Name		TMM 20 4W	TMM 20 4W
1.2.1	Reach out equipment		Telescopic forks	Telescopic forks
1.3	Power source		Diesel	Diesel
1.4	Operator type		Seated	Seated
1.5	Max. capacity	Q	2000 kg	4409 lbs
1.6	Load centre of gravity	c	600 mm	23.622 in
1.8	Load distance, centre of drive axle to fork	x	-500 mm	-19.685 in
1.9	Wheelbase	y	1598 mm	62.913 in
Weight				
2.1	Service Weight		2450 kg	5401 lbs
Wheels				
3.1	Tyres type		Inflatable	Inflatable
3.2	Dimensions of front wheels		23 x 9 - 10 IC30	23 x 9 - 10 IC30
3.3	Dimensions of rear wheels		23 x 9 - 10 IC30	23 x 9 - 10 IC30
3.5	Number of front wheels / rear wheels		2 / 1	2 / 1
3.5.1	Drive wheels (front / rear)		2 / 1	2 / 1
3.6	Front wheel gauge	b10	2095 mm	82.48 in
Dimensions				
4.7	Height of overhead guard (cabin)	h6	2080 mm	81.89 in
4.19	Overall length	l1	2598 mm	102.283 in
4.21	Overall width	b1	2315 mm	91.142 in
4.22	Forks section / width / length	s / e / l	55 mm x 170 mm x 1350 mm	2.165 in x 6.693 in x 53.15 in
4.23	Fork carriage ISO 2328 (class/form) A/B		2A	2A
4.24	Fork carriage width	b3	1260 mm	49.606 in
4.26	Distance between wheel arms/loading surfaces	b4	1492 mm	58.74 in
4.32	Ground clearance at centre of wheelbase	m2	230 mm	9.055 in
4.28	Max. Reach	l4	1005 mm	39.567 in
4.37	Overall length (without forks)	l7	2285 mm	89.961 in
4.38	Length across wheel arms (4W position)	l8	2320 mm	91.339 in
4.35	Turning radius	Wa	2463 mm	96.969 in
Performances				
5.1	Travel speed (laden / unladen)		10 km/h / 10 km/h	6.2 mph / 6.2 mph
5.7	Gradeability - laden / unladen		43 % / 26 %	43 % / 26 %
5.9	Service brake		Hydraulic	Hydraulic
5.11	Transmission type		Hydrostatic	Hydrostatic
Engine				
7.1	Engine brand		Kubota	Kubota
7.4	Number of cylinders / Capacity of cylinders		4 - 1498 cm <sup>3</sup>	4 - 91.41 in <sup>3</sup>
7.3	Rated speed		3000 tr/min	3000 tr/min
7.2	Engine power according to ISO 1585		26.5 kW	26.5 kW
Miscellaneous				
8.2	Working hydraulic pressure for attachments (bar)		190 Bar	13 PSI
8.3	Oil flow rate for attachments		43 l/min	43 l/min

	Miscellaneous			
8.4	Sound level at the driver's ear according to DIN 12 053		86 dB(A)	86 dB(A)

## Dimensional drawing



## Characteristics of masts and residual capacities

		Full Visibility Duplex				
		FVD 30	FVD 36	FVD 39		
Dual Capacity (Maximum Height & LC = 600)	Simple Reach	h1 - Height mast Lowered	mm	2352	2702	2852
		h3 - Lifting Height	mm	3000	3600	3900
		h4 - Height mast extended	mm	4455	5055	5355
		Pantograph reach in	kg	2000	2000	2000
		Pantograph reach out with stabilizers	kg	1750	1750	1750
		Pantograph reach out without stabilizers	kg	1100	1050	1000
	Double Reach	Telescopic forks reach in	kg	2000	2000	2000
		Telescopic Forks reach out with stabilizers	kg	1300	1300	1300
		Telescopic Forks reach out without stabilizers	kg	1150	1100	1050
		Pantograph & TF reach in	kg	2000	2000	2000
		Pantograph & TF reach out with stabilizers	kg	1100	1100	1100
		Pantograph & TF reach out without stabilizers	kg	550	550	550


## Equipment

Standard
3 braked wheels
4 Way System
Telescopic Forks
Three-function FNR handling levers
Optional
Complete road lighting
Extenseur
Flashing Light
Forks positioner
Front right and left working lights (x2)
Outside right rear-view mirror
Primo seat
Protective seat cover

Optional

Reversing warning buzzer

Special color paints



Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508  
RCS Nantes