

2026 MAVERICK X3 X_{MR} 64"



Loft Green Satin

PACKAGE HIGHLIGHTS

- Smart-Lok™** front differential
- FOX® 2.5 PODIUM QS3® Piggyback shocks
- Snorkeled engine air intake and CVT
- Belt monitoring system
- 850 W magneto
- 30 in. XPS Swamp King tires
- Front bumper, half-doors
- 4,500 lb (2,041kg) winch with synthetic rope
- Full heavy-duty HMW plastic skid plate
- Front and rear tow hooks
- 7.6 in. digital display with keypad
- X-package graphics/seats
- Can-Am LED signature

ENGINE	TURBO RR
Type	200 hp, Rotax® ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler, high-performance air filter and strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT, high airflow with strategically positioned CVT air intake and exhaust, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok technology True 4-mode traction system: 2WD / 4WD with front diff. lock / 4WD MUD / 4WD TRAIL
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar / 20 in. (50.8 cm) suspension travel
Front Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links / 20 in. (50.8 cm) suspension travel
Rear Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment and bottom-out control
TIRES & WHEELS	
Front / Rear Tires	XPS Swamp King 30 x 10 x 15 in.
Wheels	15 in. cast-aluminum
BRAKES	
Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,730 lb (784.4 kg)
Chassis/Cage	Dual-phase 980 steel
L x W x H	133 x 66.7 x 66.1 in. (337.8 x 169.4 x 167.9 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ® quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES

Gauge	7.6 in. digital display with keypad
Instrumentation	DC outlet (10 A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlight LED signature LED taillights
Winch	4,500 lb (2,041 kg) winch with synthetic cable
Magneto	850 W
Protection	Front bumper Half-doors Front and rear tow hooks Full heavy-duty HMW plastic skid plate

WARRANTY & EXTENDED SERVICE

Factory Warranty	1-year BRP limited warranty
Extended Service	B.E.S.T. term available up to 30 months
Terms	



© 2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. 1 Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SxS) operator's guide and watch the safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SxSs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold hand grips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly. *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry.

