



## **(VESPA PRIMAVERA)<sup>RED</sup> 50 – TECHNICAL SPECIFICATIONS**

|                                     |                                                                         |
|-------------------------------------|-------------------------------------------------------------------------|
| <b>ENGINE</b>                       | Single cylinder 4-stroke, 3 valves, i-get                               |
| <b>ENGINE CAPACITY</b>              | 49 cc                                                                   |
| <b>BORE X STROKE</b>                | 39 mm x 41.4 mm                                                         |
| <b>MAX POWER AT THE CRANK SHAFT</b> | 2.3 kW - 3.1 HP - at 7,750 rpm                                          |
| <b>MAX TORQUE</b>                   | 3.1 Nm at 5,750 rpm                                                     |
| <b>CONSUMPTION</b>                  | 38,5 km/l                                                               |
| <b>CO2 EMISSIONS COMPLIANCE</b>     | 59 g/km                                                                 |
| <b>FUEL SYSTEM</b>                  | Electronic injection                                                    |
| <b>COOLING</b>                      | Forced air                                                              |
| <b>STARTER</b>                      | Electric                                                                |
| <b>GEARBOX</b>                      | CVT continuously variable transmission with torque server               |
| <b>CLUTCH</b>                       | Automatic centrifugal dry clutch with vibration dampers                 |
| <b>LOAD-BEARING STRUCTURE</b>       | Sheet steel body with welded reinforcements                             |
| <b>FRONT SUSPENSION</b>             | Single-sided link arm with coil spring and hydraulic monoshock absorber |
| <b>REAR SUSPENSION</b>              | Coil spring with hydraulic monoshock absorber                           |
| <b>FRONT BRAKE</b>                  | Ø 200 mm stainless steel disc with hydraulic control                    |
| <b>REAR BRAKE</b>                   | Ø 140 mm drum mechanically operated                                     |
| <b>ABS SYSTEM</b>                   | -                                                                       |
| <b>FRONT TYRE</b>                   | Tubeless 110/70 - 12"                                                   |
| <b>REAR TYRE</b>                    | Tubeless 120/70 - 12"                                                   |
| <b>LENGTH / WIDTH /WHEELBASE</b>    | 1,860 / 745 / 1,330 mm                                                  |
| <b>SEAT HEIGHT</b>                  | 785 mm                                                                  |
| <b>FUEL TANK CAPACITY</b>           | 7,5 litri                                                               |
| <b>EMISSIONS COMPLIANCE</b>         | Euro 5                                                                  |