



## PRIMAVERA 50 – TECHNICAL SPECIFICATIONS

<b>ENGINE</b>	Single cylinder 4-stroke, 3 valves, i-get Single cylinder
<b>DISPLACEMENT</b>	49 cc
<b>BORE X STROKE</b>	39 mm x 41,4 mm
<b>MAX POWER AT</b>	2.3 kW - 3.1 HP - at 7,750 rpm
<b>THE CRANK SHAFT</b>	
<b>MAX TORQUE</b>	3.1 Nm at 5,750 rpm
<b>CONSUMPTION</b>	38,5 km/l
<b>CO2 EMISSIONS</b>	59 g/km
<b>COMPLIANCE</b>	
<b>FUEL SYSTEM</b>	Electronic injection
<b>COOLING</b>	Forced air
<b>STARTER</b>	Electric
<b>GEARBOX</b>	CVT continuously variable transmission with torque server
<b>CLUTCH</b>	Automatic centrifugal dry clutch with vibration dampers
<b>LOAD-BEARING</b>	Sheet steel body with welded reinforcements
<b>STRUCTURE</b>	
<b>FRONT</b>	Single-sided link arm with coil spring and hydraulic monoshock absorber
<b>SUSPENSION</b>	
<b>REAR</b>	Coil spring with hydraulic monoshock absorber
<b>SUSPENSION</b>	
<b>FRONT BRAKE</b>	Ø 200 mm stainless steel disc with hydraulic control
<b>REAR BRAKE</b>	Ø 140 mm drum mechanically operated
<b>ABS SYSTEM</b>	-
<b>FRONT TYRE</b>	Tubeless 110/70 - 12"
<b>REAR TYRE</b>	Tubeless 120/70 - 12"
<b>LENGTH /</b>	1,860 / 745 / 1,330 mm
<b>WIDTH / WHEELBASE</b>	
<b>SEAT HEIGHT</b>	785 mm
<b>FUEL TANK CAPACITY</b>	7,5 litres
<b>EMISSIONS COMPLIANCE</b>	Euro 5