



VESPA PRIMAVERA BATIK 50 – TECHNICAL SPECIFICATIONS

ENGINE Single cylinder 4-stroke, 3 valves, i-get Single cylinder

DISPLACEMENT 49 cc

BORE X STROKE 39 mm x 41,4 mm

MAX POWER AT THE CRANK SHAFT 2.3 kW - 3.1 HP - at 7,750 rpm

MAX TORQUE 3.1 Nm at 5,750 rpm

CONSUMPTION 38,5 km/l

CO2 EMISSIONS 59 g/km

COMPLIANCE

FUEL SYSTEM Electronic injection

COOLING Forced air

STARTER Electric

GEARBOX CVT continuously variable transmission with torque server

CLUTCH Automatic centrifugal dry clutch with vibration dampers

LOAD-BEARING Sheet steel body with welded reinforcements

STRUCTURE

FRONT Single-sided link arm with coil spring and hydraulic monoshock

SUSPENSION absorber

REAR Coil spring with hydraulic monoshock absorber

SUSPENSION

FRONT BRAKE Ø 200 mm stainless steel disc with hydraulic control

REAR BRAKE Ø 140 mm drum mechanically operated

ABS SYSTEM -

FRONT TYRE Tubeless 110/70 - 12"

REAR TYRE Tubeless 120/70 - 12"

LENGTH / WIDTH / 1,860 / 745 / 1,330 mm

WHEELBASE

SEAT HEIGHT 785 mm

FUEL TANK CAPACITY 7,5 litres

EMISSIONS Euro 5

COMPLIANCE