

S450 SPECS & COMPARE

▲ S450 Key Specifications

S450

Horsepower

49 hp

Rated Operating Capacity

1370 lbs

Tipping Load

2740 lbs

Operating Weight

5370 lbs

Travel Speed - High (1-Speed)

7.6 mph

Travel Speed - Low (2-Speed)

6.5 mph

Travel Speed - High (2-Speed)

9.2 mph

Auxiliary Std Flow

16.7 gpm

Aux System Pressure

3300 psi

Length without Attachment

98.4 in

Overall Width

58.6 in

Overall Height

77.8 in

Height to Hinge Pin

109.5 in

Reach @ Maximum Height

20.8 in

▼ Engine

S450

Horsepower

49 hp

▼ Performance

S450

Rated Operating Capacity

1370 lbs

Tipping Load

2740 lbs

Operating Weight

5370 lbs

Travel Speed (2-speed option)

9.2 mph

Travel Speed - High (1-Speed)

7.6 mph

Travel Speed - Low (2-Speed)

6.5 mph

Travel Speed - High (2-Speed)

9.2 mph

▼ Capacities

S450

Fuel Tank

14.2 gal

▼ Hydraulic System

S450

System Relief @ Quick Couplers

3250 psi

Auxiliary Std Flow

16.7 gpm

Aux System Pressure

3300 psi

▼ Dimensions

S450

Length with Standard Bucket

124.9 in

Length without Attachment

98.4 in

Width (with bucket)

62 in

Overall Width

58.6 in

Overall Height

77.8 in

Height to Hinge Pin

109.5 in

Reach @ Maximum Height

20.8 in

Turning Radius

76.4 in

Wheelbase

35.4 in

Standard Bucket

62 in

Standard Tires

10X16.5

▼ **Instrumentation**

S450

Fuel Gauge

Yes

Hourmeter

Yes

Engine Coolant Temperature

Yes

Engine Air Filter

Replaceable dry paper cartridge with separate safety element

Engine Oil Pressure

Yes

▼ **Features**

S450

Joystick Control

Optional

Air Conditioning

Optional

Adjustable Seat

Standard

Backup Alarm

Standard

BICS System (Interlock)

Standard

Cab Enclosure

Optional

Sound Option

Optional

Cab Heater

Optional

Operating Lights

Standard

Parking Brake

Standard

Radio

Optional

Turbocharged Engine

Standard

Rear Window

Standard

Top Window

Standard

Lift-Arm Support

Standard

Seat Belt

Standard

Suspension Seat

Optional

Two Speed Travel

Optional

Deluxe Instrumentation

Optional

Engine Shutdown

Standard

Hydraulic Bucket Positioning

Optional

High Flow Option

Not Applicable

Auxiliary Hydraulics

Standard

Spark Arrestor Muffler

Standard

Bob-Tach Attachment System

Standard

Power Bob-Tach

Optional

ACS (Switchable Controls)

Not Applicable

Ride Control

Optional

Rear Hydraulics

Optional

Horn

Standard