

E48 Specs & Compare

▲ E48 Key Specifications

E48

Horsepower

42.6 hp

Operating Weight

9830 lbs

Arm Digging Force

5820 lbf

Travel Speed (Maximum)

3.3 mph

Bucket Digging Force

9601 lbf

Dig Depth

10.4 ft

Max Dump Height

150.6 in

Reach at Ground Level

17.3 ft

Transport Length

200.5 in

Width

72.8 in

Cab Height

99.1 in

Tail Swing Overhang

12 in

Turbocharged Engine

Standard

▼ **Engine**

E48

Horsepower

42.6 hp

Engine Model

D18

Maximum Governed RPM

2200 rpm

Turbocharged Engine

Standard

▼ **Performance**

E48

Operating Weight

9830 lbs

Weight Class

4 t

Travel Speed - Low

1.6 mph

Arm Digging Force - Standard Arm

5820 lbf

Travel Speed (Maximum)

3.3 mph

Bucket Digging Force

9601 lbf

Rated Lift Capacity

4921 lbs

Lift Radius

118 in

Boom Swing - Left

75 deg

Boom Swing - Right

50 deg

Dig Depth - Standard Arm

10.4 ft

Max Dump Height - Standard Arm

150.6 in

Maximum Reach at Ground Level

17.3 ft

▼ **Capacities**

E48

Fuel Tank

19 gal

▼ **Hydraulic System**

E48

Auxiliary Pressure

3045 psi

Auxiliary Std Flow

20 gpm

▼ **Dimensions**

E48

Length

200.5 in

Overall Transport Length - Standard Arm

200.5 in

Width

72.8 in

Cab Height

99.1 in

Tail Swing Overhang - Standard Arm

12 in

▼ **Features**

E48

Air Conditioning

Optional

Swing Boom

Standard

Cab Enclosure

Optional

Radio

Optional

Engine Shutdown

Standard

Auxiliary Hydraulics

Standard

Quick Tach System

Standard

Rubber Track

Standard

Selectable Auxiliary Hydraulic Flow

Standard

Angle Blade

Optional