

L205 Specs & Compare

▲ L205 Key Specifications

L205

Horsepower

142 hp

Tipping Capacity with Bucket (Straight)

23070 lbs

Tipping Capacity with Bucket (Articulated)

20370 lbs

Rated Operating Capacity with Bucket (Articulated)

10185 lbs

Rated Operating Capacity with Bucket (Straight)

11535 lbs

Bucket Capacities

2.5-4.0 yd³ (1.9-3.0 m³)

Max. Travel Speed – Forward

23.6 mph

Operating Weight

27274 lbs

Max. Travel Speed – Reverse

12.4 mph

3rd Spool Pressure

4351 psi

3rd Spool Max. Flow Rate

40.9 gpm

Length with Standard Bucket

295.7 in

Length without Attachment

249.6 in

Width (with bucket)

100.4 in

Height to Bucket Hinge Pin

147 in

▼ **Engine**

L205

Horsepower

142 hp

▼ **Performance**

L205

Rated Operating Capacity with Forks (Straight)

6754 lbs

Rated Operating Capacity with Forks (Articulated)

5874 lbs

Tipping Capacity with Bucket (Straight)

23070 lbs

Tipping Capacity with Bucket (Articulated)

20370 lbs

Rated Operating Capacity with Bucket (Articulated)

10185 lbs

Rated Operating Capacity with Bucket (Straight)

11535 lbs

Bucket Capacities

2.5-4.0 yd³ (1.9-3.0 m³)

Max. Travel Speed – Forward

23.6 mph

Operating Weight

27274 lbs

Max. Travel Speed – Reverse

12.4 mph

▼ **Capacities**

L205

Fuel Tank

62.1 gal

▼ **Hydraulic System**

L205

Main Pump Pressure

3843 psi

3rd Spool Pressure

4351 psi

3rd Spool Max. Flow Rate

40.9 gpm

Main Pump Max. Flow Rate

40.9 gpm

▼ **Dimensions**

L205

Inside Turning Radius With Bucket

231.2 in

Outside Turning Radius

211.2 in

Articulation Angle

40 deg

Length with Standard Bucket

295.7 in

Length without Attachment

249.6 in

Width (with bucket)

100.4 in

Height with Operator Cab

130.3 in

Width (w/out Attachment)

99.6 in

Height to Bucket Hinge Pin

147 in

Dump Angle @ Maximum Height

46 deg

Ground Clearance

17 in

Rollback Angle

49 deg

Wheelbase

120 in

Tire Size

20.5R25(L3)

Wheel Tread

75.9 in

▼ **Drive System**

L205

Main Drive

Hydrostatic 4F/3R

▼ **Features**

L205

Joystick Control

Standard

Z-Bar Linkage

Standard

Inching Control

Standard

Return to Dig

Standard

Non-DPF

Not Applicable

Quick Coupler

Optional

Auxiliary Hydraulics

Standard

Ride Control

Standard