

E26 Specs & Compare

▲ E26 Key Specifications

E26

Horsepower

24.8 hp

Operating Weight

6489 lbs

Arm Digging Force

3547 lbf

Travel Speed (Maximum)

3.2 mph

Bucket Digging Force

5652 lbf

Dig Depth

114.4 in

Max Dump Height

128.8 in

Reach at Ground Level

192 in

Transport Length

170.4 in

Width

61 in

Cab Height

96 in

Tail Swing Overhang

3.5 in

Turbocharged Engine

Not Applicable

▼ **Engine**

E26

Horsepower

24.8 hp

Engine Model

D1305-E4B-BCZ-1

Maximum Governed RPM

2550 rpm

Turbocharged Engine

Not Applicable

▼ **Performance**

E26

Operating Weight

6489 lbs

Weight Class

3 t

Travel Speed - Low

1.8 mph

Arm Digging Force - Standard Arm

3547 lbf

Travel Speed (Maximum)

3.2 mph

Bucket Digging Force

5652 lbf

Rated Lift Capacity

2359 lbs

Lift Radius

118 in

Boom Swing - Left

70 deg

Boom Swing - Right

55 deg

Dig Depth - Standard Arm

114.4 in

Max Dump Height - Standard Arm

128.8 in

Maximum Reach at Ground Level

192 in

▼ **Capacities**

E26

Fuel Tank

9.1 gal

▼ Hydraulic System

E26

Auxiliary Pressure

2611 psi

Auxiliary Std Flow

14.2 gpm

▼ Dimensions

E26

Length

170.4 in

Overall Transport Length - Standard Arm

170.4 in

Width

61 in

Cab Height

96 in

Tail Swing Overhang - Standard Arm

3.5 in

▼ Features

E26

Air Conditioning

Optional

Swing Boom

Standard

Cab Enclosure

Optional

Cab Heater

Optional

Heater Air Conditioning

Optional

Radio

Optional

Engine Shutdown

Standard

Auxiliary Hydraulics

Standard

Secondary Auxiliary Hydraulics

Not Applicable

Quick Tach System

Standard

Rubber Track

Standard

Selectable Auxiliary Hydraulic Flow

Standard

Angle Blade

Not Applicable

