

L28 Specs & Compare

▲ **L28 Key Specifications**

L28

Horsepower

24.8 hp

Rated Operating Capacity (ISO) (Articulated)

1222 lbs

Rated Operating Capacity (ISO) (Straight)

1534 lbs

Operating Weight

4195 lbs

Auxiliary Std Flow

11.4 gpm

Width (over tires)

46.5 in

▼ **Engine**

L28

Horsepower

24.8 hp

Fuel Consumption

1.1 gph

▼ **Performance**

L28

ROC with Counterweight Option - Straight

1952 lbs

ROC with Counterweight Option - Articulated

1475 lbs

Rated Operating Capacity (ISO) (Straight)

1534 lbs

Rated Operating Capacity (ISO) (Articulated)

1222 lbs

Operating Weight

4195 lbs

Travel Speed

8.3 mph

▼ Capacities

L28

Fuel Tank

9.6 gal

▼ Hydraulic System

L28

System Relief @ Quick Couplers

2900 psi

Auxiliary Std Flow

11.4 gpm

▼ Dimensions

L28

Height to Bucket Hinge Pin - Retracted

85.4 in

Inside Turning Radius

78.2 in

Outside Turning Radius

100.9 in

Height to Bucket Hinge Pin - Extended

104.4 in

Articulation Angle

43 deg

Length with Standard Bucket

122.4 in

Length without Attachment

93.2 in

Width (with bucket)

50 in

Width (over tires)

46.5 in

Reach @ Maximum Height

30.9 in

Dump Angle @ Maximum Height

40 deg

Ground Clearance

5.5 in

Rollback Angle

32 deg

Wheelbase

47.2 in

Tire Size

23X10.5-12, 8 PLY

Wheel Tread

▼ **Drive System**

L28

Main Drive

Hydrostatic drive with 4 individual drive motors

▼ **Features**

L28

Front and Rear Work Lights

Standard

Air Conditioning

Not Applicable

Backup Alarm

Standard

Cab Enclosure

Optional

Cab Heater

Optional

Operating Lights

Optional

Turbocharged Engine

Not Applicable

Rear Window

Optional

Rotating Flashing Beacon

Optional

Lift-Arm Support

Standard

Grab Handles

N/A

Suspension Seat

Standard

Turn Signals

Optional

Two Speed Travel

Not Applicable

Deluxe Instrumentation

Not Applicable

Hydraulic Bucket Positioning

Standard

Auxiliary Hydraulics

Standard

Spark Arrestor Muffler

Standard

Bob-Tach Attachment System

Standard

Tires-Ply Rating

8

Cup Holder

Standard

Horn

Standard