

L35 Specs & Compare

▲	L35 Key Specifications
L35	
Horsepower	
57 hp	
Rated Operating Capacity (ISO) (Articulated)	
1695 lbs	
Rated Operating Capacity (ISO) (Straight)	
2072 lbs	
Operating Weight	
6012 lbs	
Lift Breakout Force (ISO)	
4000 lbf	
Auxiliary Std Flow	
18 gpm	
Width (over tires)	
52.4 in	
Ride Control	
Optional	

▼ Engine

L35	
Horsepower	
57 hp	

Turbocharged Engine

Standard

▼ Performance

L35

ROC with Counterweight Option - Straight

2472 lbs

ROC with Counterweight Option - Articulated

2017 lbs

Rated Operating Capacity (ISO) (Straight)

2072 lbs

Rated Operating Capacity (ISO) (Articulated)

1695 lbs

Operating Weight

6012 lbs

Travel Speed

16.2 mph

Lift Breakout Force (ISO)

4000 lbf

▼ Capacities

L35

Fuel Tank

13.5 gal

▼ Hydraulic System

L35

System Relief @ Quick Couplers

3045 psi

Auxiliary Std Flow

18 gpm

Auxiliary High Flow

25.3 gpm

▼ **Dimensions**

L35

Height to Bucket Hinge Pin - Retracted

88.2 in

Inside Turning Radius

92.8 in

Outside Turning Radius

111.2 in

Length

148.5 in

Height to Bucket Hinge Pin - Extended

114.8 in

Articulation Angle

43 deg

Length with Standard Bucket

148.5 in

Length without Attachment

110.9 in

Width (with bucket)

54 in

Height with Operator Cab

82.2 in

Width (over tires)

52.4 in

Reach @ Maximum Height

38.6 in

Dump Angle @ Maximum Height

40 deg

Ground Clearance

6.5 in

Rollback Angle

32 deg

Wheelbase

57.2 in

Tire Size

26X12-12 10 PLY

Wheel Tread

40.3 in

▼ **Controls**

L35

Auxiliary Hydraulics Type

Finger Tip Control

▼ **Drive System**

L35

Main Drive

Hydrostatic pump driving 4 independent wheel motors

▼ **Features**

L35

Front and Rear Work Lights

Standard

Air Conditioning

Optional

Adjustable Seat

Standard

Backup Alarm

Standard

BICS System (Interlock)

Standard

Cab Enclosure

Optional

ROPS/FOPS Approved

Standard

Cab Heater

Optional

Operating Lights

Standard

Traction Control

Optional

Auto Idle

Optional

Radio

Optional

Turbocharged Engine

Standard

Rear Window

Optional

Rotating Flashing Beacon

Optional

Lift-Arm Support

Standard

Grab Handles

N/A

Seat Belt

Standard

Suspension Seat

Standard

Turn Signals

Optional

Two Speed Travel

Standard

Deluxe Instrumentation

Not Applicable

High Flow Option

Optional

Auxiliary Hydraulics

Standard

Spark Arrestor Muffler

Standard

Bob-Tach Attachment System

Standard

Tires-Ply Rating

10

Heavy-Duty Float Tires

Optional

Power Bob-Tach

Optional

Ride Control

Optional

Cup Holder

Standard

Horn

Standard