

L65 Specs & Compare

▲ L65 Key Specifications

L65

Horsepower

55 hp

Engine Model

DM02-MFL05

Rated Operating Capacity with Bucket (Straight)

3133 lbs

Rated Operating Capacity with Bucket (Articulated)

2618 lbs

Rated Operating Capacity with Forks (Straight)

3759 lbs

Rated Operating Capacity with Forks (Articulated)

3172 lbs

Tipping Load - Straight

6266 lbs

Operating Weight

9944 lbs

Travel Speed - Low

4.9 mph

Travel Speed - High

15.1 mph

Auxiliary Std Flow

19.9 gpm

Inside Turning Radius w/bkt

78.7 in

Height to Hinge Pin - Fully Raised

127 in

Length with Standard Bucket

218 in

Width (with bucket)

74.8 in

Width (over tires)

69.7 in

Height with Operator Cab

97.4 in

Wheelbase

82.7 in

▼ **Engine**

L65

Horsepower

55 hp

Engine Model

DM02-MFL05

▼ **Performance**

L65

Rated Operating Capacity with Bucket (Straight)

3133 lbs

Rated Operating Capacity with Bucket (Articulated)

2618 lbs

Rated Operating Capacity with Forks (Straight)

3759 lbs

Rated Operating Capacity with Forks (Articulated)

3172 lbs

Tipping Capacity with Bucket (Straight)

6266 lbs

Tipping Capacity with Bucket (Articulated)

5236 lbs

Tipping Capacity with Forks (Straight)

4699 lbs

Tipping Capacity with Forks (Articulated)

3965 lbs

Tipping Load - Straight

6266 lbs

Bucket Capacities

0.86- 1.3 yd³

Operating Weight

9944 lbs

Travel Speed - Low

4.9 mph

Travel Speed - High

45.4 mm

▼ **Capacities**

L65

Fuel Tank

20.8 gal

▼ **Hydraulic System**

L65

Auxiliary Std Flow

19.9 gpm

▼ **Dimensions**

L65

Inside Turning Radius w/bkt

78.7 in

Height to Hinge Pin - Fully Raised

127 in

Outside Turning Radius w/forks

180.8 in

Outside Turning Radius

169.2 in

Oscillation Angle

8 deg

Articulation Angle

40 deg

Length with Standard Bucket

218 in

Length without Attachment

193.9 in

Width (with bucket)

74.8 in

Width (over tires)

69.7 in

Height with Operator Cab

97.4 in

Dump Angle @ Maximum Height

45 deg

Ground Clearance

11.3 in

Rollback Angle

55 deg

Wheelbase

82.7 in

Tire Size

365/70 R18

Wheel Tread

55.5 in

▼ **Drive System**

L65

Drive Type

Two-speed hydrostatic with Advanced Attachment Control

▼ **Features**

L65

Seat switch (OICS)

Standard

Rear View Camera

Optional

OICS System (Interlock)

Standard

Z-Bar Linkage

Standard

Engine Derate

Standard

Advanced Attachment Control

Standard

4 way Flasher

Standard

Road Lights

Standard

Travel Foot Pedal

Standard

Tilt and Telescoping Steering Wheel

Standard

Keyless Ignition

Standard

Front and Rear Work Lights

Standard

Joystick Control

Standard

Hydrostatic Transmission

Standard

High Flow

Not Applicable

Enclosed Operator Cab with HVAC

Optional

Mechanical Suspension Seat

Standard

Air Ride Suspension Seat

Not Applicable

Keyed Ignition

Optional

Operator Canopy

Optional

Backup Alarm

Standard

Turbocharged Engine

Standard

Rotating Flashing Beacon

Optional

Lift-Arm Support

Standard

Grab Handles

N/A

Seat Belt

Standard

Side Mirrors Right and Left

Standard

Suspension Seat

Standard

Turn Signals

Standard

Wheel Fenders

Standard

Two Speed Travel

Standard

Auxiliary Hydraulics

Standard

Spark Arrestor Muffler

Standard

Lift Arm Lockout With Manual Bypass

Standard

Tilt Lockout

Standard

Built-In Tie Down & Crane/Lift Locations

Standard

Hour Meter

Standard

Speedometer

Standard

Cup Holder

Standard

Glow Plug Engine Pre-heat

Standard

Horn

Standard