

# L95 Specs & Compare

▲ **L95 Key Specifications**

**L95**

Horsepower

**74 hp**

Engine Model

**DM02-LEL11**

Rated Operating Capacity with Bucket (Straight)

**3981 lbs**

Rated Operating Capacity with Bucket (Articulated)

**3335 lbs**

Rated Operating Capacity with Forks (Straight)

**4860 lbs**

Rated Operating Capacity with Forks (Articulated)

**4127 lbs**

Operating Weight

**11993 lbs**

Travel Speed - Low

**5.3 mph**

Travel Speed - High

**24.3 mph**

Hydraulic Pump Pressure

**3 psi**

Auxiliary Std Flow

**19.9 gpm**

Auxiliary High Flow

**27.3 gpm**

Inside Turning Radius w/bkt

**78.2 in**

Height to Hinge Pin - Fully Raised

**128.9 in**

Length with Standard Bucket

**219.3 in**

Width (with bucket)

**74.8 in**

Width (over tires)

**70.9 in**

Height with Operator Cab

**99.3 in**

Wheelbase

**82.7 in**

▼ **Engine**

**L95**

Horsepower

**74 hp**

Engine Model

**DM02-LEL11**

▼ **Performance**

**L95**

Rated Operating Capacity with Bucket (Straight)

**3981 lbs**

Rated Operating Capacity with Bucket (Articulated)

**3335 lbs**

Rated Operating Capacity with Forks (Straight)

**4860 lbs**

Rated Operating Capacity with Forks (Articulated)

**4127 lbs**

Tipping Capacity with Bucket (Straight)

**7962 lbs**

Tipping Capacity with Bucket (Articulated)

**6670 lbs**

Tipping Capacity with Forks (Straight)

**6076 lbs**

Tipping Capacity with Forks (Articulated)

**5159 lbs**

Bucket Capacities

**1.25 - 2.0 yd<sup>3</sup>**

Operating Weight

**11993 lbs**

Travel Speed - Low

**5.3 mph**

Travel Speed - High

**24.3 mph**

▼ **Capacities**

**L95**

Fuel Tank

**20.8 gal**

▼ **Hydraulic System**

**L95**

Hydraulic Pump Pressure

**3 psi**

Auxiliary Std Flow

**19.9 gpm**

Auxiliary High Flow

**27.3 gpm**

▼ **Dimensions**

**L95**

Inside Turning Radius w/bkt

**78.2 in**

Height to Hinge Pin - Fully Raised

**128.9 in**

Outside Turning Radius w/forks

**180.8 in**

Outside Turning Radius

**150.7 in**

Oscillation Angle

**8 deg**

Articulation Angle

**40 deg**

Length with Standard Bucket

**219.3 in**

Length without Attachment

**192.4 in**

Width (with bucket)

**74.8 in**

Width (over tires)

**70.9 in**

Height with Operator Cab

**99.3 in**

Dump Angle @ Maximum Height

**45 deg**

Ground Clearance

**13.3 in**

Rollback Angle

**49 deg**

Wheelbase

**82.7 in**

Tire Size

**405/70/R20**

Wheel Tread

**54.8 in**

▼ **Drive System**

**L95**

Drive Type

**Four-Speed hydrostatic with Advanced Attachment Control**

▼ **Features**

**L95**

Rear View Camera

**Optional**

OICS System (Interlock)

**Standard**

Z-Bar Linkage

**Standard**

Engine Derate

**Standard**

Advanced Attachment Control

**Standard**

4 way Flasher

**Standard**

Road Lights

**Standard**

Travel Foot Pedal

**Standard**

Tilt and Telescoping Steering Wheel

**Standard**

Keyless Ignition

**Standard**

Front and Rear Work Lights

**Standard**

Joystick Control

**Standard**

Hydrostatic Transmission

**Standard**

High Flow

**Standard**

Enclosed Operator Cab with HVAC

**Optional**

Mechanical Suspension Seat

**Standard**

Air Ride Suspension Seat

**Optional**

Keyed Ignition

**Optional**

Operator Canopy

**Optional**

Backup Alarm

**Standard**

Radio

**Optional**

Turbocharged Engine

**Standard**

Rotating Flashing Beacon

**Optional**

Lift-Arm Support

**Standard**

Grab Handles

**N/A**

Seat Belt

**Standard**

Side Mirrors Right and Left

**Standard**

Suspension Seat

**Standard**

Turn Signals

**Standard**

Wheel Fenders

**Standard**

Two Speed Travel

**Standard**

Auxiliary Hydraulics

**Standard**

Spark Arrestor Muffler

**Standard**

Lift Arm Lockout With Manual Bypass

**Standard**

Built-In Tie Down & Crane/Lift Locations

**Standard**

Power Bob-Tach

**Standard**

Ride Control

**Standard**

Hour Meter

**Standard**

Speedometer

**Standard**

Cup Holder

**Standard**

Glow Plug Engine Pre-heat

**Standard**

Horn

**Standard**