

S66-2 SPECS & COMPARE

▲ S66-2 Key Specifications

S66-2

Horsepower

74 hp

Rated Operating Capacity

2400 lbs

Tipping Load

4800 lbs

Operating Weight

7046 lbs

Travel Speed - Low (2-Speed)

7.4 mph

Travel Speed - High (2-Speed)

11 mph

Auxiliary Std Flow

17.6 gpm

Auxiliary High Flow

26.9 gpm

Aux System Pressure

3500 psi

Length without Attachment

107 in

Overall Width

67 in

Overall Height

80.5 in

Height to Hinge Pin

120 in

Reach @ Maximum Height

34.2 in

▼ **Engine**

S66-2

Horsepower Management

Included with SJC Option

Horsepower

74 hp

▼ **Performance**

S66-2

Rated Operating Capacity 200 lb. Counterweight

2550 lbs

Rated Operating Capacity

2400 lbs

Tipping Load

4800 lbs

Operating Weight

7046 lbs

Travel Speed (2-speed option)

11 mph

Travel Speed - Low (2-Speed)

7.4 mph

Travel Speed - High (2-Speed)

11 mph

▼ **Capacities**

S66-2

Fuel Tank

28.3 gal

▼ **Hydraulic System**

S66-2

System Relief @ Quick Couplers

3500 psi

Auxiliary Std Flow

17.6 gpm

Auxiliary High Flow

26.9 gpm

Aux System Pressure

3500 psi

▼ **Dimensions**

S66-2

Length with Standard Bucket

134.9 in

Length without Attachment

107 in

Width (with bucket)

68 in

Overall Width

67 in

Overall Height

80.5 in

Height to Hinge Pin

120 in

Reach @ Maximum Height

34.2 in

Turning Radius

80.1 in

Wheelbase

44.6 in

Standard Bucket

68 in

Standard Tires

787 X 305 X 419 [31 X 12 X 16.5]

▼ **Instrumentation**

S66-2

Fuel Gauge

Yes

Hourmeter

Yes

Engine Coolant Temperature

Yes

Engine Air Filter

Replaceable dry paper cartridge with separate safety element

Engine Oil Pressure

Yes

▼ **Features**

S66-2

Joystick Control

Optional

Speed Management

Included with SJC Option

Standard Display (includes keyless start)

Standard

Dual-Direction Bucket Positioning

Optional

Heated Cloth Air-Ride Seat

Optional

LED Front and Rear Lights

Standard

Radio Remote Control (SJC Required)

Optional

Reversing Fan

Optional

Air Conditioning

Optional

Adjustable Seat

Standard

Backup Alarm

Standard

BICS System (Interlock)

Standard

Cab Enclosure

Optional

Sound Option

Optional

Cab Heater

Optional

Operating Lights

Standard

Parking Brake

Wedge Brake System

Radio

Optional

Turbocharged Engine

Standard

Rear Window

Standard

Top Window

Standard

Lift-Arm Support

Standard

Seat Belt

Standard

Suspension Seat

Standard

Two Speed Travel

Standard

Deluxe Instrumentation

Not Applicable

Engine Shutdown

Standard

Hydraulic Bucket Positioning

Not Applicable

High Flow Option

Optional

Auxiliary Hydraulics

Standard

Spark Arrestor Muffler

DOC

Bob-Tach Attachment System

Standard

Power Bob-Tach

Optional

ACS (Switchable Controls)

Not Applicable

Ride Control

Optional

Rear Hydraulics

Optional

Horn

Standard