

S76-2 SPECS & COMPARE

▲ S76-2 Key Specifications

S76-2

Horsepower

74 hp

Rated Operating Capacity

2900 lbs

Tipping Load

5800 lbs

Operating Weight

8014 lbs

Travel Speed - Low (2-Speed)

6.8 mph

Travel Speed - High (2-Speed)

11.8 mph

Auxiliary Std Flow

23.3 gpm

Auxiliary High Flow

30.3 gpm

Aux System Pressure

3500 psi

Length without Attachment

114 in

Overall Width

72 in

Overall Height

81.9 in

Height to Hinge Pin

128.3 in

Reach @ Maximum Height

33.5 in

▼ **Engine**

S76-2

Horsepower Management

Included with SJC Option

Horsepower

74 hp

▼ **Performance**

S76-2

Rated Operating Capacity 300 lb. Counterweight

3100 lbs

Rated Operating Capacity 200 lb. Counterweight

3050 lbs

Rated Operating Capacity

2900 lbs

Tipping Load

5800 lbs

Operating Weight

8014 lbs

Travel Speed (2-speed option)

11.8 mph

Travel Speed - Low (2-Speed)

6.8 mph

Travel Speed - High (2-Speed)

11.8 mph

▼ **Capacities**

S76-2

Fuel Tank

31.7 gal

▼ **Hydraulic System**

S76-2

System Relief @ Quick Couplers

3500 psi

Auxiliary Std Flow

23.3 gpm

Auxiliary High Flow

30.3 gpm

Aux System Pressure

3500 psi

▼ **Dimensions**

S76-2

Length with Standard Bucket

142 in

Length without Attachment

114 in

Width (with bucket)

74 in

Overall Width

72 in

Overall Height

81.9 in

Height to Hinge Pin

128.3 in

Reach @ Maximum Height

33.5 in

Turning Radius

83.7 in

Wheelbase

48.3 in

Standard Bucket

74 in

Standard Tires

305 X 419 [12.00 X 16.5]

▼ **Instrumentation**

S76-2

Fuel Gauge

Yes

Hourmeter

Yes

Engine Coolant Temperature

Yes

Engine Air Filter

Replaceable dry paper cartridge with separate safety element

Engine Oil Pressure

Yes

▼ **Features**

S76-2

Joystick Control

Optional

Speed Management

Included with SJC Option

Standard Display (includes keyless start)

Standard

Dual-Direction Bucket Positioning

Standard

Heated Cloth Air-Ride Seat

Standard

LED Front and Rear Lights

Standard

Radio Remote Control (SJC Required)

Optional

Reversing Fan

Optional

Air Conditioning

Standard

Adjustable Seat

Standard

Backup Alarm

Standard

BICS System (Interlock)

Standard

Cab Enclosure

Standard

Sound Option

Standard

Cab Heater

Standard

Operating Lights

Standard

Parking Brake

Wedge Brake System

Radio

Standard

Turbocharged Engine

Standard

Rear Window

Standard

Top Window

Standard

Lift-Arm Support

Standard

Seat Belt

Standard

Suspension Seat

Not Applicable

Two Speed Travel

Standard

Deluxe Instrumentation

Not Applicable

Engine Shutdown

Standard

Hydraulic Bucket Positioning

Not Applicable

High Flow Option

Optional

Auxiliary Hydraulics

Standard

Spark Arrestor Muffler

DOC

Bob-Tach Attachment System

Standard

Power Bob-Tach

Optional

ACS (Switchable Controls)

Not Applicable

Ride Control

Standard

Rear Hydraulics

Optional

Horn

Standard