

WB700 Specs & Compare

▲ **WB700 Key Specifications**

WB0736ST

WB0748SU

WB0752SV

Mower Deck

TufDeck 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts

TufDeck 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts

TufDeck 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts

Cutting Height Range

1.5-4.5 in. (38-114 mm)

1.5-4.5 in. (38-114 mm)

1.5-4.5 in. (38-114 mm)

Width

36 in

48 in

52 in

Engine Model

Kaw FS481

Kaw FS541

Kaw FS600

Transmission Type

Hydro-Gear ZT-2800 transaxles

Hydro-Gear ZT-2800 transaxles

Hydro-Gear ZT-2800 transaxles

Pump Displacement

1 cubic in

1 cubic in

1 cubic in

▼ **Deck**

WB0736ST

WB0748SU

WB0752SV

Mower Deck

TufDeck 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts

TufDeck 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts

TufDeck 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts

Cutting Height Range

1.5-4.5 in. (38-114 mm)

1.5-4.5 in. (38-114 mm)

1.5-4.5 in. (38-114 mm)

Mower Blade Tip Speed

18645 ft/min	16832 ft/min	18645 ft/min
Width		
36 in	48 in	52 in
▼ Engine		
WB0736ST	WB0748SU	WB0752SV
Engine Model		
Kaw FS481	Kaw FS541	Kaw FS600
Horsepower		
14.5 hp	15 hp	18.5 hp
Fuel Tank		
5 gal	18.9 qt	5 gal
▼ Performance		
WB0736ST	WB0748SU	WB0752SV
Machine Weight		
773 lbs	789 lbs	832 lbs
▼ Transmission		
WB0736ST	WB0748SU	WB0752SV
Transmission Type		
Hydro-Gear ZT-2800 transaxles	Hydro-Gear ZT-2800 transaxles	Hydro-Gear ZT-2800 transaxles
Pump Displacement		
1 cubic in	1 cubic in	1 cubic in
Travel Speed		
6.5 mph	6.5 mph	6.5 mph
Travel Speed - Reverse		

3 mph

3 mph

3 mph

▼ **Wheels**

WB0736ST

WB0748SU

WB0752SV

Drive Wheel Size

20" Zero-T Tread pattern

20" Zero-T Tread pattern

20" Zero-T Tread pattern

Front Caster Wheel Size

11 x 6

11 x 6

11 x 6

▼ **Frame**

WB0736ST

WB0748SU

WB0752SV

Length

76 in

76 in

79 in