



INDUSTRIAL SERIES

STRONG AND DEPENDABLE

The Industrial series trailers are engineered using the optimal steel frame to maximize strength, durability, and payload capacity. Each trailer features tandem axles, starting at 10,000 lb. and ranging up to 20,000 lb. per axle.



SPECIFICATIONS

Features	TD210PHBT 26'	TD210GNBT 26'	TD212GNBT 28'	TD215GNBT – 28'	TD220PHBT 26'	TD320AT-30'
GVWR	23000 Lbs	25000 Lbs	30000 Lbs	37500 Lbs	46000 Lbs	69000 Lbs
GAWR (Per Axle)	10000 Lbs	10000 Lbs	12000 Lbs	15000 Lbs	20000 Lbs	20000 Lbs
Tare Weight (approx.)	5534 lb	5930 lb	6430 lb	8360 lb	9127 lb	13500 Lbs
Main Frame	W12 @ 14# I- Beam A992/A572-50	W12 @ 14# I- Beam A992/A572-50	W10 @ 22# I- Beam A992/A572-50	W10 @ 22# I- Beam A992/A572-50	W12 @ 26# I- Beam A992/A572-50	W12 @ 45# I- Beam A992/A572-50
Crossmembers	3 x 2 . 125 on 19.2" Centers	4" I-Beam on 19.2" Centers	4" I-Beam on 19.2" Centers			
Axles	(2) 10,000 lb Dual Electric Braking	(2) 10,000 lb Dual Electric Braking	(2) 12,000 lb Dual Electric Braking	(2) 15,000 lb Dual Electric Braking	(2) 20,000 lb Dual Air Braking (w/ABS)	(3) 20,000 lb Dual Air Braking (w/ABS)
Suspension	Slipper Spring 5 Leaf	Slipper Spring 5 Leaf	Slipper Spring 6 Leaf	Slipper Spring 7 Leaf	Hutch Suspension HD 3 Leaf	Hutch Suspension HD 3 Leaf
Hitch	Adjustable Lunette Eye	Gooseneck 2 5/16" Ball Coupler	Gooseneck 2 5/16" Ball Coupler	Gooseneck 2 5/16" Ball Coupler	Adjustable Lunette Eye	Adjustable Lunette Eye
Jack	Single 12000#	Double 12000#	Double 12000#	Double 12000#	Single Two Speed #25000	Double 12000#
Deck	#1 Kiln Dried Canadian Spruce	#1 Kiln Dried Canadian Spruce	Full Dimensional Rough Cut Spruce	Full Dimensional Rough Cut Spruce	Full Dimensional Rough Cut Spruce	Full Dimensional Rough Cut Spruce
Deck Height	37"	37"	37"	38"	41"	41"

Features	TD210PHBT 26'	TD210GNBT 26'	TD212GNBT 28'	TD215GNBT – 28'	TD220PHBT 26'	TD320AT-30'
Beavertail c/w Double Pivot Ramps	Standard	Standard	Standard	Standard	Standard	Hinged
	Double Pivot	Double Pivot	Double Pivot	Double Pivot	Double Pivot	Beavertail
	Spring Assisted	Spring Assisted	Spring Assisted	Spring Assisted	Spring Assist	
	TECH Ramp	TECH Ramp	TECH Ramp	TECH Ramp		
Tires	ST235/80R16	ST235/80R16	ST235/80R16	215/75R17.5	255/70R22.5	255/70R22.5
	Radial Load	Radial Load	Radial Load	Load Range H	Radial Load	Radial Load
	Range E	Range E	Range E		Range H	Range H
Lights & Wiring	LED c/w Fully	LED c/w Fully	LED c/w Fully	LED c/w Fully	LED c/w Fully	LED c/w Fully
	Protected Arctic	Protected Arctic	Protected Arctic	Protected Arctic	Protected	Protected
	Wiring	Wiring	Wiring	Wiring	Arctic Wiring	Arctic Wiring
Options		Gooseneck King Pin	Gooseneck King Pin	Gooseneck King Pin	---	

All models have the following standard features: Rub rail w/stake pockets, 102" Overall width.

Legend for Model Abbreviations

GN - Gooseneck

PH - Pintle Hitch

FEATURES

Beavertail & Double Pivot Ramps

The 5' beavertail creates an ideal loading incline combined with the ease of spring assisted ramps.

Steps & Grab Handles

Gooseneck step and grab handles make it easier and safer to get up on to the trailer deck.

Open Cleated Beavertail

The open cleated beavertail eliminates the slippage common on wooden beavertails.

Spring Assisted Double Pivot TECH Ramps

It is now easier than ever to extend the length of your deck with the spring assisted TECH ramps.

Dual Drop Foot Jacks

Dual HD drop foot jacks and expanded metal basket are standard on all goosenecks, for increased stability, lift and storage capacity.

LED Lighting

LED lighting, which allows for faster response time and brighter lights for safety, is standard on all models.

