



FX - 320 ROTARY CUTTER

- 1** A single domed 7ga continuously welded deck makes the cutter extremely easy to clean, prevents water pooling, rusting and helps shed debris
- 2** The drive system features Cat 5 CV (1000 RPM), Cat 6 CV (540 RPM) and Cat 6 wing drivelines which employ self-adjusting friction clutches.
- 3** Equipped with Schulte Super Suction Blades with 6" blade overlap for maximum grass lift and cut
- 4** A four gearbox drive line with independent slip clutches
- 5** Deck protection rings are standard and protect the cutter deck from rising blades
- 6** Large, 15" deck depth, high blade tip speeds and long gearbox shaft provide a faster cut speed
- 7** High flex wing working range of 20° down to 90° up
- 8** Replaceable side skirts



World Class *Built to Last*

schulte.ca

Specifications


SPECIFICATIONS

Cutting Width	240" (6.1 m)
Overall Width	249" (6.32 m)
Overall Length	242" (6.15 m)
Cutting Height	2"- 19.5" (51 - 450 mm)
Transport Width	106" (2.40 m)
Transport Height	120" (3.05m)
Weight (Depends on Config.)	9300 lbs (4218 kg)
Hitch Weight	3200 lbs (1452 kg)
Cutting Capacity	Fixed Knife 2" (51mm) Pan Unit 4" (102mm)
Minimum Tractor Size	100 HP (75 kW)
Blade Tip Speed	540 RPM 1000 RPM
Blade Overlap	16031 ft/min (4886m/m) 16289 ft/min (4965m/m)
Divider Gearbox Rating	260 hp (194kw)
Center & Wing Gearbox Rating	225 hp (168kw)*
Wing Drive Shafts	Cat 6
Deck Thickness	.180" (7 ga) (4.6mm)
Side Skirt Thickness	1/4" (6.4mm)
Side Skirt Depth	15" (381mm)
Wing Working Range	20° down to 90° up
Wing Floating Range	20° down to 40° up
Drive Size centre and wings	G8 / G9
Drive Size Main	Cat.5CV (1000rpm), Cat.6CV (540 rpm)
Suspension	Five rubber suspension pucks on center and single on wings

FX-320



Available with walking axles as shown or straight through axles



Pro Level Hitch Fits Cat 2 and Cat 3 is one of five optional Hitches



Optional laminated tires



225 hp (168kw)* center and wing gearbox with sight glass



Deck protection rings are standard



Heavy duty cast hinge line with wiper seals



Removable/replaceable side skirts



Heavy duty spun pan unit with 4" blades and pentagon blade bolts



Narrow 106" transport width and over-centering wing design

FX-320 Features and Options

- Optional solid laminated tires 26" or severe duty foam filled tires
- Safety light kit standard
- Pro Level, solid tongue open clevis, Equal Angle Hitch (540 RPM Only) or precision hitch
- 540/1000 RPM drive packages
- Single chains (optional double chains) front and rear
- Front or rear half belting
- Pan unit with updraft blades or shredder blade kit with optional shrouding
- Four tire kit for row crop cutting; six or eight tire kit with duals or walking axles
- Adjustable wheel standards

SCHULTE

Schulte Industries Ltd.

PO Box 70, Englefeld, SK Canada S0K 1N0

Ph (306) 287-3715 Fx (306) 287-3355

Email info@schulte.ca Web www.schulte.ca

*Intermittent use only

Schulte is a registered trademark of Alamo Group Inc.

Schulte Industries Ltd. reserves the right to change the design and specifications of it's products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.



Sold By:

Printed in Canada

20106/15

