ER620H

COMPACT HYDRAULIC EXCAVATOR

**BUILT FOR PERFORMANCE.
DESIGNED FOR RESULTS.**



SDLG ER620H Excavator (Base Machine)	**$39,499.00**
Freight / Transportation	**$549.99**
Pre-Delivery Inspection (PDI) & Setup	**$299.99**
Documentation / Admin Fee	**$137.99**
TOTAL FEES	**$987.97**
TOTAL SELLING PRICE (Before Taxes)	**$40,486.97**
HST (15% - New Brunswick)	**$6,073.05**
TOTAL PRICE (Taxes Included)	**$46,560.02**

Registration and delivery to customer (if required) extra.

SPECIFICATIONS - MANUAL FIRST, OFFICIAL SDLG FOR GAPS

Operating weight	**1,925 kg (4,244 lb)**
Engine model	**Kubota D902-EF08-CN4**
Rated power / speed	**11.8 kW (15.8 hp) @ 2,300 rpm**
Engine displacement*	**898 mL (54.8 cu in)**
Pump capacity*	**52 L/min (11.4 US gal/min)**
Main relief set pressure*	**240 bar (3,480 psi)**
Max. bucket digging force*	**16.5 kN (3,709 lbf)**
Max. arm digging force*	**10 kN (2,248 lbf)**
Travel speed - low / high	**2.1 / 3.3 km/h (1.3 / 2.1 mph)**
Maximum gradeability	**30°**
Maximum slewing speed	**9.2 rpm**
Standard bucket capacity	**0.04 m³ (0.05 yd³)**
Bucket capacity range	**0.03-0.06 m³**
Blade (W x H)*	**1,240 x 275 mm (48.8 x 10.8 in)**
Ground pressure*	**31 kPa (4.5 psi)**
Fuel tank*	**18 L (4.8 US gal)**

WORKING RANGE - JULY 2025 ER620H MANUAL

Maximum digging radius	**3,940 mm (12.9 ft)**
Maximum digging range at ground	**3,880 mm (12.7 ft)**
Maximum digging height	**3,470 mm (11.4 ft)**
Maximum dumping height	**2,425 mm (8.0 ft)**
Maximum digging depth	**2,330 mm (7.7 ft)**
Maximum vertical digging depth	**1,745 mm (5.7 ft)**
Minimum front slewing radius	**1,620 mm (5.3 ft)**

DIMENSIONS - JULY 2025 ER620H MANUAL

Overall length	**3,620 mm (11.9 ft)**
Overall width - retracted / expanded	**990 / 1,240 mm (3.2 / 4.1 ft)**
Overall height	**2,426 mm (8.0 ft)**
Track shoe width	**230 mm (9.1 in)**
Track width - retracted / expanded	**730 / 1,010 mm (2.4 / 3.3 ft)**
Track wheelbase	**1,230 mm (4.0 ft)**
Track length	**1,585 mm (5.2 ft)**
Minimum ground clearance	**145 mm (5.7 in)**
Upper-structure ground clearance	**430 mm (1.4 ft)**
Tail turning radius	**650 mm (2.1 ft)**

FEATURES

- Kubota engine
- Narrow unit with minimal tail swing for confined spaces
- X1/X3 auxiliary pipelines*
- Auxiliary pipelines with 5 quick connectors*
- Full-color, high-resolution 7-inch display*
- ROPS&TOP; guard certified canopy, double rearview mirrors and three LED work lights*
- Centrally located filters for easier maintenance*
- Quick-change mechanism is optional in the July 2025 manual

WARRANTY NOTE

A 5-year / 5,000-hour warranty is advertised by some North American ER620H dealers. Confirm the warranty terms and eligibility for the specific Yard Gear machine/serial number before sale.

Verification basis: July 2025 ER620H Operation & Maintenance Manual controls wherever it provides a value. Items marked * are filled from SDLG's official ER620H online specification/feature information. Where online specifications conflict with the July 2025 manual (including operating weight, exact engine model and travel speeds), the manual value is used.

YARD GEAR

1318 Hanwell Road, Fredericton, NB E3C 1A5
506-742-7772 | www.yardgear.ca

EQUIPMENT PEOPLE CAN COUNT ON.