

L95 Specs & Compare

← L95 Key Specifications

L95

Horsepower

74 hp

Rated Operating Capacity with Bucket (Articulated)

3335 lbs

Rated Operating Capacity with Forks (Straight)

4860 lbs

Rated Operating Capacity with Forks (Articulated)

4127 lbs

Rated Operating Capacity with Bucket (Straight)

3981 lbs

Operating Weight

11993 lbs

Travel Speed - High

24.3 mph

Travel Speed - Low

5.3 mph

Auxiliary Std Flow

19.9 gpm

Auxiliary High Flow

27.3 gpm

Width (over tires)

70.9 in

▲ Engine

L95

Horsepower

74 hp

Turbocharged Engine

yes

▲ Performance

L95

Tipping Capacity with Bucket (Straight)

7962 lbs

Rated Operating Capacity with Bucket (Articulated)

3335 lbs

Rated Operating Capacity with Forks (Straight)

4860 lbs

Rated Operating Capacity with Forks (Articulated)

4127 lbs

Rated Operating Capacity with Bucket (Straight)

3981 lbs

Tipping Capacity with Bucket (Articulated)

6670 lbs

Tipping Capacity with Forks (Straight)

6076 lbs

Tipping Capacity with Forks (Articulated)

5159 lbs

Bucket Capacities

1.25 - 2.0 yd³

Operating Weight

11993 lbs

Travel Speed - High

24.3 mph

Travel Speed - Low

5.3 mph

▲ Capacities

L95

Fuel Tank

20.8 gal

▲ Hydraulic System

L95

Auxiliary Std Flow

19.9 gpm

Auxiliary High Flow

27.3 gpm

▲ **Dimensions**

L95

Inside Turning Radius w/bkt

78.2 in

Outside Turning Radius w/forks

180.8 in

Height to Hinge Pin - Fully Raised

128.9 in

Articulation Angle

40 deg

Oscillation Angle

8 deg

Outside Turning Radius

150.7 in

Length without Attachment

192.4 in

Length with Standard Bucket

219.3 in

Width (with bucket)

74.8 in

Width (over tires)

70.9 in

Height with Operator Cab

99.3 in

Dump Angle @ Maximum Height

45 deg

Ground Clearance

13.3 in

Rollback Angle

49 deg

Wheelbase

82.7 in

Tire Size

405/70/R20

Wheel Tread

54.8 in

▲ Drive System

L95

Drive Type

Four-Speed hydrostatic with Advanced Attachment Control

▼ Features

L95

Enclosed Operator Cab with HVAC

Optional

Mechanical Suspension Seat

Standard

Air Ride Suspension Seat

Optional

Keyed Ignition

Optional

Keyless Ignition

Standard

Tilt and Telescoping Steering Wheel

Standard

Travel Foot Pedal

Standard

Road Lights

Standard

4 way Flasher

Standard

Front and Rear Work Lights

Standard

Engine Derate

Standard

Z-Bar Linkage

Standard

OICS System (Interlock)

Standard

Rear View Camera

Optional

High Flow

Standard

Hydrostatic Transmission

Standard

Advanced Attachment Control

Standard

Joystick Control

Standard

Operator Canopy

Optional

Backup Alarm

Standard

Radio

Optional

Rotating Flashing Beacon

Optional

Lift-Arm Support

Standard

Grab Handles

N/A

Seat Belt

Standard

Side Mirrors Right and Left

Standard

Suspension Seat

Standard

Turn Signals

Standard

Wheel Fenders

Standard

Two Speed Travel

Standard

Auxiliary Hydraulics

Standard

Spark Arrestor Muffler

Standard

Lift Arm Lockout With Manual Bypass

Standard

Built-In Tie Down & Crane/Lift Locations

Standard

Power Bob-Tach

Standard

Ride Control

Standard

Hour Meter

Standard

Speedometer

Standard

Cup Holder

Standard

Glow Plug Engine Pre-heat

Standard

Horn

Standard