



2016



POLARIS® OFF-ROAD VEHICLES



# RZR®

## RAZOR SHARP PERFORMANCE



### RZR SHARP PERFORMANCE

RZR® is the first and only sport side-by-side to give you the ultimate combination of Power, Suspension, Agility, Comfort & Customization. Every RZR® is engineered to perform with proven ProStar® engines. Offering up to 144 HP, industry leading suspension travel, true On-Demand All-Wheel Drive and superior comfort & ergonomics.

### BUILT FOR YOU

Whether you prefer the TRAIL, the DUNES, the DESERT or the MUD, RZR® offers a vehicle fit to the way you ride. Do you need seating for just two or the whole family? RZR® has seating options for 2 or 4 people so no one ever gets left behind.

### ULTIMATE CUSTOMIZATION

There's an easy way to put more of your style and personality into your machine. RZR® offers a wide variety of accessories in the style, color and configurations as varied as the terrain you travel.

# POWER, SUSPENSION, AGILITY, COMFORT AND CUSTOMIZATION

## TRAIL



RZR 570 EPS TRAIL  
BLACK PEARL  
45HP WIDTH 50" (127 cm)



RZR 900 EPS TRAIL  
HAVASU RED PEARL  
75HP WIDTH 50" (127 cm)



RZR 900 EPS XC EDITION  
STEALTH BLACK  
75HP WIDTH 55" (140 cm)

FOR COMPLETE LIST  
OF COLORS & MODEL  
SPECS, SEE PAGE 10

## HIGH PERFORMANCE



RZR S 900 EPS  
BLUE FIRE  
75HP WIDTH 60" (152 cm)

NEW!



RZR S 1000 EPS  
MATTE WHITE LIGHTNING  
100HP WIDTH 60" (152 cm)



RZR XP 1000 EPS  
TITANIUM MATTE METALLIC  
110HP WIDTH 64" (163 cm)

NEW!



RZR XP TURBO EPS  
GRAPHITE CRYSTAL  
144HP WIDTH 64" (163 cm)

## 4-SEAT



RZR 4 900 EPS  
HAVASU RED PEARL  
75HP WIDTH 60" (152 cm)



RZR XP 4 1000 EPS  
ELECTRIC BLUE METALLIC  
110HP WIDTH 64" (163 cm)

## SPECIAL EDITIONS



RZR XP 1000 EPS HIGH LIFTER EDITION  
TITANIUM MATTE METALLIC  
110HP WIDTH 64" (163 cm)

NEW!



RZR 900 EPS TRAIL FOX EDITION  
MATTE WHITE LIGHTNING  
75HP WIDTH 50" (127 cm)



# POLARIS® SPORTSMAN®

# HARDEST WORKING, SMOOTHEST RIDING.

## HARDEST WORKING.

Sportsman® brings you the hardest working lineup of ATVs by giving you the ProStar® Engines with options ranging from 31 HP – 89 HP. On-Demand True All-Wheel Drive (AWD) means you have four-wheel traction when it is needed, two wheel drive when you don't. Whether it is at home, on the farm or at the job site, Sportsman's class leading towing and payload ratings make sure you have what it takes to get more work done.



## SMOOTHEST RIDING.

High ground clearance and independent rear suspension adds up to the smoothest, most refined ride no matter what the trail throws at you. Sportsman® has the most responsive power steering available, with 30% more power assist than the leading competitor, plus Variable Assist for easier steering at lower speeds. Our EPS lets you ride all day with less fatigue from steering.

# FIND THE RIGHT ATV FOR YOU! HARDEST WORKING. SMOOTHEST RIDING.®

## RECREATION / UTILITY

**NEW!**



SPORTSMAN 450 H.O.  
VELOCITY BLUE  
31HP



SPORTSMAN 570  
INDY RED  
44HP



SPORTSMAN 570 EPS  
POLARIS PURSUIT® CAMO  
44HP



SPORTSMAN 570 SP  
TITANIUM MATTE METALLIC  
44HP

FOR COMPLETE LIST  
OF COLORS & MODEL  
SPECS, SEE PAGE 12.

## BIG BORE



SPORTSMAN 850  
WHITE LIGHTNING  
78HP



SPORTSMAN 850 SP  
SUNSET RED  
78HP



SPORTSMAN XP 1000  
MATTE SAGEBRUSH GREEN  
88HP



SCRAMBLER 850  
WHITE LIGHTNING  
78HP



SCRAMBLER XP 1000  
TITANIUM MATTE RED  
89HP

## 2-UP/TOURING



SPORTSMAN X2 570 EPS  
SAGE GREEN  
44HP



SPORTSMAN TOURING 570 EPS  
BRIGHT WHITE  
44HP



SPORTSMAN TOURING 570 SP  
BLUE FIRE  
44HP



SPORTSMAN TOURING 850 SP  
SUNSET RED  
78HP



SPORTSMAN TOURING XP 1000  
BLACK PEARL  
88HP

**NEW!**

SPORTSMAN XP 1000  
HIGH LIFTER EDITION  
STEALTH BLACK  
85HP

## MUD



**NEW!**  
SPORTSMAN 850  
HIGH LIFTER EDITION  
ORANGE MADNESS  
78HP





**POLARIS®  
ACE™**

**A WHOLE NEW OFF-ROAD EXPERIENCE**



## **CAPABLE**

ACE™ is built to go anywhere and do anything with its trail compliant 48" width, Polaris On-Demand True All-Wheel Drive System, high 10.25" ground clearance, massive 360 lb. cargo capacity, 1,500 lb. towing capacity and smooth Independent Rear Suspension.

## **CONFIDENT**

Take on any trail or any task with confidence. The intuitive automotive style controls and rider centric design with ROPS certified cab and frame put the rider in the center of the trail and delivers nimble ATV like handling with the security of a side-by-side.

## **COMFORTABLE**

The easy sit-in and step-out design combined with a bolstered sliding bucket seat, tilt steering and seat belt style 3-point harness make for a smooth comfortable ride. Add on a Lock & Ride® roof, windshield and doors to keep the weather out and it's easy to see how the ACE™ delivers all day comfort on the trail.

# FIND THE RIGHT ACE FOR YOU! CAPABLE, CONFIDENT, COMFORTABLE.

## POLARIS ACE



POLARIS ACE  
SAGE GREEN  
32HP



POLARIS ACE  
INDY RED  
32HP

## POLARIS ACE 570



2015 POLARIS ACE 570  
VELOCITY BLUE  
45HP



2015 POLARIS ACE 570  
WHITE LIGHTNING  
45HP



**NEW! FACTORY  
INSTALLED DOORS**  
POLARIS ACE 570 SP  
POLARIS PURSUIT® CAMO  
45HP

## POLARIS ACE 900 SP



**NEW!**

POLARIS ACE 900 SP  
STEALTH BLACK  
60HP

FOR COMPLETE LIST OF COLORS  
& MODEL SPECS, SEE PAGE 13.



# POLARIS® RANGER® GET MORE DONE!



## INDUSTRY LEADER IN UTILITY SXS

There is a reason RANGER® outsells the largest utility SxS competitor 4-1. Every RANGER® we make is built on decades of industry leading innovation, driven by customer influenced design, and quality, that puts us ahead of the rest.

## THERE IS A RANGER® FOR YOU

No matter your needs, farm - ranch - hunt or on the trail we have a RANGER® to suit your use and lifestyle. Whether you need seating just for you, or your whole crew, RANGER® has seating options for two to six people with no compromises in bed capacity or payload.

## ULTIMATE VERSATILITY

Industry exclusive Lock & Ride® Pro-Fit cab integration and easy to install accessories, means you can quickly change from a utility work horse to your companion on the hunt or trail.

## BUILT TO GET MORE DONE

RANGER® offers powerful and efficient ProStar® engine options with massive towing and payload capability. Add to that great ground clearance and legendary ride and handling you have the confidence you need to get more done off-road.

# FIND THE RIGHT RANGER® FOR YOU! HARDEST WORKING. SMOOTHEST RIDING.®

## TWO-SEAT



RANGER ETX  
WHITE LIGHTNING  
31HP



RANGER 570  
SOLAR RED  
44HP



RANGER EV  
AVALANCHE GRAY  
30HP



NEW!  
RANGER EV LI-ION  
POLARIS PURSUIT® CAMO  
30HP

## THREE-SEAT

NEW!



RANGER 570 FULL-SIZE  
SAGE GREEN  
44HP



NEW!  
RANGER XP 570  
SOLAR RED  
47HP



RANGER XP 900 EPS  
BLACK PEARL  
68HP



NEW!  
RANGER XP 900 EPS HIGH LIFTER EDITION  
STEALTH BLACK  
68HP



RANGER DIESEL  
SAGE GREEN  
24HP

## CREW



RANGER CREW 570-4  
SOLAR RED  
44HP



NEW!  
RANGER CREW 570-6  
SAGE GREEN  
46HP



NEW!  
RANGER CREW 900-5 (6) EPS  
SUNSET RED  
68HP



RANGER CREW DIESEL  
SAGE GREEN  
24HP

FOR COMPLETE LIST OF COLORS  
& MODEL SPECS, SEE PAGE 14.



	RZR® 570 Trail	RZR® 900 EPS Trail	RZR® 900 EPS XC Edition	RZR® S 900 EPS	RZR® S 1000 EPS	RZR XP® 1000 EPS	RZR XP® 1000 EPS High Lifter Edition
ENGINE	Engine Type	4-Stroke DOHC Single Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder
	Displacement	567cc	875cc	875cc	875cc	999cc	999cc
	Fuel System	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
	Cooling	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid
DRIVE TRAIN	Transmission/Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
	Drive System	High-Performance On-Demand True AWD/2WD/VersTrac Turf Mode	High-Performance On-Demand True AWD/2WD/VersTrac Turf Mode	High-Performance On-Demand True AWD/2WD/VersTrac Turf Mode	High-Performance On-Demand True AWD/2WD	High-Performance On-Demand True AWD/2WD	High-Performance On-Demand True AWD/2WD
	Engine Braking System/Active Descent Control	EBS	EBS	EBS	Not Equipped	Not Equipped	Not Equipped
SUSPENSION	Front Suspension	Dual A-Arm with Anti-Sway Bar 9" (22.9 cm) Travel	Dual A-Arm with Anti-Sway Bar 10" (25.4 cm) Travel	Dual A-Arm FOX Performance Series - 2.0 Podium X with Anti-Sway Bar 10" (25.4 cm) Travel	Dual A-Arm FOX Performance Series - 2.0 Podium X 12.25" (31.1 cm) Travel	Dual A-Arm FOX Performance Series - 2.0 Podium X 12.25" (31.1 cm) Travel	Dual A-Arm Walker Evans 2" Needle Shocks (comp adjust/res.) 16" (40.6 cm) Travel
	Rear Suspension	Dual A-Arm, Anti-Sway Bar 9.5" (24 cm) Travel	Dual A-Arm with Anti-Sway Bar 10" (25.4 cm) Travel	Dual A-Arm FOX Performance Series - 2.0 Podium X with Anti-Sway Bar 10" (25.4 cm) Travel	Dual A-Arm FOX Performance Series - 2.0 Podium X with Anti-Sway Bar 13.2" (33.5 cm) Travel	Dual A-Arm FOX Performance Series - 2.0 Podium X with Anti-Sway Bar 13.2" (33.5 cm) Travel	Trailing Arm Walker Evans 2.5" Needle Shocks (comp adjust/remote res.) with Anti-Sway Bar 18" (45.7 cm) Travel
	Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
TIRES AND WHEELS	Parking Brake	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission
	Front Tires	25 x 8-12; Maxxis	26 x 8-12; PXT	27 x 9-14; GBC Dirt Commander	27 x 9-12; GBC Dirt Commander	27 x 9-12; GBC Dirt Commander	29 x 9-14; Maxxis Bighorn
	Rear Tires	25 x 10-12; Maxxis	26 x 9-12; PXT	27 x 11-14; GBC Dirt Commander	27 x 11-12; GBC Dirt Commander	27 x 11-12; GBC Dirt Commander	29 x 11-14; Maxxis Bighorn
DIMENSIONS/CAPACITIES	Wheels	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum
	Wheelbase	77" (196 cm)	79" (200.7 cm)	79" (200.7 cm)	79" (200.7 cm)	90" (228.6 cm)	90" (228.6 cm)
	Dry Weight	Trail: 1,059 lb (480.4 kg); Base: 956 lb (431.8 kg)	1,176 lb (533.4 kg)	1,249 lb (566.5 kg)	1,230 lb (557.9 kg)	1,235 lb (560.2 kg)	1,369 lb (620.9 kg)
	Overall Vehicle Size (L x W x H)	107.5 x 50 x 69" (273 x 127 x 175.2 cm)	105 x 50 x 69.5" (266.7 x 127 x 176.5 cm)	106 x 55 x 70.5" (269.2 x 139.7 x 179.1 cm)	106 x 60 x 71.5" (269.2 x 152.4 x 181.6 cm)	119" x 64" x 73.75" (302.2 x 162.6 x 187.3 cm)	122 x 64 x 75" (309.9 x 162.6 x 190.5 cm)
	Ground Clearance	10.5" (26.7 cm) **	11" (27.9 cm) **	12" (30.5 cm) **	12.5" (31.8 cm)	12.5" (31.8 cm)	13.5" (34.3 cm)
	Fuel Capacity	7.25 gal (27.4 L)	9.5 gal (36 L)	9.5 gal (36 L)	9.5 gal (36 L)	9.5 gal (36 L)	9.5 gal (36 L)
	Bed Box Dimensions (L x W x H)	20 x 40 x 9" (51 x 102 x 23 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)
	Front/Rear Rack or Box Capacity	N.A./300 lb (136.1 kg)	N.A./300 lb (136.1 kg)	N.A./300 lb (136.1 kg)	N.A./300 lb (136.1 kg)	N.A./300 lb (136.1 kg)	N.A./300 lb (136.1 kg)
	Payload Capacity	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)
	Hitch Towing Rating	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	N.A.	N.A.
FEATURES	Hitch/Type	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	None	None
	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
	Lighting	Halogen, 55W Low/ 60W High	Halogen, 55W Low/ 60W High & Red LED Tail / Brake Lights	White LED, Low/High & Red LED Tail / Brake Lights	Halogen, 55W Low/ 60W High & Red LED Tail / Brake Lights	Halogen, 55W Low/ 60W High & Red LED Tail / Brake Lights	White LED, Low/High & Red LED Tail / Brake Lights
	Electronic Power Steering	Equipped	Equipped	Standard	Equipped	Standard	Standard
	Instrumentation	Digital Gauge, Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, DC Outlet	Digital Gauge, Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, DC Outlet	Polaris Interactive Digital Display, Speedometer, Odometer, Dual Tripmeters, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Reminder, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder, Compass, Elevation, Latitude/Longitude, Route Recording & Display, Fault Code Display, Bluetooth Connectivity, USB Port, DC Outlet	Digital Gauge, Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, DC Outlet	Digital Gauge, Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, DC Outlet	Digital Gauge, Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, DC Outlet
Colors	* White Lightning, Black Pearl	* White Lightning, Havasu Red Pearl, Matte Turbo Silver, Polaris Pursuit Camo, Matte White Lightning	Stealth Black	* White Lightning, Havasu Red Pearl, Blue Fire	Matte White Lightning, Black Pearl	Matte White Lightning, Black Pearl	Titanium Matte Metallic, Electric Blue Metallic

\*Features may vary on Base and FOX Edition. \*\*With adjustable suspension. See Owner's Manual for details.



Matte White Lightning



Black Pearl



Havasu Red Pearl



Matte Turbo Silver



Polaris Pursuit Camo



Stealth Black

# YOUTH


				
PHOENIX™ 200	RZR® 170 EFI	OUTLAW® 110 EFI	SPORTSMAN® 110 EFI	OUTLAW® 50
4-Stroke Single Cylinder	4-Stroke Single Cylinder	4-Stroke Single Cylinder	4-Stroke Single Cylinder	4-Stroke Single Cylinder
196cc	169cc	112cc	112cc	49cc
Carbureted	EFI	EFI	EFI	Carbureted
Air	Fan	Air	Air	Air
Automatic PVT F/N/R; Shaft	Automatic PVT F/N/R; O-ring Chain	Automatic PVT F/N/R; O-ring Chain	Automatic PVT F/N/R; O-ring Chain	Automatic PVT Forward; Chain
2WD	2WD	2WD	2WD	2WD
N.A.	N.A.	N.A.	N.A.	N.A.
Dual A-Arm 7" (17.8 cm) Travel	Single A-Arm 5" (12.7 cm) Travel	Single A-Arm with 5" (12.7 cm) Travel	Single A-Arm with 5" (12.7 cm) Travel	Single A-Arm 3" (7.6 cm) Travel
Mono-Shock Swingarm with 6.5" (16.5 cm) Travel	Swingarm Dual Shocks with 5" (12.7 cm) Travel	Mono-Shock Swingarm with 6" (15.2 cm) Travel	Mono-Shock Swingarm with 6" (15.2 cm) Travel	Mono-Shock Swingarm with 3" (7.6 cm) Travel
Front Hydraulic Disc; Rear Mechanical Drum; (Independent front/rear brake levers plus rear foot brake)	4-Wheel Hydraulic Disc	4-Wheel Drum	4-Wheel Drum	4-Wheel Drum
Lockable Hand Lever	Hand-Actuated	Lockable Hand Lever	Lockable Hand Lever	Lockable Hand Lever
21 x 7-10; Duro	19 x 7-8 Duro	19 x 7-8 Duro	19 x 7-8 Duro	16 x 6.5-7 Duro
20 x 10-9; Duro	20 x 10-9 Duro	18 x 9.5-8 Duro	18 x 9.5-8 Duro	16 x 8-7 Duro
Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel
45" (114.3 cm)	65" (165.1 cm)	41.5" (105.4 cm)	41.5" (105.4 cm)	33" (83.8 cm)
395 lb (179 kg)	493 lb (224 kg)	278 lb	292 lb	210 lb (95.3 kg)
65 x 42 x 42" (165.1 x 106.7 x 106.7 cm)	85 x 48 x 55" (215.9 x 121.9 x 139.7 cm)	61.25 x 36.75 x 38.5" (155.6 x 93.3 x 97.8 cm)	61.75 x 36.75 x 38.5" (156.8 x 93.3 x 97.8 cm)	48 x 31.5 x 28" (121.9 x 80 x 71.1 cm)
5.7" (14.5 cm)	6" (15.2 cm)	4" (10.2 cm)	4" (10.2 cm)	4" (10.2 cm)
SEAT HEIGHT: 32" (81.3 cm)	SEAT HEIGHT: N.A.	SEAT HEIGHT: 27" (68.6 cm)	SEAT HEIGHT: 27" (68.6 cm)	SEAT HEIGHT: 23" (58.4 cm)
2.5 gal (9.5 L)	2.5 gal (9.5 L)	1.6 gal (5.9 L)	2.0 gal (7.8 L)	1.2 gal (4.5 L)
N.A.	N.A.	N.A.	N.A.	N.A.
N.A.	N.A.	N.A.	15 lb/30 lb (6.8 kg/13.6 kg)	N.A.
N.A.	N.A.	N.A.	N.A.	N.A.
300 lb (136.1 kg) - with Accessory Hitch	N.A.	N.A.	N.A.	N.A.
Accessory/Drawbar	N.A.	N.A.	N.A.	N.A.
N.A.	N.A.	N.A.	N.A.	N.A.
Single Hi/Low Headlight; Single Rear Brakelight/Taillight	Dual Front Running Lights; Single Rear Brakelight/Taillight	Dual Front Running Lights; Single Rear Brakelight/Taillight	Dual Front Running Lights; Single Rear Brakelight/Taillight	Dual Front Running Lights; Single Rear Brakelight/Taillight
N.A.	N.A.	N.A.	N.A.	N.A.
N/R Light	N/R Light	N/R Light	N/R Light	N.A.
Voodoo Blue/White	Bright White, Voodoo Blue	Voodoo Blue; Pink Power	Sage Green	Voodoo Blue, Pink Power

RZR XP® Turbo EPS	RZR® 4 900 EPS	RZR XP® 4 1000 EPS
4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder
925cc	875cc	999 cc
Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
Liquid	Liquid	Liquid
Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
High-Performance On-Demand True AWD/2WD	High-Performance On-Demand True AWD/2WD	High-Performance On-Demand True AWD/2WD
Not Equipped	Not Equipped	Not Equipped
Dual A-Arm 2.5" FOX Podium Internal Bypass Shocks (comp adjust/res.) with Anti-Sway Bar 16" (40.6 cm) Travel	Dual A-Arm FOX Performance Series - 2.0 Podium X 12.25" (31.1 cm) Travel	Dual A-Arm Walker Evans 2" Needle Shocks (comp adjust/res.) with Anti-Sway Bar 16" (40.6 cm) Travel
Trailing Arm 3.0" FOX Podium Internal Bypass Shocks (comp adjust/remote res.) with Anti-Sway Bar 18" (45.7 cm) Travel	Dual A-Arm FOX Performance Series - 2.0 Podium X with Anti-Sway Bar 13.2" (33.5 cm) Travel	Trailing Arm Walker Evans 2.5" Needle Shocks (comp adjust/remote res.) with Anti-Sway Bar 18" (45.7 cm) Travel
4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
Park in Transmission	Park in Transmission	Park in Transmission
29 x 9-14 Maxxis Bighorn	27 x 9-12; GBC Dirt Commander	29 x 9-14; Maxxis Bighorn
29 x 11-14 Maxxis Bighorn	27 x 11-12; GBC Dirt Commander	29 x 11-14; Maxxis Bighorn
Cast Aluminum	Cast Aluminum	Cast Aluminum
90" (228.6 cm)	106.5" (270.5 cm)	117" (297.2 cm)
1,495 lb (678.1 kg)	1,474 lb (668.6 kg)	1,565 lb (709.8 kg)
119" x 64" x 73.75" (302.2 x 162.6 x 187.3 cm)	138.1" x 60" x 71.7" (350.8 x 152.4 x 182.1 cm)	146" x 64" x 73.75" (370.8 x 162.6 x 187.3 cm)
13.5" (34.3 cm)	12.5" (31.8 cm)	13.5" (34.3 cm)
9.5 gal (36 L)	9.5 gal (36 L)	9.5 gal (36 L)
28 x 22 x 7" (72 x 57 x 17.8 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)
N.A./300 lb (136.1 kg)	N.A./300 lb (136.1 kg)	N.A./300 lb (136.1 kg)
740 lb (335.6 kg)	900 lb (408.2 kg)	900 lb (408.2 kg)
N.A.	1,500 lb (680.4 kg)	N.A.
None	Standard/1.25" Receiver	None
Lock & Ride	Lock & Ride	Lock & Ride
White LED, Low/High & Red LED Tail / Brake Lights	Halogen, 55W Low/ 60W High & Red LED Tail / Brake Lights	White LED, Low/High & Red LED Tail / Brake Lights
Standard	Standard	Standard
Digital Gauge, Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, DC Outlets (2)	Digital Gauge, Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, DC Outlets (2)	Digital Gauge, Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, 2 DC Outlets (Front & Rear)
Graphite Crystal, Spectra Orange, Velocity Blue	Harava Red Pearl, Blue Fire	Titanium Matte Metallic, Electric Blue Metallic

**POLARIS**  
**SPORTSMAN**®



	SPORTSMAN® 450 H.O.	SPORTSMAN® 570 (Avail. EPS)	SPORTSMAN® 570 SP	SPORTSMAN® X2 570 EPS	SPORTSMAN® TOURING 570 (Avail. EPS)	SPORTSMAN® TOURING 570 SP	SPORTSMAN® 850 / SP	SPORTSMAN® XP® 1000
ENGINE	Engine Type	4-Stroke OHC Single Cylinder	4-Stroke DOHC Single Cylinder	4-Stroke DOHC Single Cylinder	4-Stroke DOHC Single Cylinder	4-Stroke DOHC Single Cylinder	4-Stroke SOHC Twin Cylinder	4-Stroke SOHC Twin Cylinder
	Displacement	567cc	567cc	567cc	567cc	567cc	850cc	952cc
	Fuel System	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injected	Electronic Fuel Injected
	Cooling	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid
DRIVE TRAIN	Transmission/Final Drive	Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Shaft
	Drive System	On-Demand True AWD/2WD	On-Demand True AWD/2WD	Close Ratio On-Demand True AWD/2WD	Close Ratio On-Demand True AWD/2WD w/VersaTrac Turf Mode	On-Demand True AWD/2WD	Close Ratio On-Demand True AWD/2WD	On-Demand True AWD/2WD
	Engine Braking System/Active Descent Control	No/No	No/No EPS: Yes/No	Standard/Standard	Standard/Standard	No/No EPS: Yes/No	Standard/Standard	Standard/No SP: Standard/Standard
SUSPENSION	Front Suspension	MacPherson Strut 8.2" (20.8 cm) Travel	MacPherson Strut 8.2" (20.8 cm) Travel	Dual A-arm 8.2" (20.8 cm) Travel	MacPherson Strut 8.2" (20.8 cm) Travel	MacPherson Strut 8.2" (20.8 cm) Travel	Dual A-Arm 8.2" (20.8 cm) Travel	Dual A-Arm 9" (22.9 cm) Travel
	Rear Suspension	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, Rolled 10.25" (26 cm) Travel	Dual A-Arm, Rolled 10.25" (26 cm) Travel
BRAKES	Front/Rear Brakes	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake
	Parking Brake	Park in Transmission/Lockable Hand Lever	Park in Transmission/Lockable Hand Lever	Park in Transmission/Lockable Hand Lever	Park in Transmission/Lockable Hand Lever	Park in Transmission/Lockable Hand Lever	Park in Transmission/Lockable Hand Lever	Park in Transmission/Lockable Hand Lever
TIRES AND WHEELS	Front Tires	24 x 8-12	25 x 8-12	26 x 8-14	25 x 8-12	25 x 8-12	26 x 8-14	26 x 8-14
	Rear Tires	24 x 10-12	25 x 10-12	26 x 10-14	25 x 10-12	25 x 10-12	26 x 10-14	26 x 10-14
	Wheels	Stamped Steel	Stamped Steel	Cast Aluminum	Stamped Steel	Cast Aluminum	Stamped Steel; SP: Cast Aluminum	Cast Aluminum
DIMENSIONS/CAPACITIES	Wheelbase	50.5" (128.3 cm)	50.5" (128.3 cm)	50.5" (128.3 cm)	56" (142.2 cm)	56" (142.2 cm)	53" (134.6 cm)	53" (134.6 cm)
	Dry Weight	702 lb (318 kg) EPS: 713 lb (323 kg)	702 lb (318 kg) EPS: 713 lb (323 kg)	730 lb (332 kg)	788 lb (358 kg) EPS: 793 lb (336 kg)	773 lb (351 kg)	753 lb (342 kg) SP: 767 lb (349 kg)	822 lb (374 kg)
	Overall Vehicle Size (L x W x H)	83 x 48 x 46" (210.8 x 121.9 x 116.8 cm)	83 x 48 x 48" (210.8 x 121.9 x 121.9 cm)	83 x 48 x 48" (210.8 x 121.9 x 121.9 cm)	89 x 48 x 48" (218.4 x 121.9 x 121.9 cm)	86 x 48 x 48" (218.4 x 121.9 x 121.9 cm)	86 x 48 x 48" (218.4 x 121.9 x 121.9 cm)	83.25 x 47.6 x 50.75" (211.4 x 120.9 x 128.9 cm)
	Ground Clearance	10.25" (26 cm)	11" (27.9 cm)	11.5" (29.2 cm)	11" (27.9 cm)	11" (27.9 cm)	11.5" (29.2 cm)	11.5" (29.2 cm)
	Seat Height	33.25" (84.5cm)	33.75" (85.7 cm)	34.25" (87 cm)	33.75" (85.7 cm)	33.75" (85.7 cm)	34.25" (87 cm)	37" (94 cm)
	Fuel Capacity	4.5 gal (17 L)	4.5 gal (17 L)	4.5 gal (17 L)	4.5 gal (17 L)	4.5 gal (17 L)	4.5 gal (17 L)	5.25 gal (19.9 L)
	Bed Box Dimensions (L x W x H)	N.A.	N.A.	N.A.	37.5"x19.5"x6.5" (95x49.5x16.5 cm)	N.A.	N.A.	N.A.
	Front/Rear Rack or Box Capacity	90 lb (40.8 kg)/ 180 lb (81.6 kg)	90 lb (40.8 kg)/ 180 lb (81.6 kg)	90 lb (40.8 kg)/ 180 lb (81.6 kg)	90 lb (40.8 kg)/ 400 lb (180 kg)	90 lb (40.8 kg)/ 180 lb (81.6 kg)	120 lb (55 kg)/ 240 lb (110 kg)	120 lb (55 kg)/ 240 lb (110 kg)
	Payload Capacity	485 lb (220 kg)	485 lb (220 kg)	485 lb (220 kg)	705 lb (320 kg)	575 lb (261 kg)	485 lb (220 kg)	575 lb (261 kg)
	Hitch Towing Rating	1,225 lb (555.7 kg)	1,225 lb (555.7 kg)	1,500 lb (680 kg)	1,225 lb (555.7 kg)	1,225 lb (555.7 kg)	1,500 lb (680 kg)	1,500 lb (680.4 kg)
FEATURES	Hitch/Type	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver
	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
	Lighting	Dual 50w Low Beam Bumper Lights, Single 50w High Beam Pod Light; Dual Brakelights/Taillights	Dual 50w Low Beam Bumper Lights, Single 50w High Beam Pod Light; Dual Brakelights/Taillights	Triple 50w High Beam, Dual 50w Low Beam Headlights; Dual Brakelights/Taillights	Dual 50w Low Beam Bumper Lights, Single 50w High Beam Pod Light; Dual Brakelights/Taillights	Triple 50w High Beam, Dual 50w Low Beam Headlights; Dual Brakelights/Taillights	Triple 50w High Beam, Dual 50w Low Beam Headlights; Dual Brakelights/Taillights	Triple 50w High Beam, Dual 50w Low Beam Headlights; Dual Brakelights/Taillights
	Electronic Power Steering	N.A.	N.A. / EPS: Standard	Standard	Standard	N.A. / EPS: Standard	Standard	N.A./Standard
Instrumentation	Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripometers, Hour meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripometers, Hour meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripometers, Hour meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripometers, Hour meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Turf Indicator, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripometers, Hour meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Turf Indicator, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripometers, Hour Meter, Clock, Service Time, Diagnostic Indicator, Gear Indicator, Fuel Gauge, Hi-Temp/Low-Batt Lights, DC Outlet	Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripometers, Hour Meter, Clock, Service Time, Diagnostic Indicator, Gear Indicator, Fuel Gauge, Hi-Temp/Low-Batt Lights, DC Outlet	Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripometers, Hour Meter, Clock, Service Time, Diagnostic Indicator, Gear Indicator, Fuel Gauge, Hi-Temp/Low-Batt Lights, DC Outlet
	Colors	Sage Green, Velocity Blue	Sage Green, Indy Red, Yellow, Polaris Pursuit Camo EPS: Sage Green, Indy Red, Velocity Blue, Polaris Pursuit Camo	Sunset Red, Titanium Matte Metallic, Polaris Pursuit Camo	Sage Green, Indy Red	Sage Green EPS: Bright White	Blue Fire	White Lightning, Sage Green, Polaris Pursuit Camo SP: Sunset Red, Titanium Matte Metallic





SPORTSMAN® TOURING 850 SP	SPORTSMAN® TOURING XP 1000 / LTD	SCRAMBLER® 850 HO	SCRAMBLER XP® 1000	SPORTSMAN® 850 HIGH LIFTER	SPORTSMAN XP® 1000 HIGH LIFTER
4-Stroke SOHC Twin Cylinder	4-Stroke SOHC Twin Cylinder	4-Stroke SOHC Twin Cylinder	4-Stroke SOHC Twin Cylinder	4-Stroke SOHC Twin Cylinder	4-Stroke SOHC Twin Cylinder
850cc	952cc	850cc	952cc	850cc	952cc
Electronic Fuel Injected	Electronic Fuel Injected	Electronic Fuel Injected	Electronic Fuel Injected	Electronic Fuel Injected	Electronic Fuel Injected
Liquid	Liquid	Liquid	Liquid	Liquid	Liquid
Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Geared Down, Shaft	Automatic PVT P/R/N/L/H; Geared Down, Shaft
Close Ratio On-Demand True AWD/2WD	Close Ratio On-Demand True AWD/2WD	On-Demand True AWD/2WD	Close Ratio On-Demand True AWD/2WD	On-Demand True AWD/2WD	Close Ratio On-Demand True AWD/2WD
Standard/Standard	Standard/Standard	No/No	No/No	No/No	No/No
Dual A-Arm 9" (22.9 cm) Travel	Dual A-Arm 9" (22.9 cm) Travel	Dual A-Arm 9" (22.9 cm) Travel	Dual A-Arm 9" (22.9 cm) Travel	Hi Clearance Arched Dual A-Arm 7.4" (18.8 cm) Travel	Hi Clearance Dual A-Arm 7.4" (18.8 cm) Travel
Dual A-Arm, Rolled 10.25" (26 cm) Travel	Dual A-Arm, Rolled 10.25" (26 cm) Travel	Dual A-Arm, Rolled 10.25" (26 cm) Travel	Dual A-Arm, Rolled 10.25" (26 cm) Travel	Hi Clearance Arched Dual A-Arm, Rolled 6.7" (17 cm) Travel	Hi Clearance Arched Dual A-Arm, Rolled 6.7" (17 cm) Travel
Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake
Park in Transmission/ Lockable Hand Lever	Park in Transmission/ Lockable Hand Lever	Park in Transmission/ Lockable Hand Lever	Park in Transmission/ Lockable Hand Lever	Park in Transmission/Lockable Hand Lever	Park in Transmission/Lockable Hand Lever
26 x 8-14	26 x 9-14	26 x 8-14	26 x 8-14	29.5 x 9.5-14	29.5 x 9.5-14
26 x 10-14	26 x 11-14	26 x 10-14	26 x 10-14	29.5 x 9.5-14	29.5 x 9.5-14
Cast Aluminum	Cast Aluminum	Stamped Steel	Cast Aluminum	Stamped Steel	Cast Aluminum
57" (144.8 cm)	57" (144.8 cm)	53" (134.6 cm)	53" (134.6 cm)	53" (134.6 cm)	53" (134.6 cm)
804 lb (365 kg)	886 lb (403 kg)	735 lb (333 kg)	745 lb (338 kg)	921 lb (417 kg)	974 lb (441 kg)
86.5 x 47.6 x 58.25" (219.7 x 120.9 x 147.9 cm)	86.5 x 47.6 x 58.25" (219.7 x 120.9 x 147.9 cm)	82.3" X 48.6" X 48.4" (209 cm X 123 cm X 123 cm)	82.3" X 48.6" X 48.4" (209 cm X 123 cm X 123 cm)	83 x 49 x 52" (210 x 124 x 132 cm)	88 x 49 x 52" (223 x 124 x 132 cm)
11.25" (28.5 cm)	11.25" (28.5 cm)	11.5" (29.2 cm)	11.5" (29.2 cm)	13.5" (34.3 cm)	15" (38.1 cm)
35.75" (90.8 cm)	35.75" (90.8 cm)	35" (89 cm)	35" (89 cm)	39" (99 cm)	39" (99 cm)
5.25 gal (19.9 L)	5.25 gal (19.9 L)	5.25 gal (19.9 L)	5.25 gal (19.9 L)	5.25 gal (19.9 L)	5.25 gal (19.9 L)
N.A.	N.A.	N.A.	N.A.	N.A.	N.A.
120 lb (55 kg)/ 240 lb (110 kg)	120 lb (55 kg)/ 240 lb (110 kg)	25 lb (11.3 kg) 50 lb (22.7 kg)	25 lb (11.3 kg) 50 lb (22.7 kg)	0 lb (0 kg)/75 lb (34 kg)	0 lb (0 kg)/75 lb (34 kg)
575 lb (261 kg)	575 lb (261 kg)	290 lb (131 kg)	290 lb (131 kg)	290 lb (132 kg)	290 lb (132 kg)
1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)
Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver
Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
Triple 50w High Beam, Dual 50w Low Beam Headlights; Dual Brakelights/Tailights	Triple 50w High Beam, Dual 50w Low Beam Headlights; Dual Brakelights/Tailights	Dual Hi/Low Beam (50w/50w) Headlights; Single Rear Taillight	White LED; Hi/Low Beam; Single Rear Taillight	Dual 50w Low Beam Headlights; Dual Brakelights/Tailights	Dual 50w Low Beam Headlights; Dual Brakelights/Tailights
Standard	Standard	N.A.	Standard	N.A.	Standard
Analog Speedometer, Digital Odometer, Tachometer, Two Tripometers, Hour Meter, Clock, Service Indicator, Diagnostic Indicator, Gear Indicator, Fuel Gauge, AWD Indicator, Hi-Temp/Low-Batt Lights, DC Outlet	Analog Speedometer, Digital Odometer, Tachometer, Two Tripometers, Hour Meter, Clock, Service Indicator, Diagnostic Indicator, Gear Indicator, Fuel Gauge, AWD Indicator, Hi-Temp/Low-Batt Lights, DC Outlet	Analog Speedometer, Digital Odometer, Tachometer, Two Tripometers, Hour Meter, Clock, Service Indicator, Diagnostic Indicator, Gear Indicator, Fuel Gauge, Hi-Temp/Low-Batt Lights, DC Outlet	Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripometers, Hour Meter, Clock, Service Time, Diagnostic Indicator, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripometers, Hour Meter, Clock, Service Time, Diagnostic Indicator, Gear Indicator, Fuel Gauge, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Analog Speedometer, Odometer, Tachometer, Two Tripometers, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Hi-Temp Light, Clock, DC Outlet
Sunset Red	Black Pearl LTD: Pearl White	White Lightning	Titanium Matte Metallic, Titanium Matte Lime	High Lifter Edition Orange Madness	High Lifter Edition Stealth Black



ACE™	2015 ACE™ 570	ACE™ 570 SP	ACE™ 900 SP
4-Stroke DOHC Single Cylinder	4-Stroke DOHC Single Cylinder	4-Stroke DOHC Single Cylinder	4-Stroke DOHC Twin Cylinder
325cc	567cc	567cc	875 cc
Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
Liquid	Liquid	Liquid	Liquid
Automatic PVT P/R/N/L/H; Shaft			
On-Demand True AWD/2WD	On-Demand True AWD/2WD	Close Ratio On-Demand True AWD/2WD	Close Ratio On-Demand True AWD/2WD
No/No	No/No	Standard/No	No/No
MacPherson Strut 8.2" (20.8 cm) Travel			
Dual A-Arm, IRS 9.5" (24.1 cm) Travel			
4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc
Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission
25 x 8-12	25 x 8-12	25 x 8-12	25 x 8-12
25 x 10-12	25 x 10-12	25 x 10-12	25 x 10-12
Stamped Steel	Stamped Steel	Cast Aluminum	Cast Aluminum
61.5" (156.2 cm)	61.5" (156.2 cm)	61.5" (156.2 cm)	61.5" (156.2 cm)
830 lb (377 kg)	854 lb (388 kg)	881 lb (400.5 kg)	966 lb (439 kg)
90" x 48" x 68" (229 cm x 122 cm x 173 cm)	90" x 48" x 68" (229 cm x 122 cm x 173 cm)	90" x 48" x 68" (229 cm x 122 cm x 173 cm)	90" x 48" x 68" (229 cm x 122 cm x 173 cm)
10.25" (26 cm)	10.25" (26 cm)	10.25" (26 cm)	10" (25.4 cm)
N.A.	N.A.	N.A.	N.A.
5.25 gal (19.9 L)			
18" x 35" x 4" (46 cm x 89 cm x 10 cm)	18" x 35" x 4" (46 cm x 89 cm x 10 cm)	18" x 35" x 4" (46 cm x 89 cm x 10 cm)	18" x 35" x 4" (46 cm x 89 cm x 10 cm)
120 lb (55 kg)/ 240 lb (110 kg)			
575 lb (261 kg)			
1,500 lb (680.4 kg)			
Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver
Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
Dual 50w Low Beam Bumper Lights, Dual Brakelights/Taillights	Dual 50w Low Beam Bumper Lights, Dual Brakelights/Taillights	Dual 50w Low Beam Bumper Lights, Dual Brakelights/Taillights	Dual 50w Low Beam Bumper Lights, Dual Brakelights/Taillights
N.A.	N.A.	Standard	Standard
Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripometers, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripometers, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripometers, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripometers, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Hi-Temp Light, Clock, DC Outlet
Indy Red, Sage Green	White Lightning, Velocity Blue	Polaris Pursuit Camo	Stealth Black

# POLARIS® RANGER®



	RANGER® EV	RANGER® EV Li-Ion	RANGER® ETX	RANGER® 570 (Avail. EPS)	RANGER CREW® 570-4 (Avail. EPS)	RANGER® 570 Full-Size	RANGER® XP 570 (Avail. EPS)	RANGER CREW® 570-6 (Avail. EPS)
ENGINE	Engine Type	Single 48-Volt, High-Efficiency, AC-Induction Motor	Single 48-Volt, High Efficiency, AC-Induction Motor	4-Stroke Single Cylinder				
	Displacement	N.A.	N.A.	325cc	567cc	567cc	567cc	567cc
	Fuel System/Battery	6 Acid	2 Li-Ion	Electronic Fuel Injection				
	Cooling	N.A.	N.A.	Liquid	Liquid	Liquid	Liquid	Liquid
DRIVE TRAIN	Transmission/Final Drive	Direct Drive With Low-Noise Gears	Direct Drive With Low-Noise Gears	Automatic PVT H/L/N/R/P; Shaft				
	Drive System	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD	On-Demand True AWD/2WD/ VersaTrac Turf Mode ***
	Engine Braking System/ Active Descent Control	Not Equipped	Not Equipped	Not Equipped	Not Equipped / Hunter Edition: ADC/EBS	Not Equipped	Not Equipped	Not Equipped
SUSPENSION	Front Suspension	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	Dual A-Arm 10.0" (25.4 cm) Travel	Dual A-Arm 10.0" (25.4 cm) Travel
	Rear Suspension	Dual A-Arm, IRS 9" (22.9 cm) Travel	Dual A-Arm, IRS 9" (22.9 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10.0" (25.4 cm) Travel	Dual A-Arm, IRS 10.0" (25.4 cm) Travel
BRAKES	Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
	Parking Brake	Hand-Actuated	Hand-Actuated	Park In-Transmission				
TIRES AND WHEELS	Front Tires	25 x 9-12; Carlisle	25 x 9-12; Carlisle	25 x 8-12; 489	25 x 8-12; 489	25 x 10-12; 489	25 x 8-12; 489	25 x 10-12; 489
	Rear Tires	25 x 9-12; Carlisle	25 x 9-12; Carlisle	25 x 11-12; 489	25 x 11-12; 489	25 x 10-12; 489	25 x 11-12; 489	26 x 11-12; PXT
	Wheels	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel EPS: Cast Aluminum	Stamped Steel	Stamped Steel EPS: Cast Aluminum	Stamped Steel
DIMENSIONS/CAPACITIES	Wheelbase	72" (182.9 cm)	72" (182.9 cm)	73" (185.4 cm)	73" (185.4 cm)	105" (266.7 cm)	75" (190.5 cm)	81" (206 cm)
	Dry Weight	1,726 lb (783 kg)	1,288 lb (584 kg)	1,045 lb (474 kg)	1,042 lb (473 kg) * EPS: 1,059 lb (480 kg)	1,327 lb (602 kg) EPS: 1,344 lb (610 kg)	1,100 lb (499 kg)	1,265 lb (574 kg) EPS: 1,320 lb (599 kg)
	Overall Vehicle Size (L x W x H)	110 x 58 x 73" (279 x 147 x 185 cm)	110 x 58 x 73" (279 x 147 x 185 cm)	110 x 58 x 73" (279 x 147 x 185 cm)	110 x 58 x 73" (279 x 147 x 185 cm)	142 x 60 x 73" (361 x 152 x 185 cm)	114 x 60 x 74" (290 x 152 x 188 cm)	116.5 x 60 x 76" (296 x 152 x 193 cm)
	Ground Clearance	10" (25.4 cm)	10" (25.4 cm)	10" (25.4 cm)	10" (25.4 cm)	10.5" (26.7 cm)	12" (30.5 cm)	11.3" (28.7 cm)
	Seats	2	2	2	2	4	3	3
	Fuel Capacity	N.A.	N.A.	9 gal (34.1 L)	9 gal (34.1 L)	9 gal (34.1 L)	10 gal (37.9 L)	10 gal (37.9 L)
	Bed Box Dimensions (L x W x H)	32 x 42 x 11.5" (81 x 107 x 29 cm)	32 x 42 x 11.5" (81 x 107 x 29 cm)	32 x 42 x 11.5" (81 x 107 x 29 cm)	32 x 42 x 11.5" (81 x 107 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)
	Box Capacity	500 lb (226.8 kg)	500 lb (226.8 kg)	500 lb (226.8 kg)	500 lb (226.8 kg)	500 lb (226.8 kg)	800 lb (363 kg)	1,000 lb (453.6 kg)
	Payload Capacity	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)	1,000 lb (453.6 kg) *	1,250 lb (567 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)
	Hitch Towing Rating	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	2,000 lb (907.2 kg)
FEATURES	Hitch/Type	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver
	Cargo System/Cab	Lock & Ride/ProFit	Lock & Ride/ProFit	Lock & Ride/ProFit	Lock & Ride/ProFit	Lock & Ride/Available	Lock & Ride/ProFit	Lock & Ride/ProFit
	Lighting	50W Headlight, LED Tail	50W Headlight, LED Tail	50W Headlight, LED Tail	50W Headlight, LED Tail	50W Headlight, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high
Electronic Power Steering	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped; EPS: Standard	Not Equipped	Not Equipped; EPS: Standard	Not Equipped; EPS: Standard
	Instrumentation	Digital Hour Meter, Mode Indicator, DC Outlet, Hi-Temp Light, Change Cycle Indicator, Battery Life Indicator	Digital Gauge, Speedometer, Odometer, Trip Meter, Clock, Gear Indicator, 2WD/AWD/Turf Indicator, Faults	Digital Gauge, Speedometer, Odometer, Tachometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp, Coolant Temperature, Voltmeter, Service Indicator, Seat Belt Reminder, DC Outlets (2)	Digital Gauge, Speedometer, Odometer, Tachometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp, Coolant Temperature, Voltmeter, Service Indicator, Seat Belt Reminder, DC Outlets (1)	Digital Gauge, Speedometer, Odometer, Tachometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp, Coolant Temperature, Voltmeter, Service Indicator, Seat Belt Reminder, DC Outlets (1)	Digital Gauge, Speedometer, Odometer, Tachometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp, Coolant Temperature, Voltmeter, Service Indicator, Seat Belt Reminder, DC Outlets (1)	Digital Gauge, Speedometer, Odometer, Tachometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp, Coolant Temperature, Voltmeter, Service Indicator, Seat Belt Reminder, DC Outlets (2)
Colors		Avalanche Grey , Polaris Pursuit Camo	Polaris Pursuit Camo	Sage Green, White Lightning	Solar Red, Sage Green, Polaris Pursuit Camo EPS: Sunset Red	* Solar Red, Sage Green, Polaris Pursuit Camo EPS: Super Graphite	Solar Red, Sage Green	Solar Red, Sage Green, Polaris Pursuit Camo EPS: Pearl White
								Sage Green EPS: Polaris Pursuit Camo

\*Feature may vary on RANGER 570 Base/Hunter Edition models

\*\*Feature may vary based on RANGER XP 900 Base/Hunter/Hunter Deluxe/Turf/NorthStar/High Lifter Edition models.

\*\*\*Pro-Lock® available on all full-size EPS models and 570 Hunter Edition; Except CREW 570-6 EPS Polaris Pursuit Camo & Diesel models



<b>RANGER XP® 900 (Avail. EPS)</b>	<b>RANGER XP® 900 EPS High Lifter Edition</b>	<b>RANGER CREW® 900-5 &amp; -6 (Avail. EPS)</b>	<b>RANGER® DIESEL</b>	<b>RANGER CREW® DIESEL</b>	<b>RANGER® 6x6</b>	<b>2015 RANGER® DIESEL HST</b>	<b>2015 RANGER® DIESEL HST Deluxe (Cab w/ HVAC)</b>
4-Stroke Twin Cylinder	4-Stroke Twin Cylinder	4-Stroke Twin Cylinder	3-Cylinder Diesel	3-Cylinder Diesel	4-Stroke Twin Cylinder	3-Cylinder Diesel	3-Cylinder Diesel
875cc	875cc	875cc	1028cc	1028cc	760cc	1028cc	1028 cc
Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Mechanical Injection	Mechanical Injection	Electronic Fuel Injection	Indirect Injection	Indirect Injection
Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid
Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic Hydrostatic w/Treadle Pedal (H/L/N/Park)	Automatic Hydrostatic w/Treadle Pedal (H/L/N/Park)
On-Demand True AWD/2WD/ VersaTrac Turf Mode ***	Pro-Lock On-Demand AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True 4WD/Rear 4WD/Mid Differential Lock	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD/ VersaTrac Turf Mode
Not Equipped / Hunter Ed.: EBS / Hunter Dlx: EBS & ADC / Trail Ed: EBS & ADC	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Hydrostatic EBS	Hydrostatic EBS
Dual A-Arm 10.0" (25.4 cm) Travel	Dual A-Arm 8.0" (20.3 cm) Travel	Dual A-Arm 10.0" (25.4 cm) Travel	Dual A-Arm 10.0" (25.4 cm) Travel	Dual A-Arm 10.0" (25.4 cm) Travel	Dual A-Arm 9.6" (24.4 cm) Travel	Dual A-Arm 6" (15.24 cm) Travel	Dual A-Arm 6" (15.24 cm) Travel
Dual A-Arm, IRS 10.0" (25.4 cm) Travel	Dual A-Arm, IRS 8.8" (22.4 cm) Travel	Dual A-Arm, IRS 10.0" (25.4 cm) Travel	Dual A-Arm, IRS 10.0" (25.4 cm) Travel	Dual A-Arm, IRS 10.0" (25.4 cm) Travel	Dual A-Arm, IRS 9" (22.9 cm) Travel	De Dion 6" (15.24 cm) Travel	De Dion 6" (15.24 cm) Travel
4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission	Hand-Actuated	Park In-Transmission	Park In-Transmission
26 x 9-12; 489 / Painted: PXT	28x9.5-14; Outlaw 2	26 x 9-12; PXT	25 x 10-12; 489	26 x 9-12; PXT	25 x 10-12; 489	25 x 10-12; 489	25 x 10-12; 489
26 x 11-12; 489 / Painted: PXT	28x11-14; Outlaw 2	26 x 11-12; PXT	25 x 11-12; 489	26 x 11-12; PXT	25 x 11-12; 489	25 x 11-12; 489	25 x 11-12; 489
Stamped Steel Painted: Cast Aluminum	Cast Aluminum Buckle	Stamped Steel EPS: Cast Aluminum	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel
81" (206 cm)	83 in. (211 cm)	113" (287 cm)	81 in (206 cm)	113" (287 cm)	105" (266.7 cm)	84" (213.4cm)	84" (213.4cm)
1,318 lb (598 kg) ** EPS: 1,373 lb (622 kg)	1,561 lb (708.1 kg)	1,571 lb (713 kg) EPS: 1,587 lb (720 kg)	1,430 lb (649 kg)	1,690 lb (767 kg)	1,551 lb (704 kg)	1,647 lb (747 kg)	1,915 lb (868 kg)
116.5 x 60 x 76" *** (296 x 152 x 193 cm)	123 x 66.5 x 77" (312 x 169 x 196 cm)	148.5 x 61 x 76" (377 x 155 x 193 cm)	116.5 x 60 x 76" (296 x 152 x 193 cm)	148.5 x 61 x 76" (377 x 155 x 193 cm)	137 x 60 x 76" (348 x 152 x 193 cm)	123.5 x 64 x 73" (314 x 163 x 185 cm)	123.5 x 64 x 73" (314 x 163 x 185 cm)
12" (30.5 cm)	13 in. (33 cm)	11.3" (28.7 cm)	12" (30.5 cm)	11.3" (28.7 cm)	12" (30.5 cm)	10" (25.4 cm)	10" (25.4 cm)
3	3	5 or 6	3	6	3	3	3
10 gal (37.9 L)	10 gal (37.9 L)	10 gal (37.9 L)	10 gal (37.9 L)	10 gal (37.9 L)	9 gal (34.1 L)	10 gal (37.9 L)	10 gal (37.9 L)
36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.5 x 54 x 11.5 in. (93 x 137 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)	42.5 x 54 x 11.5" (108 x 137 x 29 cm)	43.5 x 54 x 11.5" (110.5 x 137 x 29 cm)	43.5 x 54 x 11.5" (110.5 x 137 x 29 cm)
1,000 lb (453.6 kg)	N.A./1,000 lb (453.6 kg)	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)	1,250 lb (567 kg)	1,250 lb (567 kg)	1,250 lb (567 kg)
1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,750 lb (793.8 kg)	1,500 lb (680.4 kg)	1,750 lb (793.8 kg)	2,000 lb (907.2 kg)	1,750 lb (793.8 kg)	1,750 lb (793.8 kg)
2,000 lb (907.2 kg)	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)
Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver
Lock & Ride/ProFit	Lock & Ride/ProFit	Lock & Ride/ProFit	Lock & Ride/ProFit	Lock & Ride/ProFit	Lock & Ride/Available	Lock & Ride/ProFit	Lock & Ride/ProFit
55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high	55W low/ 60W high, LED Tail	55W low/ 60W high	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail
Not Equipped; EPS: Standard	Standard	Not Equipped; EPS: Standard	Not Equipped	Not Equipped	Not Equipped	Hydraulic Power Steering	Hydraulic Power Steering
Digital Gauge, Speedometer, Odometer, Tachometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp, Coolant Temperature, Voltmeter, Service Indicator, Seat Belt Reminder, DC Outlets (2)	Digital Gauge, Speedometer, Odometer, Tachometer, Tripmeter, Fuel Gauge, Hi-Temp, Coolant Temperature, Voltmeter, Service Indicator, Seat Belt Reminder, DC Outlets (2)	Digital Gauge, Speedometer, Odometer, Tachometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp, Coolant Temperature, Voltmeter, Service Indicator, Seat Belt Reminder, DC Outlets (2)	Digital Gauge, Speedometer, Odometer, Tachometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp, Coolant Temperature, Voltmeter, Service Indicator, Seat Belt Reminder, DC Outlets (2)	Digital Gauge, Speedometer, Odometer, Tachometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp, Coolant Temperature, Voltmeter, Service Indicator, Seat Belt Reminder, DC Outlets (2)	Digital Gauge, Speedometer, Odometer, Tachometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp, Coolant Temperature, Voltmeter, Service Indicator, Seat Belt Reminder, DC Outlets (2)	Digital Gauge, Speedometer, Odometer, Tachometer, Tripmeter, Hour Meter, Clock, Gear Indicator, Fuel Gauge, Hi-Temp/Low-Batt Lights, DC Outlets (2)	Digital Gauge, Speedometer, Odometer, Tachometer, Tripmeter, Hour Meter, Clock, Gear Indicator, Fuel Gauge, Hi-Temp/Low-Batt Lights, DC Outlets (2)
* Solar Red, Sage Green, Polaris Pursuit Camo (Non-EPS) EPS: Sunset Red, Titanium Matte Metallic, Black Pearl, Velocity Blue, Stealth Black, Blue Fire	High Lifter Edition Stealth Black	Sage Green EPS: Sunset Red, Titanium Matte, Velocity Blue, Polaris Pursuit Camo	Sage Green	Sage Green	Avalanche Grey, Sage Green	Sage Green, Polaris Pursuit Camo	Sage Green



Pearl White

Titanium Matte Metallic

Velocity Blue

Black Pearl

Stealth Black

Blue Fire

# MEET THE 2016 HIGH LIFTER EDITION MODELS, NOW AVAILABLE IN THE RZR®, RANGER® & SPORTSMAN® LINE-UPS.



## THE 2016 LINE-UP OF HIGH LIFTER EDITION MODELS ARE BUILT TO HANDLE THE WAY YOU RIDE.

Not only will you stand out amongst the crowd with custom High Lifter graphics kits, color matched & factory installed accessories, these machines will be sure to get you to where you need to go. Fitted with premium High Lifter Outlaw II tires, high clearance A-Arms, mud-specific gearing, and built with high mount air intake and vent lines, you'll be able to tackle the thickest mud around.

WARNING: Polaris off-road vehicles can be hazardous to operate and are not intended for on-road use. Driver must be at least 16 years old with a valid driver's license to operate. Passengers, if permitted, must be at least 12 years old. All riders should always wear helmets, eye protection, and protective clothing. Always use seat belts and cab nets or doors (as equipped). Never engage in stunt driving, and avoid excessive speeds and sharp turns. Riding and alcohol/drugs don't mix. All riders should take a safety training course. Call 800-342-3764 for additional information. Check local laws before riding on trails. ©2015 Polaris Industries Inc. Printed in the U.S.A. Part#9930171

**POLARIS.COM**

 **POLARIS**