



## VESPA PRIMAVERA BATIK 50 – TECHNICAL SPECIFICATIONS

**ENGINE** Single cylinder 4-stroke, 3 valves, i-get Single cylinder  
**DISPLACEMENT** 49 cc  
**BORE X STROKE** 39 mm x 41.4 mm  
**MAX POWER AT**  
    **THE CRANK** 3.1 hp @ 7,750 rpm  
    **SHAFT**  
**MAX TORQUE** 2.3 ft-lb @ 5,750 rpm  
**CONSUMPTION** 90.6 mpg  
**CO2 EMISSIONS**  
    **COMPLIANCE** 92.5 mpg  
**FUEL SYSTEM** Electronic injection  
    **COOLING** Forced air  
    **STARTER** Electric  
**GEARBOX** CVT continuously variable transmission with torque server  
    **CLUTCH** Automatic centrifugal dry clutch with vibration dampers  
**LOAD-BEARING**  
    **STRUCTURE** Sheet steel body with welded reinforcements  
    **FRONT** Single-sided link arm with coil spring and hydraulic monoshock  
    **SUSPENSION** absorber  
    **REAR**  
    **SUSPENSION** Coil spring with hydraulic monoshock absorber  
**FRONT BRAKE** Ø 200 mm stainless steel disc with hydraulic control  
**REAR BRAKE** Ø 140 mm drum mechanically operated  
**ABS SYSTEM** -  
**FRONT TYRE** Tubeless 110/70 - 12"  
**REAR TYRE** Tubeless 120/70 - 12"  
**LENGTH / WIDTH /**  
    **WHEELBASE** 73.2 / 29.3 / 52.4 in  
**SEAT HEIGHT** 30.9 in  
**FUEL TANK CAPACITY** 1.98 gal  
    **EMISSIONS**  
    **COMPLIANCE** Euro 5