



# 2019 CFMOTO CFORCE 400 HO/HO EPS LX

STARTING AT  
**\$4,999\***



**Best 5 Year**  
(LIMITED)  
**Warranty\*\***

**CFMOTO.CA**



**WIND  
ZONE**  
windzone.ca

\*Plus PDI, freight and applicable taxes. Photos are for illustrative purposes only and any accessories shown are not included. Subject to change without notice. Details in store. \*\*5 Year limited warranty: 1 year full + balance 48 months powertrain only or 5,000 km.

# 2019 CFMOTO CFORCE 400 HO/HO EPS LX



**Best 5 Year  
(LIMITED)  
Warranty\*\***

■ NEBULA BLACK  
■ ORANGE  
■ ROYAL BLUE

## PLUS VALUE

**GET IT ALL  
THE BEST!**  
PRICE, WARRANTY,  
FEATURES  
& ADVENTURE!

### STANDARD FEATURES AND BENEFITS

#### SAFETY

Lateral mirrors | Horn | Halogen hi & low beam  
Hazard lights | Flashers  
Anti-theft system with shifter lock

#### LOOK

High quality graphics | Premium glossy paint

#### CONVENIENCE

Trailer connector | Storage back driver seat | Hitch receiver  
12V plug | Double USB Plug | LX Model: Winch (2500 lbs)

#### DURABILITY

Skid plate | Painted steel front bumper | Extended Fender  
A-arm protectors

#### LCD DASHBOARD

Digital information center with brightness control, KM/MPH  
odometer and a multi-function gauge: RPM, speed, tachometer,  
gear position, temperature, engine light, fuel level, hour meter  
and a clock.

**PLUS VALUE  
OF \$999**

### ENGINE

TYPE	Single-Cylinder, 4-valve, 4 strokes
DISPLACEMENT	400 cc
BORE & STROKE	91 x 61.5 mm (3.6 x 2.4 in)
COMPRESSION	10.3 : 1
ENGINE MANAGEMENT	BOSCH EFI & Ignition
MAXIMUM TORQUE	24.3 FT/LB @ 6000 rpm
MAXIMUM POWER OUTPUT	30.5 HP / 7200 rpm
COOLING SYSTEM	Liquid
STARTING	Electric
BATTERY	Yuasa, 30 Amp

### SIZE / WEIGHT

LENGTH x WIDTH x HEIGHT	2100 x 1100 x 1150 mm (82.7 x 43.3 x 45.3 in)
WHEELBASE	1260 mm (49.6 in)
SEAT HEIGHT	530 mm (20.9 in)
GROUND CLEARANCE	240 mm (9.4 in)
FUEL TANK CAPACITY	15 L (3.96 gal)
CURB WEIGHT	360 kg (783 lbs)
TOWING CAPACITY	To come
FRONT/REAR RACK CAPACITY	20 kg (44 lb) / 40 kg (88 lbs)

### TRANSMISSION

CV-TECH IBC clutch system	Primary and secondary variable transmission Gear box: L / H / N / R / P (parking lock shift system)
POWER TRAIN	2 wheel / 4 wheel drive, electric locking differential



### WHEELS

FRONT WHEELS	Steel Wheels (12 x 6 in) LX Model: Aluminium Black rims (12 X 6 po)
REAR WHEELS	Steel Wheels (12 x 7.5 in) LX Model: Aluminium Black rims (12 X 7,5 po)
FRONT TIRES	AT 25 x 8-12 (Innova Mud Gear Lite 6 ply rating)
REAR TIRES	AT 25 x 10-12 (Innova Mud Gear Lite 6 ply rating)

### SUSPENSION AND STEERING

FRONT SUSPENSION	Double wishbone independent suspension Hydraulic shock absorber, five adjustments spring preloads
TRAVEL	229 mm (9 in)
REAR SUSPENSION	Double wishbone independent suspension Hydraulic shock absorber, five adjustments spring preloads
TRAVEL	220 mm (8.7 in)
STEERING	Standard / LX Model : Electronic Power Steering (EPS)

### BRAKES

#### FRONT AND REAR BRAKE DISC SYSTEM

