



2019 CFMOTO UFORCE 500 HO/HO EPS LX



STARTING AT
\$9,999*

**Best 5 Year
(LIMITED)
Warranty ****

CFMOTO.CA



**WIND
ZONE**

windzone.ca

2019 CFMOTO UFORCE 500 HO/HO EPS LX



**Best 5 Year
(LIMITED)
Warranty****

NEBULA BLACK
ROYAL BLUE

ENGINE

TYPE	Single-Cylinder, 4-valve, 4 strokes
DISPLACEMENT	495 cc
BORE & STROKE	91 x 76.2 mm (3.6 x 3 in)
COMPRESSION	10.3 : 1
ENGINE MANAGEMENT	BOSCH EFI & Ignition
MAXIMUM TORQUE	34 FT/LB @ 5800 rpm
MAXIMUM POWER OUTPUT	37.5 HP / 6800 rpm
COOLING SYSTEM	Liquid
STARTING	Electric
BATTERY	Yuasa, 30 Amp

SIZE / WEIGHT

LENGTH x WIDTH x HEIGHT	2980 x 1465 x 1850 mm (117.3 x 57.7 x 72.8 in)
WHEELBASE	1830 mm (72 in)
SEAT HEIGHT	445 mm (17.5 in)
GROUND CLEARANCE	260 mm (10.2 in)
FUEL TANK CAPACITY	26 L (6.86 gal)
CURB WEIGHT	634 kg (1398 lbs)
TOWING CAPACITY	To come
REAR BOX CAPACITY	150 kg (330 lbs)



**GET IT ALL
THE BEST!**
PRICE, WARRANTY,
FEATURES
& ADVENTURE!

STANDARD FEATURES AND BENEFITS

SAFETY

Passenger hold bar | Side Doors | Lateral mirrors | Horn
ROPS certified Roll Cage | Hand brake | Halogen hi & low beam
Hazard lights | Flashers

LOOK

High quality graphics | Premium glossy paint

CONVENIENCE

Trailer connector | Adjustable & lockable steering | Cup holders
Storage under hood | Glove compartment | Hitch receiver
12V plug | Adjustable driver seat | LX model: Winch (3500 lbs)

DURABILITY

Skid plate | Stainless steel exhaust system | Steel front bumper

LCD DASHBOARD

Digital information center with brightness control, KM/MPH
odometer and a multi-function gauge: RPM, speed, tachometer,
gear position, temperature, engine light, fuel level, hour meter
and a clock.

**PLUS VALUE
OF \$999**

TRANSMISSION

CV-TECH IBC clutch system	Primary and secondary variable transmission Gear box: L / H / N / R / P (parking lock shift system)
POWER TRAIN	2 wheel / 4 wheel drive, electric locking differential



WHEELS

FRONT WHEELS	Aluminium black rims (14 x 7 in)
REAR WHEELS	Aluminium black rims (14 x 8 in)
FRONT TIRES	AT 26 x 9-14 (ABUZZ CST 6 ply rating)
REAR TIRES	AT 26 x 11-14 (ABUZZ CST 6 ply rating)

SUSPENSION AND STEERING

FRONT SUSPENSION	Double wishbone independent suspension Hydraulic shock absorber with 5 spring preload adjustment
TRAVEL	180 mm (7.1 in)
REAR SUSPENSION	Double wishbone independent suspension Hydraulic shock absorber with 5 spring preload adjustment
TRAVEL	170 mm (6.7 in)
STEERING	Rack and pinion LX model: Rack and pinion, Electronic Power Steering (EPS)

BRAKES

FRONT AND REAR BRAKE DISC SYSTEM